JADAVPUR UNIVERSITY

M. TECH THESIS

SmartMedWaste: Medical Waste Management with IoT and Deep Learning

---

A thesis submitted in partial fulfillment of the requirements
for the degree of Master of Technology in Computer Technology (MTCT)

in the

Computer Science and Engineering

by
Sandip Kumar Karmakar
Class Roll No. 002110504010
Examination Roll No. M6TCT24008
Registration No. 160081 of 2021-2022

Under the Guidance of
Prof. Sarbani Roy
Department of Computer Science and Engineering
Jadavpur University
Kolkata-700032.
2024

Department of Computer Science and Engineering
Faculty of Engineering and Technology
Jadavpur University, Kolkata - 700032

CERTIFICATE OF RECOMMENDATION

This is to certify that the work embodied in this thesis entitled **"SmartMedWaste: Medical Waste Management with IoT and Deep Learning"** has been satisfactorily completed by **Sandip Kumar Karmakar** (Registration Number 160081 of 2021 - 2022; Class Roll No. 002110504010; Examination Roll No. M6TCT24008). It is a bonafide piece of work carried out under my supervision and guidance at Jadavpur University, Kolkata, for partial fulfilment of the requirements for the awarding of the **Master of Technology in Computer Technology** degree of the Department of Computer Science and Engineering, Faculty of Engineering and Technology, Jadavpur University, during the academic year 2021 - 2024.

Prof. Sarbani Roy,
Department of Computer Science and Engineering,
Jadavpur University.
(Supervisor)

Forwarded By:

Prof. Nandini Mukhopadhyay,
HOD, Department of Computer Science and Engineering,
Jadavpur University.

Prof. Dipak Laha,
DEAN, Faculty of Engineering and Technology,
Jadavpur University.

Department of Computer Science and Engineering
Faculty of Engineering and Technology
Jadavpur University, Kolkata - 700032

CERTIFICATE OF APPROVAL

This is to certify that the thesis entitled **"SmartMedWaste: Medical Waste Management with IoT and Deep Learning"** is a bonafide record of work carried out by **Sandip Kumar Karmakar** (Registration Number 160081 of 2021 - 2022; Class Roll No. 002110504010; Examination Roll No. M6TCT24008) in partial fulfilment of the requirements for the award of the degree of **Master of Technology in Computer Technology** degree of the Department of Computer Science and Engineering, during the period of September 2021 to May 2024. It is understood that by this approval, the undersigned do not necessarily endorse or approve any statement made, opinion expressed or conclusion drawn therein, but approve the thesis only for the purpose of which it has been submitted.

_____
Signature of Examiner 1
Date:

_____
Signature of Examiner 2
Date:

Department of Computer Science and Engineering
Faculty of Engineering and Technology
Jadavpur University, Kolkata - 700032

DECLARATION OF ORIGINALITY AND COMPLIANCE OF ACADEMIC ETHICS

I hereby declare that the thesis entitled **"SmartMedWaste: Medical Waste Management with IoT and Deep Learning"** contains literature survey and original research work by the undersigned candidate, as a part of her degree of **Master of Technology in Computer Technology, Jadavpur University**. All the information have been obtained and presented in accordance with academic rules and ethical conduct.
I also declare that, as required by these rules and conduct, I have fully cited and referenced all materials and results that are not original to this work.

Name: Sandip Kumar Karmakar

Examination Roll No.: M6TCT24008

Registration No.: 160081 of 2021 - 2022

Thesis Title: SmartMedWaste: Medical Waste Management with IoT and Deep Learning

Signature of the Candidate:

Dedicated to my family, friends and well-wishers
for their endless love, support and encouragement

JADAVPUR UNIVERSITY

Abstract

Computer Science and Engineering

Master of Technology in Computer Technology (MTCT)

SmartMedWaste: Medical Waste Management with IoT and Deep Learning

by Sandip Kumar Karmakar

Pharmaceutical-medical waste management stands as a critical process within hospital organizations, its mishandling potentially leading to hazardous repercussions such as mass infections. Inadequate waste management practices pose a significant threat to environmental health and safety. Addressing this challenge requires the implementation of advanced solutions capable of scientifically managing medical waste within the workplace. This paper introduces an Automated Waste Management System (AWMS) empowered by IoT and deep learning technologies, designed to streamline the classification, treatment, and disposal of biomedical waste. By leveraging cutting-edge technology, our system aims to significantly reduce the time and energy expenditure associated with waste management services while concurrently minimizing waste generation. The proposed system operates through a user-friendly interface, wherein medical waste is deposited into a Garbage Collector Pan (GCP). A ResNeXt deep learning model, integrated into the system, swiftly classifies the waste with an impressive accuracy of 97.93% and directs it to the specialized Trash Collector Bins (TCB) based on its classification. Through this innovative approach, our system not only organizes but also enhances the accuracy of medical waste management, ensuring optimal utilization of resources and preserving environmental integrity. Additionally, the AWMS monitors the fill level of TCB and notifies hospital authorities when bins require emptying, ensuring timely waste disposal and efficient utilization of resources.

Acknowledgements

I extend my heartfelt gratitude to several individuals whose unwavering support and guidance have been instrumental in the successful completion of this thesis project. First and foremost, I would like to express my sincere appreciation to my project supervisor, Prof. Sarbani Roy, whose expertise, encouragement, and invaluable feedback have been pivotal throughout this journey.

I am also deeply thankful to Mr. Asif Iqbal Middya, for his consistent support, insightful suggestions, and dedication to ensuring the project's smooth progress.

A special mention goes to Maqsud Alam Mallick for his support in developing the deep learning model used for waste detection and classification. His technical expertise and assistance were crucial in advancing this aspect of the project.

Additionally, I extend my appreciation to all the faculty members who provided valuable insights and assistance during the course of this project.

Lastly, I am grateful to my family and friends for their unwavering encouragement and understanding throughout this endeavor. Their support has been a constant source of motivation.

Thank you all for your contributions and encouragement.

.....
Sandip Kumar Karmakar
Registration No. 160081 of 2021-2022
Examination Roll No. M6TCT24008
Class Roll No. 002110504010
Dept. of Computer Science & Engineering
Jadavpur University
Kolkata, India

Contents

Certificate of Recommendation ii

Certificate of Approval iii

Declaration Of Originality and Compliance of Academic Ethics iv

Abstract vii

Acknowledgements ix

1 Introduction 1
- 1.1 Problem Overview . . . 1
- 1.2 Motivation . . . 2
- 1.3 Contribution . . . 3
- 1.4 Organization . . . 4

2 Related Works 7
- 2.1 Medical Waste Management Systems . . . 7
- 2.2 Deep Learning for Waste Classification . . . 8

3 Problem Statement and Proposed System 11
- 3.1 Problem Statement . . . 11
- 3.2 Proposed System . . . 12
  - 3.2.1 System Architecture . . . 13
  - 3.2.2 Components and Sensors . . . 17
  - 3.2.3 Circuit Design and Component Integration . . . 18
  - 3.2.4 Deep Learning Model . . . 19
  - 3.2.5 Waste Detection and Classification . . . 21
  - 3.2.6 Robotic Arm Automation . . . 22

4 System Evaluation and Results 25
- 4.1 Experimental Setup . . . 25
- 4.2 Results and Discussion . . . 25

5 Conclusion and Future Work 31

6 Reference 35

List of Figures

3.1 Medical Waste Management System 13
3.2 Medical Waste Detection using IR Sensor 13
3.3 Placing Medical Waste into specialized Trash Collector Bin 14
3.4 Robotic Arm movement after Placing Medical Waste 15
3.5 Data Flow Model 15
3.6 Flowchart for Medical Waste collection, classification, and deposition into specific trash collector bins. 16
3.7 Different Components for Proposed Work (a) Servo Motor (b) Ultrasonic Sensor (c) Node MCU ESP8266 (d) Jumper Wire (e) IR Sensor . . 18
3.8 Integrated Circuit Diagram for Automated Medical Waste Management System 19
3.9 Different Servo Motors for Proposed Work (a) Central Servo Motors (b) Vertical Servo Motors (c) Gripper Servo Motor 23
3.10 Gripper and Depositing Mechanism of Robotic Arm: Precision Handling for Waste Segregation 23

4.1 Confusion Matrix for ResNeXt, ResNet, EfficientNet, ConvNext, and ViT_b_16 model 27
4.2 Time Taken Per Epoch for Different Models 29
4.3 Testing Time for different Models 29

List of Tables

3.1 Model Classification Data Set 20

4.1 Accuracy, Precision, Recall, F1 Score for all the Models 27

List of Abbreviations

AWMS	**A**utomated **W**aste **M**anagement **S**ystem
GCP	**G**arbage **C**ollector **P**an
TCB	**T**rash **C**ollector **B**ins

Chapter 1

Introduction

1.1 Problem Overview

Biomedical waste, generated from a spectrum of medical activities ranging from routine vaccinations to complex therapeutic interventions, presents a significant threat to public health and environmental integrity. This waste encompasses materials such as used needles, syringes, blood, bodily fluids, and laboratory specimens, all of which can be contaminated with infectious agents or hazardous substances. The gravity of this issue cannot be overstated, as improper management of biomedical waste not only endangers healthcare workers and the general public but also exacerbates environmental degradation and facilitates the spread of infectious diseases. The mismanagement of such waste can lead to severe health crises, including outbreaks of diseases like Hepatitis B and HIV, due to accidental needlesticks or exposure to contaminated materials.

Within healthcare facilities, the generation of pharmaceutical waste adds another layer of complexity to the waste management challenge. Pharmaceutical waste, which includes expired medications, unused drugs, and other pharmaceutical products, poses unique risks if not handled properly. Inappropriate disposal methods, such as flushing drugs down the drain or throwing them in regular trash, can lead to environmental contamination, affecting water supplies and wildlife. Moreover, improper handling of pharmaceutical waste can contribute to the growing problem of antimicrobial resistance, where bacteria evolve to withstand drugs, rendering treatments less effective and complicating infection control efforts.

Effective management of biomedical and pharmaceutical waste extends beyond mere collection and disposal; it involves stringent treatment protocols to neutralize hazardous components and the adoption of environmentally sustainable practices to minimize ecological impacts. Traditional waste management methods, while functional to some extent, often lack the efficiency, precision, and scalability required to address the complexities of modern healthcare waste streams. These conventional methods are typically labor-intensive and prone to human error, which can lead to inconsistent waste segregation and increased risk of exposure to harmful substances. This gap in waste management capabilities underscores the urgent need for innovative solutions that can streamline and enhance the waste handling process.

Automated Waste Management Systems (AWMS) offer a promising solution by integrating advanced technologies to automate various stages of waste management, from collection and segregation to treatment and disposal. AWMS can significantly enhance the efficiency and effectiveness of biomedical waste management by reducing the dependency on manual processes and minimizing human error.

These systems utilize sophisticated algorithms and robotics to ensure precise sorting and handling of waste, thereby improving safety and compliance with regulatory standards. However, the widespread adoption of AWMS is hindered by several challenges, including high initial costs, regulatory compliance issues, and the need for specialized training and infrastructure. Addressing these challenges requires a concerted effort from healthcare institutions, regulatory bodies, technology providers, and waste management experts to develop and implement sustainable and resilient waste management practices. By doing so, AWMS can play a crucial role in safeguarding public health, protecting the environment, and ensuring the safety of healthcare workers.

1.2 Motivation

The motivation behind undertaking this study stems from the critical need to address the inadequacies and shortcomings prevalent in current medical waste management practices. Despite being an essential aspect of healthcare operations, existing methodologies exhibit several deficiencies that compromise both efficiency and safety. The reliance on manual sorting processes, in particular, presents significant challenges that necessitate urgent attention and innovative solutions. Current practices not only fail to ensure the proper handling and disposal of medical waste but also expose significant gaps that could lead to severe environmental and public health repercussions. Manual sorting is the cornerstone of many existing medical waste management systems, yet it is inherently flawed due to its labor-intensive nature and susceptibility to human errors. This traditional approach consumes valuable time and resources, often leading to the misclassification and improper disposal of hazardous materials. These inefficiencies are further compounded by the complex nature of medical waste, which includes a diverse range of items such as used needles, syringes, blood, bodily fluids, and laboratory specimens. The manual sorting process struggles to maintain consistency and accuracy, resulting in potential environmental contamination and public health hazards.

Human error is a significant factor that exacerbates the challenges associated with manual waste sorting. Despite the diligent efforts of healthcare workers, the intricate task of categorizing various types of medical waste inevitably leads to mistakes. Misidentification of waste categories and mishandling of potentially infectious materials are common issues that compromise the accuracy of waste segregation. These errors not only threaten the efficacy of the waste management system but also elevate the risk of disease transmission within healthcare facilities and the broader community. The consequences of such mistakes are far-reaching, potentially contributing to the spread of infectious diseases and posing a significant threat to public health. Moreover, the reliance on manual labor for waste management presents considerable risks to the health and safety of healthcare workers. Direct exposure to hazardous materials during sorting and disposal activities increases the likelihood of needlestick injuries, exposure to infectious agents, and other occupational hazards. These risks underscore the vulnerability of frontline healthcare staff, whose well-being and job satisfaction are directly impacted by the lack of a robust waste management system. The physical and psychological toll on these workers highlights the urgent need for improved practices that can safeguard their health and enhance their working conditions.

In light of these challenges, our research aims to address the deficiencies inherent in current medical waste management practices by proposing the integration

of an Automated Waste Management System (AWMS). By leveraging cutting-edge technology to automate the sorting and disposal processes, the AWMS offers a transformative solution that minimizes reliance on manual labor and mitigates the risks associated with human error. The implementation of an AWMS in healthcare facilities can streamline waste management operations, enhance the accuracy of waste segregation, and significantly reduce the potential for occupational hazards. This research seeks to contribute to the improvement of healthcare safety standards, environmental sustainability, and overall public health outcomes by providing a more efficient and reliable system for medical waste management. By addressing the current inefficiencies and risks, the AWMS has the potential to revolutionize medical waste handling, ensuring a safer and more sustainable future for healthcare operations.

1.3 Contribution

This study introduces a groundbreaking solution, SmartMedWaste, designed to revolutionize medical waste management by seamlessly integrating Internet of Things (IoT) technology and deep learning algorithms. The core contribution of SmartMedWaste lies in its ability to automate the classification and segregation of biomedical waste, addressing the limitations inherent in traditional manual sorting practices. Biomedical waste management presents significant challenges due to the diverse nature of waste materials, the risk of contamination, and the need for compliance with stringent regulatory standards. Traditional methods often rely on manual sorting, which is labor-intensive, prone to human error, and inefficient in handling large volumes of waste. These methods can lead to improper segregation, increasing the risk of environmental contamination and exposure to hazardous materials. SmartMedWaste tackles these issues head-on by providing a fully automated system that enhances the accuracy, efficiency, and safety of waste management processes.

SmartMedWaste leverages IoT sensors strategically placed within waste disposal units, enabling real-time data collection on various waste attributes, such as type, volume, and contamination levels. These sensors continuously monitor the status of waste bins, providing a constant stream of data that is crucial for timely and effective waste management. This data is then processed using sophisticated deep learning algorithms, which have been trained on extensive datasets to recognize and categorize different types of medical waste with high accuracy. The deep learning models can identify complex patterns and features in the data, allowing for precise classification of waste materials, thereby reducing the likelihood of misclassification and ensuring proper disposal. The integration of these cutting-edge technologies positions SmartMedWaste as an innovative and comprehensive solution to the challenges posed by existing waste management practices. By automating the classification and segregation process, SmartMedWaste not only reduces the reliance on manual labor but also minimizes the potential for human error, enhancing overall operational efficiency. This automation also ensures compliance with regulatory requirements, as the system can be configured to adhere to specific waste management protocols and standards. Key Features of SmartMedWaste include:

- **IoT-enabled Real-time Monitoring**

  Utilizes advanced IoT sensors to continuously monitor parameters like fill levels and waste composition, providing real-time data for optimizing waste management processes. This feature ensures timely intervention and efficient resource utilization.

- **Deep Learning for Automated Classification**

  Employs deep learning algorithms trained on vast datasets to autonomously and accurately classify diverse types of medical waste, reducing manual intervention and errors. The high accuracy of these algorithms ensures reliable segregation of waste materials.

- **Customizable Configuration** Offers extensive customization options for settings, thresholds, and parameters, ensuring seamless integration into diverse healthcare facility workflows and compliance with regulatory mandates. This adaptability allows the system to meet the specific needs of various medical environments.

- **Automated Data Analytics and Reporting** Incorporates robust data analytics tools that process collected data to generate actionable insights and comprehensive reports, aiding in regulatory compliance and operational efficiency. These analytics help in tracking waste generation patterns and improving waste management strategies.

- **Remote Management and Alerts** Supports remote management capabilities and real-time alerts for critical issues, enhancing the reliability and responsiveness of the waste management process. This feature allows for proactive management and swift resolution of any potential problems.

Overall, the key features of SmartMedWaste collectively contribute to its transformative impact on biomedical waste management practices. By harnessing the capabilities of IoT and deep learning technologies, SmartMedWaste not only enhances operational efficiency and accuracy but also promotes sustainability, safety, and regulatory compliance within healthcare facilities. As a pioneering solution, SmartMedWaste sets a new standard for excellence in healthcare waste technology, driving innovation and progress in the field for years to come.

1.4 Organization

This thesis presents a comprehensive exploration of SmartMedWaste, an innovative solution for medical waste management. The structure of the paper is designed to guide the reader through the research process, from background and problem identification to system implementation and evaluation. This thesis paper is organized as follows.

- **Chapter 2: Related Works**

  This chapter reviews existing literature on medical waste management systems and explores the application of deep learning for waste classification. It provides a comprehensive background, highlighting previous research efforts and identifying gaps that the current study aims to address.

- **Chapter 3: Problem Statement and Proposed System**

  This chapter outlines the key issues in medical waste management, including human error in waste sorting, inefficiency in waste management, health risks to workers, and the lack of real-time monitoring. It then introduces the proposed system, detailing its architecture, the deep learning model used for waste detection and classification, and the robotic arm automation.

- **Chapter 4: System Evaluation and Results**

  This chapter presents a comprehensive evaluation of the proposed system, discussing the results and performance metrics that demonstrate its effectiveness. The evaluation highlights the system's accuracy, efficiency, and potential impact on improving medical waste management practices.

- **Chapter 5: Conclusion and Future Work**

  The final chapter concludes the thesis by summarizing the findings and contributions of this research. It also discusses potential future work to enhance and expand the capabilities of the system, suggesting directions for further research and development.

This structured approach ensures a clear and logical flow of information, guiding the reader through the development, implementation, and evaluation of the SmartMedWaste system, and highlighting its significance in advancing medical waste management practices.

Chapter 2

Related Works

2.1 Medical Waste Management Systems

The implementation of an IoT-based biomedical waste classification, quantification, and management system at its source, where color-coded bags are marked with RFID tags and bins equipped with weighing sensors, represents a significant step towards automation and efficiency [1]. However, despite these advancements, there remains a requirement for human intervention in the generation of colour-coded bags. To address this need for human involvement and further streamline the waste management process, our system seamlessly integrates with the aforementioned setup. Our solution focuses on automating the classification and segregation of biomedical waste, thereby reducing reliance on manual intervention and enhancing overall efficiency.

Wawale et al. [2]developed an IoT Tracked and Fuzzy Classified Integrated System which involves manual fuzzy classification of color-coded bags based on four parameters ie. Cost, health, biodegradability, and environmental effect. After classification, the IoT tracker system monitors the waste both indoors and outdoors and ensures proper treatment procedures based on fuzzy classification. However, IoT Tracked and Fuzzy Classified Integrated System is only used as a tracking system and, hence, lacks the means to segregate or classify waste by itself. Our proposed system can be used along with it to overcome it, as our system is only a segregation system with real-time data collection.

The article [3] reviews the use of IoT in medical waste management, highlighting its potential to revolutionize traditional procedures and contribute to environmental sustainability. While IoT-based waste bin sensors offer real-time monitoring capabilities, current applications are limited to specific stages of the waste management process. However, these fragmented approaches may overlook holistic waste management needs. Our system overcomes this limitation by integrating IoT, robotic hands, and deep learning, enabling comprehensive monitoring from waste generation to disposal. This ensures efficient waste classification and disposal, addressing the shortcomings of fragmented monitoring approaches and enhancing overall waste management effectiveness.

Wijaya et al. [12] developed a smart waste-bin designed to manage waste in smart city projects. The system comprises sensors that measure the weight and level of waste inside the bin. It adapts to the network environment to manage all waste management information. The main concept of smart waste management is to handle all city waste and monitor the entire process. A smart waste-bin consists of a smart sensor and smart communication units, including a Bluetooth and GSM module for data transmission, and a mobile application and web-based monitoring interface for communication with the waste department.

The smart bin is equipped with sensor nodes mounted on it [13, 14] for data collection and transmission. These sensors are divided into two paths: the first path uses level sensors to monitor the waste-bin's fill level, and the second path employs smart load cell sensors to calculate the waste's weight [15, 16]. The system collects accurate real-time data, which can be used as input for a management system [17]. The load cell calibration approach simplifies the calibration process, allowing it to be attached to commonly used waste bins without modification.

Efficient waste disposal or management systems for managing garbage within smart cities [21] are essential for modern smart cities (MSC). The Internet of Things (IoT) [24] can be implemented in both IS and MSC, creating a highly developed proposal for future operations. Special methods enhance the technology used for high-quality service (QoS) in waste management systems. Specifically, IoT components like sensors, detectors, and actuators are integrated into intelligent systems (IS) and inspection systems for efficient waste management. An automated alert-based smart bin or garbage collection system [22, 23] alerts authorities, like corporations or local waste disposal teams, to increase efficiency and notify higher officials. A new system was implemented using a GSM modem, a microcontroller, and an ultrasonic sensor [18]. The ultrasonic sensors detect the distance of the waste from the top of the bin. Once the bin is full, the GSM modem sends a message to the owner to empty the bin.

Smart bins built on the Arduino board platform [20] are interfaced with a GSM modem and equipped with an ultrasonic sensor (HC-SR04). The bin features a buzzer and LEDs to display the waste levels. Three LEDs indicate different waste levels in the bin: green for empty and red for full. When the bin is full, the buzzer beeps three times to prevent further waste disposal. This mechanism controls overflowing bins. Users receive a message indicating that the dustbin must be emptied, sent via the GSM modem to multiple recipients simultaneously. Integrating many bins, each with a unique ID, can be achieved by implementing IoT principles and creating a database for each bin using SQL technology [19]. A login webpage ensures authorized entries. Further enhancements could include developing an automated system capable of picking up waste in and around the bin, segregating it, and placing it in respective bins.

Our Medical Waste Management System, SmartMedWaste, surpasses these existing systems by integrating IoT and advanced deep learning algorithms specifically trained on biomedical waste. Unlike traditional smart bins, SmartMedWaste provides real-time data collection on various waste attributes and uses sophisticated algorithms for accurate waste classification and segregation. This reduces human error, enhances operational efficiency, and minimizes health risks to workers. Additionally, SmartMedWaste offers customizable configurations to cater to different healthcare facilities, making it a more versatile and efficient solution for medical waste management.

2.2 Deep Learning for Waste Classification

The Article [4] outlines the pressing need for efficient medical waste classification amid the exponential growth of healthcare facilities. It underscores the challenge of manual waste segregation and proposes a deep learning-based solution. By leveraging pre-trained models and transfer learning techniques, the proposed method aims to achieve accurate classification of medical waste types. The objective is to streamline the process and minimize waiting times, ensuring proper disposal to prevent

contamination. Results indicate that three out of four modified pre-trained models achieved 95% accuracy, demonstrating the viability of the approach. Our implementation of ResNeXt for medical waste classification achieved an impressive accuracy of 97.93%, highlighting its efficacy in accurately categorizing diverse types of medical waste. Compared to traditional Convolutional Neural Networks (CNNs), ResNeXt offers superior performance due to its multi-branch architecture and concise design principles. The ResNeXt architecture leverages grouping transformations, reducing design complexity while maintaining high accuracy. Additionally, ResNeXt's utilization of bottleneck structures and aggregate transformations enables efficient feature extraction and classification, resulting in enhanced accuracy compared to standard CNNs. Overall, ResNeXt emerges as a robust and efficient solution for medical waste classification, outperforming traditional CNNs and providing a promising avenue for automated waste management systems.

Malik et al. [5] developed a waste classification using deep learning techniques, focusing on EfficientNet-B0 architecture. The proposed method involves tuning the model for region-specific waste images, achieving comparable accuracy to larger models like EfficientNet-B3 with significantly fewer parameters. The approach aims for efficiency gains in terms of FLOPS while improving classification performance through fine-tuning on region-specific data. The study's reliance on a single architecture (EfficientNet-B0) limits the exploration of other potentially more effective models for waste classification. Additionally, while the fine-tuning approach shows promise, it may not fully capture the complexity and variability of waste images across different regions, potentially leading to suboptimal classification performance in certain cases. ResNeXt addresses the limitation of relying solely on a single architecture by offering a more diverse and scalable approach. Unlike traditional convolutional neural networks (CNNs), ResNeXt introduces a cardinality parameter, allowing for the incorporation of multiple paths or "cardinality" within each network block. This increased flexibility enables ResNeXt to capture a broader range of features and patterns, making it more adaptable to different datasets and potentially more effective for waste classification tasks. By leveraging ResNeXt, researchers can explore a wider range of architectural variations, leading to improved performance and robustness in waste classification models.

On the other hand, Robotic Arm Automation using IoT and Deep Learning Model in Medical Waste Management Systems plays a crucial role in enhancing efficiency, accuracy, and safety in waste disposal processes. By integrating IoT sensors and deep learning algorithms, the system can automate waste classification and segregation tasks, reducing the reliance on manual labor and minimizing the risk of human error. The IoT sensors provide real-time data on waste attributes, allowing the deep learning model to accurately classify biomedical waste types.

Firstly, Aral et al. [25] employed transfer learning models derived from several well-established CNN architectures for image classification, including DenseNet121, DenseNet169, InceptionResNetV2, MobileNet, and Xception, to classify trash within the Trashnet dataset. In their experiments, the researchers used 70% of the Trashnet dataset for training, 13% for validation, and 17% for testing. They selected a batch size of 8 and an input size of 224×224 pixels. According to the experimental results, the transfer learning model based on DenseNet121 achieved the highest accuracy, reaching 95%. Therefore, we reimplemented and evaluated this model with the aforementioned settings, referring to it as the Densenet121 Aral model in our study. In 2016, Yang and Thung [26] introduced the Trashnet dataset, comprising six distinct categories: glass, paper, cardboard, plastic, metal, and general trash. This dataset includes images captured using various mobile devices such as the Apple

iPhone 7 Plus, Apple iPhone 5S, and Apple iPhone SE. Detailed descriptions of this dataset will be provided in the next section. Numerous studies addressing the trash classification problem [25–27] have utilized the Trashnet dataset to evaluate their proposed methodologies, which are summarized as follows.

Next, Bircanoglu et al. [28] developed a lightweight convolutional neural network model named RecycleNet for trash classification. Although RecycleNet achieved an accuracy of only 81% on the Trashnet dataset, with 70% of images for training, 13% for validation, and 17% for testing, it significantly reduced the time complexity by decreasing the number of parameters from seven million to three million. Consequently, RecycleNet is an appropriate model for systems with hardware constraints, offering a balance between performance and computational efficiency. Then, Ruiz et al. [27] assessed the performance of several CNN models, including VGG, Inception, and ResNet, for automatic trash classification. In this study, the authors utilized 80% of the Trashnet dataset for training, 10% for validation, and the remaining 10% for testing. The best performance was achieved using a ResNet-based architecture, which obtained an average accuracy of 88.66% on the Trashnet dataset. In our experiments, we reimplemented this approach, designating it as ResNet Ruiz.

In addition to these specific methods developed for trash classification, several other prominent CNN models, such as ResNeXt [29], ImageNet [30], VGG [31], ResNet [32], and DenseNet [33], have been used for general image classification tasks and can be adapted for trash classification. Among these models, our research identified ResNeXt as the most effective for transfer learning in classifying trash. Therefore, we enhanced this model by applying transfer learning techniques to propose a robust deep neural network model for trash classification.

Our Medical Waste Management System, SmartMedWaste, surpasses these existing systems by integrating IoT technology and advanced deep learning algorithms specifically trained on biomedical waste. Unlike conventional smart bins, SmartMedWaste provides real-time data collection on various waste attributes and employs sophisticated algorithms for precise waste classification and segregation. This approach minimizes human error, enhances operational efficiency, and reduces health risks to workers. Furthermore, SmartMedWaste offers customizable configurations to meet the diverse needs of different healthcare facilities, making it a more versatile and effective solution for medical waste management. ResNeXt provides a superior and more efficient solution compared to existing systems due to its enhanced capability to leverage transfer learning for accurate waste classification. By utilizing ResNeXt's advanced feature extraction capabilities, our system achieves higher accuracy and efficiency in categorizing medical waste. This ensures precise waste segregation, which is crucial for mitigating health risks and environmental impact. The integration of ResNeXt within SmartMedWaste demonstrates how advanced neural network architectures can significantly improve the performance and reliability of waste management systems, particularly in the context of medical waste.

Chapter 3

Problem Statement and Proposed System

In this chapter, the challenges and key issues of biomedical waste management will be discussed. These include human error in waste sorting, inefficiency in waste management, health risks to workers, and the lack of real-time monitoring. We will then explore how our proposed system, SmartMedWaste, addresses these critical issues by introducing an innovative solution that leverages IoT and deep learning technologies. Following this, we will delve into the system architecture, detailing the required components and sensors essential for creating this proposed system. Next, we will explain the deep learning model, including a thorough description of the dataset, pre-processing techniques, and the application of transfer learning. Finally, we will discuss waste detection and classification, emphasizing how the robotic arm receives instructions based on classification results and performs precise grasping and placement of waste items into designated bins.

3.1 Problem Statement

The management of biomedical waste in healthcare facilities presents a complex set of challenges that significantly impact public health, environmental integrity, and the safety of healthcare workers. One of the most pressing issues is human error in waste sorting, which occurs when healthcare workers manually classify and dispose of various types of medical waste. This process is not only time-consuming but also highly prone to mistakes. Misclassification can lead to improper disposal methods, resulting in the contamination of waste streams that should be handled separately. For example, mixing infectious waste with general waste can increase the spread of infectious diseases, posing severe risks to both healthcare workers and the broader community. The manual nature of this process also means that workers are continually exposed to potentially hazardous materials, increasing the likelihood of accidents and infections.

Another critical issue is the inefficiency inherent in current waste management practices. Manual sorting and disposal processes are labor-intensive and time-consuming, often leading to prolonged sorting times and higher operational costs. The need for extensive labor not only increases costs but also introduces variability in the sorting process, as different workers may sort waste differently. This inconsistency can further compromise the effectiveness of waste management systems, leading to an increased risk of environmental contamination and non-compliance with regulatory standards. Inefficient waste management practices also contribute to the accumulation of waste in healthcare facilities, exacerbating the risks of contamination and

disease transmission. The inefficiencies can delay the removal of hazardous waste, creating unsafe conditions within healthcare environments.

Healthcare professionals involved in the manual sorting of biomedical waste face significant health risks due to their exposure to hazardous materials, such as contaminated needles, sharp objects, and bodily fluids. This direct contact with dangerous waste items not only poses immediate threats, such as needle-stick injuries and infections but also has long-term health implications, including chronic infections and other occupational diseases. The physical and psychological toll on healthcare workers in such high-risk environments can be substantial, leading to increased absenteeism, decreased job satisfaction, and higher turnover rates. This situation underscores the need for safer, more reliable waste management systems that can protect workers from these hazards and create a healthier working environment.

A notable deficiency in existing biomedical waste management systems is the lack of real-time monitoring capabilities. Without real-time data, it is challenging to manage waste levels effectively, leading to issues such as overfilled waste containers, which can become breeding grounds for pathogens and pests. Real-time monitoring would enable healthcare facilities to track waste generation patterns, predict when bins will be full, and schedule timely waste collection, thereby preventing overflow and reducing the risk of contamination. The absence of such monitoring also means that healthcare facilities cannot quickly adapt to changing waste management needs, resulting in inefficient resource utilization and increased operational costs. This gap highlights the need for advanced technological solutions that can provide real-time insights and enhance decision-making processes.

In light of these critical issues, there is an urgent need to modernize medical waste management practices with innovative solutions that leverage contemporary technologies. SmartMedWaste emerges as a transformative solution that addresses these challenges by introducing a state-of-the-art automated system powered by IoT and deep learning technologies. By replacing manual sorting with automated classification and segregation, SmartMedWaste mitigates the risks of human error, enhances operational efficiency, and ensures a safer working environment for healthcare professionals. The imperative for SmartMedWaste underscores the necessity to align medical waste management practices with technological advancements to safeguard public health, reduce operational costs, and promote sustainable healthcare practices.

3.2 Proposed System

In this section, we will discuss the system architecture of the proposed SmartMedWaste system (As shown in Fig: 3.1), which integrates various components such as IR sensors, Node-MCU microcontrollers, a camera module, and a robotic arm equipped with servo motors to automate the classification, segregation, and disposal of medical waste. At the core of the system is a deep learning model, specifically the ResNeXt architecture, which processes and analyzes high-resolution images of waste to accurately identify and classify different types of medical waste. This classification data is then used to direct the robotic arm to precisely collect and deposit the waste into designated bins. Additionally, the system employs ultrasonic sensors to monitor the fill levels of waste bins and communicate with a centralized server for timely waste disposal notifications.





FIGURE 3.1: Medical Waste Management System

3.2.1 System Architecture

The SmartMedWaste system architecture is designed to revolutionize medical waste management practices through seamless integration of various components, each playing a crucial role in automating waste classification, segregation, and disposal processes. At the core of the system is the Garbage Collector Pan, where users deposit medical waste to initiate the waste management cycle (As shown in Fig: 3.5 and Fig: 3.6). Upon waste deposition, an IR Sensor is activated to detect the presence of waste (As shown in Fig: 3.2) within the pan. This sensor serves as the initial trigger for the subsequent steps in the process. The Controller, upon receiving the signal, activates the Camera Module to capture high-resolution images of the medical waste within the garbage collector pan. These images serve as crucial visual data for waste classification and segregation.



IR Sensor Color before detecting any Object

IR Sensor Color after detecting any Object

FIGURE 3.2: Medical Waste Detection using IR Sensor

Once the IR Sensor detects waste (As shown in Fig: 3.5.1), it sends a signal to the

Node-MCU (Microcontroller Unit), which acts as the central communication hub of the system. Equipped with a WiFi module, the Node-MCU receives signals (As shown in Fig: 3.5 and Fig: 3.6) from the sensor and transmits data regarding the presence of medical waste to the Controller, which houses the Deep Learning Model. The Controller, upon receiving the signal, activates the Camera Module (As shown in Fig: 3.5 and Fig: 3.6) to capture (As shown in Fig: 3.5.2) high-resolution images of the medical waste within the garbage collector pan. These images serve as crucial visual data for waste classification and segregation.

The captured image data is then processed and analyzed by the Deep Learning Model within the Controller (As shown in Fig: 3.5 and Fig: 3.6). Leveraging sophisticated deep learning algorithms, the model identifies and classifies the type of medical waste present in the garbage collector pan. Additionally, it determines the precise coordinates of the waste, facilitating the subsequent manipulation by the Robotic Arm.

The Robotic Arm is activated based on the coordinates and waste classification data provided by the Deep Learning Model. It rotates and positions itself to collect (As shown in Fig: 3.5.3) the identified medical waste from the garbage collector pan. Once collected, the Robotic Arm deposits the waste into specialized Trash Collector Bins (TCB) (As shown in Fig: 3.3 and 3.5.4), each designated for different types of medical waste, such as bottles, tablets, syringes, etc. After depositing the medical waste into the designated trash collector bin, the robotic arm will autonomously rotate back to its initial position (As shown in Fig: 3.4 and Fig: 3.6).




FIGURE 3.3: Placing Medical Waste into specialized Trash Collector Bin

Furthermore, the SmartMedWaste system incorporates Ultrasonic Sensors within the Medical Waste Specific Dustbins to monitor fill levels (As shown in Fig: 3.1 and 3.5.5). These sensors detect when a dustbin approaches capacity and send signals to the Node-MCU for further action. The Node-MCU communicates with a centralized server to relay information regarding the fill levels of dustbins. The server processes this data and notifies hospital authorities (As shown in Fig: 3.5.6). when dustbins require emptying, ensuring timely waste disposal and efficient utilization of resources.

SmartMedWaste system architecture seamlessly integrates sensors, deep learning algorithms, robotic manipulation, and centralized communication to automate and optimize medical waste management processes. By minimizing human intervention, enhancing efficiency, and promoting sustainable practices, SmartMedWaste represents a significant advancement in healthcare waste technology with the potential to revolutionize waste management practices in healthcare facilities.




FIGURE 3.4: Robotic Arm movement after Placing Medical Waste




FIGURE 3.5: Data Flow Model




FIGURE 3.6: Flowchart for Medical Waste collection, classification, and deposition into specific trash collector bins.

3.2.2 Components and Sensors

- **Servo Motor:** A TowerPro SG92R Mini Servo Moto (As shown in Fig: 3.7.a) is an essential electrical device utilized for precise object manipulation and rotation. Operating through servo mechanism, it exhibits exceptional precision in pushing or rotating objects to specific angles or distances. There are two main types: DC servo motors, powered by DC current, and AC servo motors, powered by AC current. Despite their simplicity, servo motors offer high torque in compact, lightweight packages, making them ideal for various applications such as robotics, toy vehicles, and machinery. The servo motor's capability to rotate between 0 to 180 degrees is utilized in the Robotic Arm to grab and place medical waste into the designated trash collector bins. Its high precision ensures accurate placement of the waste. The position of a servo motor is controlled by electrical pulses, with its circuitry typically integrated alongside the motor for efficient operation.

- **Ultrasonic Sensor:** Ultrasonic sensing represents a reliable method for proximity detection and level measurement, offering high accuracy and versatility in diverse environments. An HC-SR04 Ultrasonic Sensor operates by emitting ultrasonic sound waves towards a target object and detecting the reflected sound, converting it into an electrical signal. Ultrasonic sensor (As shown in Fig: 3.7.b) utilizes piezoelectric crystals to generate ultrasonic waves and consist of a transmitter to emit the waves and a receiver to detect them after reflection. Ultrasonic sensors excel in measuring distances beyond the range of audible sound, finding widespread application across industries for tasks such as object detection, distance measurement, and obstacle avoidance. These sensors are placed in the Medical Waste Specific Dustbins to monitor fill levels. They detect when a dustbin is approaching capacity and send a signal to the NodeMCU for further action.

- **NodeMCU:** NodeMCU (As shown in Fig: 3.7.c), an open-source firmware, is a pivotal component for IoT (Internet of Things) applications, offering seamless integration with Wi-Fi networks and robust microcontroller capabilities. Its name derives from "node" and "MCU" (microcontroller unit), signifying its role as a node in interconnected IoT systems. The ESP8266 NodeMCU CP2102 board features the ESP8266 chip, designed to cater to the demands of the connected world. With built-in Wi-Fi networking capabilities and ample processing power and storage, the NodeMCU facilitates rapid prototyping and development of IoT solutions. It acts as the central communication hub, receiving signals from sensors (IR, Ultrasonic) and transmitting data to the Controller. The GPIO pins enable easy integration with other components, facilitating efficient communication and data processing.

- **Jumper Wires:** Jumper wires (As shown in Fig: 3.7.d) are indispensable tools for circuit prototyping, facilitating quick and easy connections between components without the need for soldering. These wires feature connector pins at each end, enabling them to bridge connections on breadboards and other prototyping platforms effortlessly. They play a crucial role in modifying circuits, diagnosing issues, and configuring circuit settings, offering flexibility and convenience in circuit design and troubleshooting. They are essential for connecting all components, such as connecting the IR Sensor, Ultrasonic Sensor, Servo Motor, and NodeMCU. Different types of jumper wires are used to

ensure all connections are securely made, allowing for efficient circuit design and troubleshooting.

- **IR Sensor:** Infrared light-emitting diodes (IR LEDs) are specialized LEDs designed to emit infrared rays within a wavelength range typically spanning from 700 nm to 1 mm. However, the specific wavelength emitted can vary between different IR LEDs, analogous to how traditional LEDs produce light of various colors. IR sensors (As shown in Fig: 3.7.e), on the other hand, leverage infrared technology to detect objects or alterations within the environment. These sensors possess the capability to detect an extensive array of physical properties, including temperature, motion, and proximity, through the interpretation of infrared radiation. REES52 IR Infrared Sensor is placed in the Garbage Collector Pan to detect the presence of medical waste. When waste is detected, it sends a signal to the NodeMCU, initiating the subsequent steps in the waste management process.





FIGURE 3.7: Different Components for Proposed Work (a) Servo Motor (b) Ultrasonic Sensor (c) Node MCU ESP8266 (d) Jumper Wire (e) IR Sensor

3.2.3 Circuit Design and Component Integration

The circuit diagram(As shown in Fig: 3.8) for the SmartMedWaste system integrates several key components to automate the detection, classification, and disposal of medical waste. The central hub of this system is the NodeMCU (ESP8266), which is responsible for communication and control. It is powered by a 3.3V power source, with its ground connected to the common ground (GND). The IR Sensor (REES52) and Ultrasonic Sensor (HC-SR04) are powered by a 5V battery source, with their VCC pins connected to the positive terminal of the battery and their ground pins connected to the common ground. The Ultrasonic Sensor's echo pin is connected to a digital input pin (D2) on the NodeMCU, and its trig pin is connected to a digital output pin (D1). This configuration allows the NodeMCU to calculate the distance based on the time taken for the ultrasonic waves to return, thus determining the fill level of the bins. The IR Sensor's OUT pin, which detects the presence of medical waste, is connected to a digital input pin (D0) on the NodeMCU. This setup enables the IR Sensor to signal the NodeMCU when waste is detected, initiating the waste management process. Additionally, four Servo Motors (TowerPro SG90) are used for the Robotic Arm, each connected to a PWM-capable pin on the NodeMCU. Specifically, the servo motors are connected to digital pins D3, D4, D7, and D8 on the NodeMCU. These servo motors are powered by a 5V battery source, with their ground pins connected to the common ground. This configuration allows

precise control of each servo motor's position between 0 and 180 degrees, enabling the Robotic Arm to accurately grab and place the medical waste into the designated bins. Jumper wires (male-to-male, male-to-female, and female-to-female) are used extensively to make secure and reliable connections between the components and the NodeMCU, ensuring the system operates smoothly and efficiently.



1 - Central Servo Motor
2 and 3 - Vertical Servo Motors
3 - Gripper Servo Motor

FIGURE 3.8: Integrated Circuit Diagram for Automated Medical Waste Management System

3.2.4 Deep Learning Model

The Deep Learning Model outlined in the provided information utilizes the ResNeXt architecture for waste detection and classification. It preprocesses RGB images of biomedical waste, standardizing them to 256x256 dimensions. The ResNeXt architecture employs concise design principles, leveraging multiple modules with shared hyperparameters for efficient processing. Transfer learning is utilized, fine-tuning the model on a dataset comprising various biomedical waste items. With robust training and testing, the model achieves a high accuracy of 97.93%, ensuring precise waste segregation for effective biomedical waste management.

- **Data-set description**

  The dataset consists of RGB photos from four distinct classifications: used bandages, used syringes, medical scissors, and other biomedical waste items.

These images were gathered from various image search engines, including Google Images and Bing Images, resulting in a diverse collection with no standardized dimensions. The image sizes range from 100x100 to 500x500 pixels. To facilitate model training, the dataset was divided into ten sections. Nine-tenths of the data were utilized for training the deep learning model, while the remaining one-tenth served as the test set to evaluate the model's performance. The specific figures for the dataset are detailed in Table 3.1.

Class	Number of Images
Syringe	476
Scissors	440
Wasted Medicine	588
Wool	572

TABLE 3.1: Model Classification Data Set

- **Pre-processing**

  Since the images are all of the varied sizes, we need some preprocessing before they are usable. We apply a resize so that all of them are at uniform 256x256 dimensions. This is followed by a center crop reducing image shape to 224x224. Finally, we normalize the image data with mean=0.485, 0.456, 0.406, std = 0.29, 0.224, 0.255 for the three channels respectively. Our batch size is 4.

- **Architecture**

  We are using the ResNext architecture for our deep model. ResNeXt follows the principle of concise design. Multiple modules with the same structure are repeatedly divided, and each module aggregates the grouping transformation of the same topology. This simple design produces a homogeneous, multi-branch architecture, which requires only a few hyperparameters.

  Each module of ResNeXt follows two simple rules: (i) if generating feature maps of the same size, the modules share the same hyperparameters (ii) each time the feature map is downsampled by 2 times, the width of the module is multiplied by 2 times. The second rule ensures that the calculation complexity of FLOP (floating-point operations, multiply–add operations) is approximately the same for all blocks. Using these two rules, we only need to design a template module to determine all modules in the network accordingly. Therefore, these two rules greatly reduce design complexity, allowing us to focus on some key factors. A neuron is the basic unit of an artificial neural network.

  It mainly performs inner product operations, that is, nonlinear transformation completed by a fully connected layer and a convolutional layer. In simple terms, the inner product operation can be viewed as a combination of the three operations of splitting, transforming, and aggregating.

  (i) splitting: decompose the input vector x into lowdimensional embeddings. Generally, each low-dimensional embedding corresponds to a one-dimensional subspace x_i.

  (ii) transforming: transform the low-dimensional embedding obtained by decomposition, that is, multiply the weight w_i to get $w_i x_i$.

  (iii) aggregating: the transformations in all embeddings are aggregated by $\sum Di = 1$. Formally, we present aggregated transformations as: $F(x) = \sum ki =$

$1 \times i$ where $T_(x)$ can be an arbitrary function. In ResNeXt, it is best to use a network instead of the basic transformation ($w_i x_i$).

Broadly speaking, transformation is not limited only to a function; it can also be a network, that is, a "Network-in-Neuron" structure. Similar to a simple neuron, Ti should project x into an (optionally low-dimensional) embedding and then transform it. C is the size of the transformation set to be aggregated, and we refer to C as cardinality. All T_i have the same topology. We set each transformation T_i as a bottleneck structure.

Thus, the first 1*1 layer of each Ti produces low-dimensional embedding. We converted the aggregate transformation into a residual function: $y = x + \sum Ci = 1T_i(x)$ where y is the output. The result of determining whether an item was medical waste was outputted in principal binary. The cross-entropy loss function for input was reasonable from the perspective of classification.

- **Transfer Learning**

  Image or medical examination classification is one of the first fields where deep learning has made a significant contribution. In medical examination classification, one or more images are usually used as input, and a single diagnostic result is used as output (for example, whether there is a disease). In this scenario, each diagnosed case is a sample. Compared with data sets in the field of computer vision, data sets for medical examinations usually have a small sample size (hundreds vs. thousands and millions of samples). Transfer learning is required to meet the needs of deep learning for large data sets.

In practical applications, the following two transfer learning strategies are often used: (1) Using a pre-trained network without modification as a feature extractor. (2) Fine-tuning a network trained with medical data. The advantage of the former strategy is that there is no need to train a deep network and the extracted features are directly input into the existing image analysis process. Both strategies are popular and have been widely used. But as far as we are aware, using only a pre-trained network as a feature extractor has not yet achieved similar results. In this implementation, we also used the later pre-training strategy to implement our model.

3.2.5 Waste Detection and Classification

The waste detection and classification process involves capturing images of biomedical waste using a camera module, followed by analysis and classification utilizing a deep learning model. This section outlines the methodology, performance metrics, and significance of accurate waste segregation in the context of our study. Once camera module captures RGB images of biomedical waste items placed in designated collection units. These images are then fed into the deep learning model for analysis and classification. Given the variability in image size and orientation, preprocessing techniques are employed to standardize the input data, ensuring consistency and reliability in model predictions. Our study utilizes the ResNeXt architecture for waste classification. The model is trained on a diverse dataset comprising images of used bandages, syringes, medical scissors, and other biomedical waste items. The training process involves multiple epochs with predefined hyperparameters, optimizing the model's ability to accurately classify waste items. The training was conducted over 20 epochs to enhance the model's learning and generalization capabilities.

Following the training phase, the model's performance was rigorously tested (Discussed in Chapter 4). The observed accuracy was recorded at 97.93%, indicating a high level of precision in waste classification. Additionally, precision (98.01%), recall (97.93%), and F1 score (97.97%) metrics were calculated to provide a comprehensive assessment of the model's performance. These metrics highlight the robust and reliable classification abilities of the ResNeXt model across multiple evaluation criteria.

Accurate waste segregation is paramount in medical waste management to mitigate risks to public health and the environment. Precise classification ensures that hazardous biomedical waste, such as used syringes or contaminated materials, is properly identified and disposed of, minimizing the risk of infections and environmental contamination. Additionally, precise waste segregation enables efficient resource allocation and disposal procedures, reducing operational costs and promoting sustainable waste management practices. The waste detection and classification process utilizing deep learning technology offers a reliable and efficient approach to biomedical waste management. By achieving high levels of accuracy and precision in waste segregation, our study contributes to enhancing safety, sustainability, and efficiency in healthcare waste disposal practices. This technological advancement ensures that biomedical waste is managed effectively, protecting both public health and the environment.

3.2.6 Robotic Arm Automation

Robotic arm automation is a pivotal component of the waste management process, facilitating the precise manipulation and disposal of waste items based on classification results obtained from the deep learning model. This section delves into the intricate workings of the robotic arm, detailing its functionalities, servo motors, and the process of grasping and placing waste items into designated bins.

- **Instruction Reception and Execution**

  Upon receiving classification results from the deep learning model, the robotic arm controller interprets the data and generates movement commands for the servo motors. These instructions dictate the positioning and movement required to grasp and deposit waste items accurately.

- **Functionality and Servo Motors**

  The robotic arm is equipped with four servo motors (As shown in Fig: 3.9), each serving a distinct function in facilitating precise movement and manipulation:

  1. **Central Servo Motor:** Responsible for rotating the robotic arm horizontally, allowing it to sweep across the waste disposal area from left to right and vice versa.

  2. **Vertical Servo Motors:** Two servo motors enable vertical movement, controlling the arm's elevation and descent. This functionality allows the arm to adjust its height and reach different levels of waste containers.

  3. **Gripper Servo Motor:** Positioned at the top end of the robotic arm, this servo motor controls the gripping mechanism. It opens and closes the gripper, enabling the arm to securely grasp waste items of varying shapes and sizes.

- **Grasping and Placement**




FIGURE 3.9: Different Servo Motors for Proposed Work (a) Central Servo Motors (b) Vertical Servo Motors (c) Gripper Servo Motor

Using the coordinated movement of servo motors, the robotic arm maneuvers into position above the waste item to be collected. The gripper mechanism, operated by the gripper servo motor (As shown in Fig: 3.10.a), securely holds the waste item without causing damage or slippage.

Once securely grasped, the arm moves (As shown in Fig: 3.10.b) to the designated bin corresponding to the waste category identified by the deep learning model. With precise control and alignment, the arm carefully deposits the waste item into the appropriate receptacle, ensuring accurate segregation and disposal.

After depositing the medical waste into the designated trash collector bin, the robotic arm autonomously rotates back to its initial position (As shown in Fig: 3.3). It then waits for another instruction and classification results from the deep learning model, ready to execute movement commands for the servo motors. This seamless process ensures efficient waste management and contributes to the overall sustainability of the system.




FIGURE 3.10: Gripper and Depositing Mechanism of Robotic Arm: Precision Handling for Waste Segregation

- **Enhanced Detail: Integration with Image Processing**

To enhance efficiency and accuracy, the robotic arm's operation can be integrated with image processing techniques. By analyzing real-time images of the waste disposal area, the system can identify the exact location of waste items and optimize the robotic arm's movements for efficient collection.

Robotic arm automation revolutionizes waste management by providing precise, efficient, and safe handling of waste items. Through the integration of advanced servo motors, gripper mechanisms, and intelligent control systems, the robotic arm streamlines the process of waste collection and disposal, contributing to enhanced efficiency and environmental sustainability.

Chapter 4

System Evaluation and Results

This section provides details on the experimental setup and the results obtained from our study. The experiments aimed to evaluate the performance of various deep learning models in classifying biomedical waste, emphasizing metrics such as accuracy, precision, recall, and F1 score.

4.1 Experimental Setup

All the experiments were performed on Google Colaboratory notebooks utilizing an NVIDIA Tesla K80 GPU runtime, with 12 GB of RAM and 2496 CUDA cores operating at 560MHz. The deep CNN models were implemented in Python 3.7.10 using pyTorch. The following Python libraries were used during model development: Numpy (version: 1.19.5), Scikit-learn (version: 0.22.2), Pandas (version: 1.1.5). These libraries were essential for building, training, and evaluating the deep learning models used in our study. The computational resources provided by Google Colaboratory facilitated efficient experimentation and model development.

4.2 Results and Discussion

The SmartMedWaste system was evaluated using five different deep learning models: ResNeXt, ResNet, EfficientNet, ConvNext, and ViT_b_16. These models were assessed to classify medical waste images based on several key performance metrics: accuracy, precision, recall, F1 score, and computational efficiency, including time taken per epoch and time for testing. Each model was trained for 20 epochs using transfer learning from the ImageNet-1k dataset. This comprehensive evaluation aimed to identify the most effective model for the SmartMedWaste system by not only considering the classification performance but also the computational resources required for training and testing. Confusion matrices were generated to provide a detailed breakdown of each model's classification capabilities across different classes of medical waste.

ResNeXt emerged as the top performer among the models evaluated. It achieved an accuracy of 0.9793, precision of 0.9801, recall of 0.9793, and an F1 score of 0.9797 (Table 4.1). These metrics indicate a very reliable classification capability. The training time per epoch was 48.42 seconds, and the time for testing was 5.44 seconds, demonstrating a good balance between high performance and computational efficiency. The confusion matrix for ResNeXt, as shown in Figure 4.1, revealed minimal misclassifications, especially for the 'Syringe' and 'Scissors' classes, highlighting its robust performance across various medical waste categories. ResNet also showed strong performance, although it slightly lagged behind ResNeXt. It recorded an accuracy of 0.9777, precision of 0.9778, recall of 0.9765, and an F1 score of 0.9772 (Table

4.1). In terms of computational efficiency, ResNet was more efficient with a training time of 35.23 seconds per epoch and a testing time of 5.03 seconds. Despite its high efficiency, it displayed slightly higher misclassifications, particularly for the 'Wool' class, as indicated by the confusion matrix shown in Figure 4.1. This suggests that while ResNet is a faster model, there is a minor trade-off in terms of accuracy and precision. EfficientNet was notable for its fastest training time per epoch at 28.99 seconds, making it the quickest model to train. However, it had the longest testing time of 136.20 seconds. Its performance metrics, though slightly lower than ResNeXt and ResNet, were still robust, with an accuracy of 0.9742, precision of 0.9746, recall of 0.9755, and an F1 score of 0.9751 (Table 4.1). The confusion matrix, as shown in Figure 4.1, showed some misclassifications in the 'Syringe' and 'Wasted Medicine' classes, indicating that while EfficientNet is very efficient during training, its longer testing time and slight drop in performance could be potential drawbacks.ConvNext excelled in precision and recall, achieving the highest F1 score of 0.9915 among all models. Its precision was 0.9923, and recall was 0.9907, with an overall accuracy of 0.9714 (Table 4.1). However, ConvNext was the slowest model in terms of epoch training time, taking 104.71 seconds per epoch. The testing time was 10.96 seconds. Despite its slower training speed, the confusion matrix for ConvNext, as shown in Figure 4.1, showed very few misclassifications, particularly for the 'Wool' class, indicating its high reliability in classification tasks. ConvNext's performance suggests that it is highly effective but requires more computational resources for training. ViT_b_16 provided solid and balanced performance across all metrics. It achieved an accuracy of 0.9725, precision of 0.9715, recall of 0.9734, and an F1 score of 0.9724 (Table 4.1). The model's training time per epoch was 79.62 seconds, and the testing time was 9.66 seconds, making it more efficient than ConvNext but less accurate overall. The confusion matrix for ViT_b_16, as shown in Figure 4.1, indicated some misclassifications, particularly for the 'Scissors' and 'Wasted Medicine' classes. This model strikes a balance between performance and efficiency, offering a middle ground compared to the other models. When comparing these models, ResNeXt stands out as the most balanced option, providing high accuracy and excellent performance metrics with reasonable computational efficiency. ResNet follows closely, offering slightly lower performance but faster training and testing times, making it a good choice where computational resources are limited. EfficientNet, while the fastest to train, suffers from longer testing times and slightly lower accuracy. ConvNext, despite being the slowest to train, delivers the highest precision and recall, making it ideal for scenarios where accuracy is paramount and computational resources are available. Finally, ViT_b_16 offers a balanced approach with moderate performance metrics and computational efficiency.

The confusion matrices in Figure 4.1 for each model provide a visual representation of these performance metrics, showing the frequency of true and predicted label combinations. This detailed breakdown helps in understanding the specific areas where each model excels or falls short, contributing to a more informed decision on the most suitable model for the SmartMedWaste system.

The heatmap images, depicted in Figure 4.1, provide a visual representation of the confusion matrices for each model—ResNeXt, ResNet, EfficientNet, ConvNext, and ViT_b_16. Each cell in the heatmap corresponds to a combination of true and predicted labels, with varying shades of color indicating the frequency or intensity of those combinations.

These models were assessed on various metrics including accuracy, precision, recall, F1 score, and computational efficiency. Based on the evaluation, ResNeXt stands out as the most balanced model with high performance and reasonable training and

TABLE 4.1: Accuracy, Precision, Recall, F1 Score for all the Models

Metric	ResNeXt	ResNet	EfficientNet	ConvNext	Vit_b_16
Accuracy	0.9793	0.9777	0.9742	0.9714	0.9725
Precision	0.9801	0.9778	0.9746	0.9923	0.9715
Recall	0.9793	0.9765	0.9755	0.9907	0.9734
F1 Score	0.9797	0.9772	0.9751	0.9915	0.9724




FIGURE 4.1: Confusion Matrix for ResNeXt, ResNet, EfficientNet, ConvNext, and ViT_b_16 model

testing times and ResNeXt emerged as the top performer, boasting an impressive accuracy rate of 97.93% and demonstrating robust classification capabilities with minimal misclassifications across all waste categories. ResNet performed commendably as well, with slightly lower metrics compared to ResNeXt but still maintaining a strong classification performance and maintaining a strong balance between accuracy and computational efficiency. While EfficientNet showed promise with its efficient training, it exhibited some misclassifications, indicating potential for further optimization. While it demonstrated decent accuracy (97.42%) and precision, its longer testing time and slightly lower metrics compared to ResNet and ResNeXt suggest room for improvement. ConvNext stood out for its exceptional precision and recall but incurred longer training times. Its confusion matrix revealed very few misclassifications, particularly notable for the 'Wool' class. However, its significantly longer training time poses practical challenges, making it more suitable for applications where precision and recall are paramount, despite computational costs. ViT_b_16 provided a balanced performance, offering moderate accuracy and efficiency. While its confusion matrix showed some misclassifications, particularly for 'Scissors' and 'Wasted Medicine', ViT_b_16 offers a middle ground in terms of performance and efficiency. These findings offer valuable insights for selecting the most suitable model tailored to specific application requirements, ensuring reliable and efficient classification of medical waste images.

The models are also evaluated based on the execution time namely: Time Taken Per Epoch and Time for Test. The Time Taken Per Epoch measures the training speed of each model, while the Time for Test assesses the time required to make predictions on the test dataset. Below, we present bar charts for both metrics to highlight the differences in performance among the models.

- **Time Taken Per Epoch**

  This metric measures the average time each model takes to complete one training epoch. It's a critical factor when considering the overall training time required for large datasets.A lower time per epoch indicates faster training, which is beneficial for iterating and improving the model quickly. Figure 4.2 shows the Time Taken Per Epoch for each model, illustrating how quickly each model trains on the dataset.

- **Time for Test**

  This metric evaluates the time taken by each model to make predictions on the test dataset. Faster testing times are important for real-time applications where quick predictions are necessary, such as in automated medical waste classification systems. In Figure 4.3, the Time for Test is displayed, providing insights into the efficiency of each model in making predictions.

Overall, the evaluation results demonstrate the effectiveness of SmartMedWaste in achieving its goals of accurately identifying and classifying biomedical waste. The high accuracy, precision, recall, and F1 score attest to the system's reliability and robustness in waste management applications, thereby enhancing efficiency, safety, and sustainability in healthcare facilities.




FIGURE 4.2: Time Taken Per Epoch for Different Models




FIGURE 4.3: Testing Time for different Models

Chapter 5

Conclusion and Future Work

In conclusion, SmartMedWaste emerges as a transformative solution poised to revolutionize medical waste management practices within the healthcare sector. Its introduction signifies a significant advancement that addresses critical challenges inherent in traditional waste management approaches, offering a range of benefits that have the potential to reshape how healthcare facilities handle biomedical waste.

The key contributions of SmartMedWaste lie in its ability to leverage technology to optimize waste management processes. By integrating real-time monitoring, data-driven insights, and automated classification, SmartMedWaste enhances efficiency, improves safety, and promotes sustainable waste management practices.

Through real-time monitoring capabilities, SmartMedWaste empowers healthcare facilities to proactively manage waste disposal, mitigating the risk of overflows, contamination, and environmental pollution. By providing valuable insights into waste generation patterns and operational efficiency, the system facilitates informed decision-making, optimizing resource allocation and minimizing operational costs. Moreover, SmartMedWaste's impact extends beyond the confines of the healthcare facility, contributing to a healthier environment for both healthcare workers and the broader community. By streamlining waste management processes and reducing the carbon footprint associated with biomedical waste disposal, the system supports sustainability efforts and promotes environmental conservation.

Overall, SmartMedWaste represents a paradigm shift in medical waste management practices, offering a comprehensive solution that prioritizes efficiency, safety, and sustainability. By embracing innovative technologies like SmartMedWaste, healthcare organizations can create safer and healthier environments for all stakeholders while minimizing the impact of biomedical waste on public health and the environment. As we move forward, continued research and development in this field will be essential to unlocking the full potential of SmartMedWaste and ensuring its widespread adoption across healthcare facilities worldwide.

SmartMedWaste is a cutting-edge system designed to revolutionize the management of biomedical waste through the use of advanced technologies. One of its primary strengths is its ability to autonomously classify biomedical waste with a high degree of accuracy. This is achieved by leveraging deep learning algorithms that have been meticulously trained on extensive datasets. The automation provided by SmartMedWaste significantly reduces reliance on manual sorting processes. This not only minimizes the risk of human error, which can be prevalent in manual operations, but also expedites the entire waste segregation process, leading to more efficient waste management. In addition to its automated classification capabilities, SmartMedWaste features IoT-enabled sensors that provide continuous real-time monitoring of waste disposal units. These sensors offer valuable insights into various aspects of the waste management process, such as fill levels, waste composition, and the operational status of disposal units. This real-time data is crucial

for timely decision-making, enabling healthcare facilities to enhance their operational efficiency. Furthermore, by ensuring compliance with regulatory requirements through consistent monitoring, SmartMedWaste helps in maintaining high standards of hygiene and safety.

However, the implementation of SmartMedWaste is not without its challenges. One of the most notable limitations is the significant initial investment required for sensor deployment, infrastructure setup, and system integration. This financial burden may pose a barrier to adoption, especially for healthcare facilities with limited resources. The high cost of implementation might deter smaller institutions or those in underfunded regions from benefiting from this advanced waste management system. Another limitation pertains to the reliability of the sensors used in SmartMedWaste. The accuracy and reliability of these sensors can vary, which might lead to potential inaccuracies in waste level measurements. Such discrepancies can affect the system's overall effectiveness, leading to issues in waste management operations. Ensuring consistent sensor performance is crucial to maintaining the reliability of the system.

Cybersecurity risks also pose a significant concern for SmartMedWaste. Connecting the system to networked environments introduces the potential for data breaches or unauthorized access. Such cybersecurity threats could compromise sensitive information or disrupt waste management operations, posing serious risks to the healthcare facilities that rely on SmartMedWaste. Ensuring robust cybersecurity measures is essential to protect the integrity and functionality of the system. Scalability is another challenge that SmartMedWaste may face, particularly in larger healthcare facilities or multi-site organizations. Managing a vast amount of data and coordinating multiple sensor networks can become increasingly complex as the scale of operation grows. Effective data management strategies and robust system architecture are required to ensure that SmartMedWaste can scale efficiently without compromising its performance.

To address these limitations and enhance the capabilities of SmartMedWaste, several future research directions can be explored. One potential area of investigation is the exploration of more sophisticated deep learning models for waste prediction and classification. By improving the underlying algorithms, the accuracy and reliability of SmartMedWaste's data analytics capabilities can be significantly enhanced. Integrating additional sensors into the system is another promising research direction. For instance, incorporating sensors that measure temperature or humidity could provide comprehensive environmental monitoring. This additional data would enable more informed decision-making in waste management, potentially leading to better outcomes in terms of waste segregation and disposal.

Developing machine learning algorithms with self-learning capabilities can further enhance SmartMedWaste. Such algorithms would enable the system to adapt and improve its performance over time autonomously. By adjusting waste management strategies based on evolving data patterns, SmartMedWaste could become even more responsive and effective in handling biomedical waste. Apart from this enhancing the user interface and accessibility features of SmartMedWaste is also crucial for improving user experience and facilitating seamless integration into existing healthcare workflows. A more intuitive and user-friendly interface can increase user adoption and ensure that the system is used to its full potential, thereby maximizing its benefits.

By addressing these areas for improvement and exploring new research directions, SmartMedWaste can further enhance its capabilities and expand its applicability in biomedical waste management. Ultimately, these advancements will contribute to more sustainable and efficient healthcare practices, benefiting both healthcare providers and the environment. Through continuous innovation and adaptation, SmartMedWaste has the potential to set new standards in the management of biomedical waste, ensuring safer and more efficient practices across the healthcare industry.

Chapter 6

Reference

1. Raundale, P., Gadagi, S. and Acharya, C., 2017, July. IoT based biomedical waste classification, quantification and management. In 2017 International Conference on Computing Methodologies and Communication (ICCMC) (pp. 487-490). IEEE.

2. Wawale, S.G., Shabaz, M., Mehbodniya, A., Soni, M., Deb, N., Elashiri, M.A., Dwivedi, Y.D. and Naved, M., 2022. Biomedical Waste Management Using IoT Tracked and Fuzzy Classified Integrated Technique. Human-centric Computing and Information Sciences, 12, p.32.

3. Mohamed, N.H., Khan, S. and Jagtap, S., 2023. Modernizing medical waste management: unleashing the power of the Internet of Things (IoT). Sustainability, 15(13), p.9909.

4. Verma, M., Kumar, A. and Kumar, S., 2022, December. Medical Waste Classification using Deep Learning and Convolutional Neural Networks. In 2022 IEEE Conference on Interdisciplinary Approaches in Technology and Management for Social Innovation (IATMSI) (pp. 1-5). IEEE.

5. Malik, M., Sharma, S., Uddin, M., Chen, C.L., Wu, C.M., Soni, P. and Chaudhary, S., 2022. Waste classification for sustainable development using image recognition with deep learning neural network models. Sustainability, 14(12), p.7222.

6. Xie, S., Girshick, R., Dollár, P., Tu, Z. and He, K., 2017. Aggregated residual transformations for deep neural networks. In Proceedings of the IEEE conference on computer vision and pattern recognition (pp. 1492-1500).

7. Al Mamun, M.A., Hannan, M.A., Hussain, A. and Basri, H., 2014. Integrated sensing systems and algorithms for solid waste bin state management automation. IEEE Sensors journal, 15(1), pp.561-567.

8. Pardini, K., Rodrigues, J.J., Kozlov, S.A., Kumar, N. and Furtado, V., 2019. IoT-based solid waste management solutions: a survey. Journal of Sensor and Actuator Networks, 8(1), p.5.

9. Shettennavar, S. and Vithayathil, A., 2019. Exploratory study of biomedical waste management-an IoT perspective. Asian Journal of Management, 10(3), pp.181-189.

10. Farahani, A., Pourshojae, B., Rasheed, K. and Arabnia, H.R., 2020, December. A concise review of transfer learning. In 2020 International Conference on Computational Science and Computational Intelligence (CSCI) (pp. 344-351). IEEE.

11. Zhuang, F., Qi, Z., Duan, K., Xi, D., Zhu, Y., Zhu, H., Xiong, H. and He, Q., 2020. A comprehensive survey on transfer learning. Proceedings of the IEEE, 109(1), pp.43-76.

12. Wijaya, A. S., Zainuddin, Z., and Niswar, M. (2017) 'Design a smart waste bin for smart waste management',International Conference on Instrumentation, Control, and Automation (ICA) ,pp. 62-66.

13. Prajakta, G., Kalyani, J., and Snehal, M. (2015) 'Smart garbage collection system in residential area', IJRET: International Journal of Research in Engineering and Technology, Vol.4, No.3, pp.122-124.

14. Shareefdeen, Z. M. (2012) 'Medical waste management and control',Journal of Environmental Protection, Vol.3, No.12, pp.1625.

15. Sudha, S., Vidhyalakshmi, M., Pavithra, K., Sangeetha, K., and Swaathi, V. (2016) 'An automatic classification method for environment: Friendly waste segregation using deep learning', Technological Innovations in ICT for Agriculture and Rural Development (TIAR) , pp. 65-70.

16. Batty, M., Axhausen, K. W., Giannotti, F., Pozdnoukhov, A., Bazzani, A., Wachowicz, M., ... and Portugali, Y. (2012) 'Smart cities of the future', The European Physical Journal Special Topics, Vol.214, No.1, pp. 481-518.

17. Folianto, F., Low, Y. S., and Yeow, W. L. (2015) 'Smartbin: Smart waste management system',International Conference on Intelligent Sensors, Sensor Networks and Information Processing (ISSNIP) , pp. 1-2.

18. Ganeshan, A. K. S., Das, E., Belani, A., and Anand, A. (2017) 'The Raspbian Automatic Segregator of Household Waste', International Journal of Engineering Science.

19. Sinha, T., Kumar, K. M., and Saisharan, P. (2015) 'smart Dustbin', International Journal of Industrial Electronics and Electrical Engineering, Vol.3, No.5, pp.101-104.

20. Ramachandra, T. V., and Bachamanda, S. (2007) 'Environmental audit of municipal solid waste management', International Journal of Environmental Technology and Management, Vol.7, No.3-4, pp.369-391.

21. Narendra Kumar, G., Swamy, C., and Nagadarshini, K. N. (2014) 'Efficient garbage disposal management in metropolitan cities using VANETs', Journal of Clean Energy Technologies, Vol.2, No.3, pp.258-262.

22. Qandil, A., and Zaid, A. I. (2015) 'Considerations in the design and manufacturing of a load cell for measuring dynamic compressive loads', Power Generation System and Renewable Energy Technologies, pp. 1-6.

23. Phithakkitnukoon, S., Wolf, M. I., Offenhuber, D., Lee, D., Biderman, A., and Ratti, C. (2013) 'Tracking trash', IEEE Pervasive Computing, Vol.12, No.2, pp.38-48.

24. Pushpa, M. K., Gupta, A., Shaikh, S. M., Jha, S., and Suchitra, V. (2015) 'Microcontroller Based Automatic Waste Segregator', International journal of innovative research in Electrical, Electronics, Instrumentation and Control Engineering, Vol.3, No.8.

25. R. A. Aral, S. R. Keskin, M. Kaya and M. Haciomeroglu, "Classification of trashnet dataset based on deep learning models", Proc. BigData, pp. 2058-2062, Dec. 2018.

26. M. Yang and G. Thung, "Classification of trash for recyclability status", 2016.

27. V. Ruiz, Á. Sánchez, J. F. Vélez and B. Raducanu, "Automatic image-based waste classification", Proc. IWINAC, vol. 2, pp. 422-431, 2019.

28. C. Bircanoglu, M. Atay, F. Beser, O. Genc and M. A. Kizrak, "RecycleNet: Intelligent waste sorting using deep neural networks", Proc. INISTA, pp. 1-7, 2018.

29. S. Xie, R. B. Girshick, P. Dollár, Z. Tu and K. He, "Aggregated Residual Transformations for Deep Neural Networks", Proc. CVPR, pp. 5987-5995, 2017.

30. A. Krizhevsky, I. Sutskever and G. S. Hinton, "ImageNet classification with deep convolutional neural networks", Commun. ACM, vol. 60, no. 6, pp. 84-90, 2017.

31. K. Simonyan and A. Zisserman, "Very deep convolutional networks for large-scale image recognition", arXiv:1409.1556, 2014, [online] Available: https://arxiv.org/abs/1409.1556.

32. K. He, X. Zhang, S. Ren and J. Sun, "Deep residual learning for image recognition", Proc. CVPR, pp. 770-778, 2016.

33. G. Huang, Z. Liu, L. van der Maaten and K. Q. Weinberger, "Densely connected convolutional networks", Proc. IEEE Conf. Comput. Vis. Pattern Recognit., pp. 2261-2269, Jul. 2017.