Leveraging Ensemble Loss in Generative Adversarial Networks for Enhanced Underwater Imagery

Thesis submitted in partial fulfillment of the requirements for the degree of

Master of Engineering
in
Computer Science and Engineering

Submitted by

Rajarshi Mitra
Regn. No. - 163562 of 2022 - 2023
Exam Roll No. - M4CSE24008
Class Roll No. - 002210502011
Session - 2022 - 2024

Under the supervision of

Prof. Sanjoy Kumar Saha

Department of Computer Science and Engineering
Jadavpur University
188, Raja S.C. Mallick Rd,
Kolkata - 700032, West Bengal, India

Department of Computer Science and Engineering
Faculty of Engineering and Technology
Jadavpur University, Kolkata - 700032

CERTIFICATE OF RECOMMENDATION

This is to certify that the work embodied in this thesis entitled **"Leveraging Ensemble Loss in Generative Adversarial Networks for Enhanced Underwater Imagery"** has been satisfactorily completed by **Rajarshi Mitra** (Registration Number 163562 of 2022 - 2023; Class Roll No. 002210502011; Examination Roll No. M4CSE24008). It is a bonafide piece of work carried out under my supervision and guidance at Jadavpur University, Kolkata, for partial fulfillment of the requirements for the awarding of the **Master of Engineering** in **Computer Science and Engineering** degree in the Department of Computer Science and Engineering, Faculty of Engineering and Technology, Jadavpur University, during the academic year 2022 - 2024.

Prof. Sanjoy Kumar Saha,
Department of Computer Science and Engineering,
Jadavpur University.
(Supervisor)

Forwarded By:

Prof. Nandini Mukhopadhyay,
HOD, Department of Computer Science and Engineering,
Jadavpur University.

Prof. Dipak Laha,
DEAN, Faculty of Engineering and Technology,
Jadavpur University.

Department of Computer Science and Engineering
Faculty of Engineering and Technology
Jadavpur University, Kolkata - 700032

CERTIFICATE OF APPROVAL

This is to certify that the thesis entitled **"Leveraging Ensemble Loss in Generative Adversarial Networks for Enhanced Underwater Imagery"** is a bonafide record of work carried out by **Rajarshi Mitra** (Registration Number 163562 of 2022 - 2023; Class Roll No. 002210502011; Examination Roll No. M4CSE24008) in partial fulfillment of the requirements for the award of the degree of **Master of Engineering** in **Computer Science and Engineering** degree in the Department of Computer Science and Engineering, during the period of September 2022 to May 2024. It is understood that by this approval, the undersigned do not necessarily endorse or approve any statement made, opinion expressed or conclusion drawn therein, but approve the thesis only for the purpose of which it has been submitted.

_____
Signature of Examiner 1
Date:

_____
Signature of Examiner 2
Date:

Department of Computer Science and Engineering
Faculty of Engineering and Technology
Jadavpur University, Kolkata - 700032

DECLARATION OF ORIGINALITY AND COMPLIANCE OF ACADEMIC ETHICS

I hereby declare that the thesis entitled **"Leveraging Ensemble Loss in Generative Adversarial Networks for Enhanced Underwater Imagery"** contains literature survey and original research work by the undersigned candidate, as a part of his degree of **Master of Engineering** in **Computer Science and Engineering, Jadavpur University**. All the information have been obtained and presented in accordance with academic rules and ethical conduct.
I also declare that, as required by these rules and conduct, I have fully cited and referenced all materials and results that are not original to this work.

Name: Rajarshi Mitra

Examination Roll No.: M4CSE24008

Registration No.: 163562 of 2022 - 2023

Thesis Title: Leveraging Ensemble Loss in Generative Adversarial Networks for Enhanced Underwater Imagery

Signature of the Candidate:

. . . . . .

Dedicated to my unwavering pillars of support,
my parents,
whose love and sacrifice have fueled every chapter of my journey.

. . . . . .

Acknowledgements

I express my profound gratitude and a profound sense of indebtedness to my guide, **Dr. Sanjoy Kumar Saha**, a Professor in the Department of Computer Science and Engineering at Jadavpur University, Kolkata, India. His unwavering support and guidance have been invaluable throughout the execution of this thesis, significantly contributing to its fruition. Dr. Saha's expertise and direction have been pivotal in defining the course and enhancing the caliber of this thesis, and I am sincerely grateful for his consistent commitment.

I express my sincere gratitude to the Head of the Department, **Dr. Nandini Mukhopadhyay**, Professor, Department of Computer Science and Engineering, Jadavpur University, Kolkata, India, for being kind enough to permit me to carry out my research in this prestigious institution.

I thank my seniors, Mr. Samiran Dey and Mr. Sujan Sarkar, and friends Mr. Akash Halder, Ms. Tirtha Das, Mr. Shankha Shubhra Das, Ms. Debarati Paul, Mr. Arkadeep Sengupta, Mr. Dibyendu Chattoraj and Mr. Ankit Das for their unwavering support, validation and understanding throughout this journey. Their companionship and camaraderie have been invaluable to me.

I must also extend a special word of thanks to my parents and family members for the encouragement and support they have rendered in preparing this thesis.

Rajarshi Mitra

Examination Roll No.: M4CSE24008

Registration No.: 163562 of 2022 - 2023

Department of Computer Science and Engineering,

Jadavpur University.

Abstract

The exploration of underwater environments has captivated humanity for centuries, sparking curiosity and driving innovation in a wide range of disciplines ranging from marine biology to archaeology. However, the intrinsic challenges associated with underwater imaging have long posed formidable obstacles to effective analysis and interpretation of captured imagery. These challenges, including poor visibility, color distortion, and loss of image details, demand innovative methodologies tailored to the unique characteristics of underwater scenes. In response, this paper presents a pioneering approach to underwater image enhancement, leveraging an ensemble loss function comprising three novel components: gradient loss, contrast loss, and brightness loss. Traditional image enhancement techniques often fall short when applied to underwater imagery due to the distinct characteristics of the underwater environment. Factors such as light attenuation, water turbidity, and particle scattering lead to diminished visibility and spectral distortions, complicating the task of accurately capturing and analyzing underwater scenes. To address these challenges, our proposed methodology adopts a holistic approach, integrating multiple loss functions that target specific aspects of underwater image degradation.

The first component of our ensemble loss function, gradient loss, focuses on preserving spatial gradients within underwater images. Spatial gradients play a crucial role in defining image structure and detail, yet they are often attenuated or distorted in underwater environments. By incorporating gradient loss into our optimization framework, we aim to mitigate the loss of spatial information, thereby enhancing image clarity and definition. The second component, contrast loss, addresses the challenge of contrast reduction commonly observed in underwater imagery. Due to light attenuation and scattering, underwater scenes often suffer from reduced contrast, resulting in flat and washed-out appearances. Contrast loss seeks to rectify this issue by encouraging the preservation and enhancement of image contrast, leading to images with improved depth perception and visual impact. The third component, brightness loss, targets variations in luminance across underwater scenes. In underwater environments, light intensity decreases with depth, leading to uneven illumination and exposure across images. Brightness loss aims to normalize luminance levels, ensuring consistent brightness and exposure throughout the image, thereby improving overall visual consistency and coherence.

To evaluate the efficacy of our proposed methodology, we conducted extensive experiments using the Enhancing Underwater Visual Perception (EUVP) dataset,

a widely adopted benchmark dataset in the field of underwater image enhancement. Our experimental results demonstrate significant improvements in image fidelity, color accuracy, and artifact reduction when incorporating the proposed ensemble loss functions. Qualitative assessments further highlight the enhanced visual quality of underwater images, characterized by improved clarity, contrast, and color rendition. In addition to quantitative evaluations, we conducted comparative analyses against existing methods to assess the performance of our model. Our results show that our methodology outperforms state-of-the-art techniques in terms of image quality, fidelity, and visual perception, underscoring its effectiveness and robustness in addressing the challenges inherent in underwater image enhancement.

Contents

Abstract i

Table of Contents iii

List of Figures v

List of Tables vii

List of Abbreviations viii

1 Introduction 1

2 Literature Survey 5
2.1 Previous works . . . 5

3 Methodology 14
3.1 Model overview . . . 14
3.2 Architecture . . . 15
3.3 Loss Functions . . . 18
3.3.1 Adversarial Loss . . . 18
3.3.2 L1 Loss . . . 18
3.3.3 Gradient Loss: . . . 19
3.3.4 Contrast Difference Loss: . . . 19
3.3.5 Brightness Difference Loss: . . . 20
3.3.6 Our ensemble loss: . . . 21

4 Results and Experiments 22
4.1 Dataset . . . 22
4.2 Implementation Strategy . . . 24
4.3 Results and Analysis . . . 24
4.3.1 Qualitative Analysis . . . 25
4.3.2 Quantitative Analysis . . . 28
4.3.2.1 PSNR . . . 29
4.3.2.2 SSIM . . . 29
4.3.2.3 FID . . . 29
4.3.2.4 LPIPS . . . 30
4.3.3 Ablation Study . . . 32

5 Conclusions **36**
5.1 Conclusions of the Present Work 36
5.2 Scope for Future Works 37

Bibliography **39**

List of Figures

1.1 Our proposed methodology for underwater image enhancement starts with the original input image. The generator produces an enhanced image, evaluated against the ground truth using Contrast, Brightness, Gradient, Adversarial, and L1 Loss functions. These losses guide the optimization process, minimizing disparities and aligning with the ground truth. Simultaneously, the discriminator classifies the generated image as true or false, providing adversarial feedback to the generator. This iterative refinement improves image quality, realism, and fidelity. This approach offers a robust framework for enhancing underwater imagery, benefiting fields like marine biology and oceanography. 3

3.1 The above figure illustrates the architecture of the generator used in our model. The model takes 256x256 RGB images, uses an encoder with downscale blocks increasing filters from 64 to 512, compresses features into a latent space, then reconstructs images via a decoder mirroring the encoder, using Conv2DTranspose with Tanh activation for output in the range [-1, 1]. 15

3.2 This figure illustrates how the discriminator works. The discriminator takes image and target inputs of shape (256, 256, 3), concatenates them, passes through downscale blocks with increasing filters, extracts high-level features with a convolutional layer, applies batch normalization and leaky ReLU activation, and outputs the likelihood of real/fake using a single-filter convolutional layer. . 17

4.1 Column 2 represents the ground truth images, Column 3 represents the predicted images generated using L_{adv} and L_1, Column 4 represents the predicted images generated using L_{adv}, L_1 and L_{gradient}, Column 5 represents the predicted images generated using L_{adv}, L_1, L_{grad} and L_{br}, Column 6 represents the predicted images generated using L_{adv}, L_1, L_{grad}, L_{br} and L_{con}. 26

4.2 Comparison of Original, Ground Truth, and Predicted Images. The model is trained on EUVP dataset and is tested using the UIEB dataset. The first row represents the original images, second row represents the ground truth images and the third row represents the predicted images. 27

4.3 Comparison of Original, Ground Truth, and Predicted Images. The model is trained on EUVP dataset and is tested using the LSUI dataset. The first row represents the original images, second row represents the ground truth images and the third row represents the predicted images. 28
4.4 The top left block represents the input images, the top right block represents the ground truth image, the bottom left represents the images generated using our model of perceptual loss, and the bottom right represents the images generated using conventional perceptual loss. 35

List of Tables

4.1 Quantitative comparison for average PSNR, SSIM, LPIPS and FID values between our model and currently existing models. Red denotes the best score, Green denotes the second best score and Blue denotes the third best score. The values of the existing models are taken from the paper [1]. 31

4.2 Quantitative comparison for average PSNR, SSIM, LPIPS and FID values between our model and currently existing models. Red denotes the best score, Green denotes the second best score and Blue denotes the third best score. The values of the existing models are taken from the paper [17]. 31

4.3 Quantitative comparison for average PSNR, SSIM, LPIPS and FID values between our model and currently existing models. Red denotes the best score, Green denotes the second best score and Blue denotes the third best score. The values of the existing models are taken from the paper [18]. 32

4.4 Results of hyperparameter tuning of the loss component weights for 100 epochs each. Red denotes the best score, Green denotes the second best and Blue denotes the third best. 33

4.5 Ablation study on the implementation of loss functions for 400 epochs each. 34

4.6 Comparison of our novel perceptually driven loss with the conventional perceptual loss. 35

List of Abbreviations

A	
ADS	**A**tmosphere-based **D**ynamic **S**tructure
C	
CMSFFT	**C**hannel-wise **M**ulti-**S**cale **F**eature **F**usion **T**ransformer
CNN	**C**onvolutional **N**eural **N**etwork
CycleGAN	**Cycle** **G**enerative **A**dversarial **N**etwork
E	
EUVP	**E**nhancing **U**nderwater **V**isual **P**erception
F	
FID	**F**réchet **I**nception **D**istance
G	
GAN	**G**enerative **A**dversarial **N**etwork
GUPDM	**G**eneralized **U**nderwater **I**mage **E**nhancement via **P**hysical-knowledge-guided **D**ynamic **M**odel
I	
IBLA	**I**mage **B**lurriness and **L**ight **A**bsorption
L	
LAB	**L**ightness, **A** (green to magenta), **B** (blue to yellow)
LCH	**L**ightness, **C**hroma, **H**ue
LPIPS	**L**earned **P**erceptual **I**mage **P**atch **S**imilarity
LSGAN	**L**east **S**quares **G**enerative **A**dversarial **N**etworks
LSUID	**L**arge **S**cale **U**nderwater **I**mage **D**ataset

M

MSE	**M**ean **S**quared **E**rror

P

PMS	**P**rior-based **M**ulti-scale **S**tructure
PSNR	**P**eak **S**ignal to **N**oise **R**atio

R

RAUNE-Net	**R**eal-time **A**daptive **U**nderwater **N**eural **E**nhancement **Net**work
Res-GAN	**Res**idual **G**enerative **A**dversarial **N**etwork
Res-WGAN	**Res**idual **W**asserstein **G**enerative **A**dversarial **N**etwork
RGB	**R**ed, **G**reen, **B**lue

S

SESR	**S**imultaneous **E**nhancement and **S**uper-**R**esolution
SGFMT	**S**patial-wise **G**lobal **F**eature **M**odeling **T**ransformer
SSIM	**S**tructural **S**imilarity **I**ndex **M**easure

T

TDS	**T**ransmission-guided **D**ynamic **S**tructure

U

UDCP	**U**nderwater **D**ark **C**hannel **P**rior
UGAN	**U**nderwater **G**enerative **Ad**versarial **N**etwork
UIBLA	**U**nderwater **I**mage **R**estoration **B**ased on **I**mage **B**lurriness and **L**ight **A**bsorption
UIE	**U**nderwater **I**mage **E**nhancement
UIEBD	**U**nderwater **I**mage **E**nhancement **B**enchmark **D**ataset
UWCNN	**U**nder**w**ater **C**onvolutional **N**eural **N**etwork

V

VAE	**V**ariational **A**uto**e**ncoder
VDSR	**V**ery-**D**eep **S**uper-**R**esolution Reconstruction

CHAPTER 1

Introduction

The underwater image enhancement plays a pivotal role in diverse fields spanning research, exploration, and practical applications, serving as a cornerstone for unlocking the mysteries of the underwater world. Improved imagery not only enhances visibility underwater but also facilitates the observation and analysis of intricate structures, diverse organisms, and geological formations, thereby contributing significantly to scientific endeavors such as marine ecosystems and oceanography.

In the realm of scientific research, enhanced underwater imagery is indispensable for understanding the complex dynamics of marine environments. By providing clearer and more detailed visuals, researchers can delve deeper into the intricacies of marine ecosystems, studying biodiversity, habitat structures, and ecological interactions with unprecedented clarity. Furthermore, enhanced imagery aids in monitoring environmental changes over time, enabling scientists to assess the impact of human activities and climate change on underwater ecosystems.

In sectors such as underwater archaeology and offshore infrastructure inspection, the importance of enhanced images cannot be overstated. Clearer visuals allow archaeologists to meticulously survey underwater archaeological sites, unraveling ancient mysteries and preserving cultural heritage for future generations. Similarly, in offshore industries, such as oil and gas exploration, enhanced imagery facilitates precise inspection of underwater infrastructure, ensuring the safety and integrity of critical assets.

Security systems deployed in maritime environments also stand to benefit significantly from enhanced underwater imagery. By providing clearer and more detailed visuals of underwater activities, such as vessel movements and diver operations, enhanced images enhance situational awareness and enable prompt response to potential security threats. This is particularly crucial for safeguarding ports, coastlines, and maritime borders, thereby bolstering maritime safety and

security.

Moreover, the educational value of enhanced underwater imagery cannot be overlooked. By showcasing the mesmerizing beauty and biodiversity of the underwater world, enhanced images serve as powerful educational tools, inspiring curiosity and raising awareness about marine conservation and the importance of preserving fragile aquatic ecosystems. Through educational outreach programs, museums, and documentaries, enhanced underwater imagery fosters a deeper appreciation for the ocean's wonders and the need for sustainable stewardship of marine resources.

In our research on underwater image enhancement (UIE), we embarked on a thorough investigation utilizing a rich dataset of paired images sourced from the esteemed Enhancing Underwater Visual Perception (EUVP) dataset [1]. This dataset comprised meticulously curated pairs of original underwater images and their corresponding enhanced versions, serving as invaluable training data for our exploration. Central to our methodology was the employment of the pix2pix Generative Adversarial Network (GAN) [2], a sophisticated framework renowned for its prowess in image-to-image translation tasks. This architecture, comprising both a generator and a discriminator network, formed the backbone of our approach, allowing us to leverage the power of adversarial training to enhance underwater imagery.

To further augment the capabilities of the pix2pix GAN [2] in addressing the unique challenges of underwater imaging, we introduced three novel loss functions: gradient loss, contrast loss, and brightness loss. These loss functions were meticulously crafted to target specific aspects of image degradation commonly encountered in underwater scenarios. The gradient loss aimed to preserve spatial gradients within the images, crucial for maintaining structural integrity and detail. Meanwhile, the contrast loss sought to mitigate the often-substantial reduction in contrast observed in underwater images, ensuring that crucial details are not lost amidst the murky depths. Additionally, the brightness loss was instrumental in addressing variations in luminance across underwater scenes, promoting uniform brightness and exposure throughout the images.

Our ultimate goal in this endeavor was to enhance the clarity and visual fidelity of underwater images, thereby unlocking their full potential for applications in various domains, including marine biology, oceanography, and underwater archaeology. By enhancing the quality of underwater imagery, we aimed to provide researchers and practitioners with invaluable tools for studying and understanding the complexities of the underwater world. Through meticulous experimentation, evaluation, and validation, we sought to push the boundaries of underwater image enhancement, contributing to a deeper appreciation and explo-

ration of the vast and diverse ecosystems that lie beneath the waves.




Figure 1.1: Our proposed methodology for underwater image enhancement starts with the original input image. The generator produces an enhanced image, evaluated against the ground truth using Contrast, Brightness, Gradient, Adversarial, and L1 Loss functions. These losses guide the optimization process, minimizing disparities and aligning with the ground truth. Simultaneously, the discriminator classifies the generated image as true or false, providing adversarial feedback to the generator. This iterative refinement improves image quality, realism, and fidelity. This approach offers a robust framework for enhancing underwater imagery, benefiting fields like marine biology and oceanography.

The proposed methodology, outlined in Figure 1.1, encompasses a holistic approach to underwater image enhancement, leveraging innovative techniques to address the unique challenges inherent in this domain. Our contributions can be summarized as follows:

1. Utilization of Gradient Loss: We introduce gradient loss as a key component of our methodology to preserve edges and fine details within underwater images. By aligning gradients between the generated and ground-truth images, we aim to mitigate the loss of structural integrity commonly observed in underwater scenes. This ensures that crucial visual cues, such as object boundaries and texture details, are faithfully preserved, enhancing the overall clarity and fidelity of the enhanced images.

2. Integration of Brightness Loss: To address variations in brightness levels inherent in underwater images, we employ brightness loss to minimize the difference between the generated and ground-truth images. This loss function is crucial for ensuring uniform brightness and exposure throughout the

enhanced images, thereby improving their perceptual quality and visual consistency. By harmonizing brightness levels, we aim to enhance the interpretability and realism of the resulting imagery, facilitating accurate analysis and interpretation in applications such as marine biology and underwater archaeology.

3. Incorporation of Contrast Loss: We introduce contrast loss to mitigate discrepancies in contrast characteristics between the generated and ground-truth images. By enhancing visual clarity and depth perception, this loss function plays a pivotal role in improving the overall quality of underwater imagery. By preserving and enhancing contrast, we aim to reveal hidden details and structures within underwater scenes, enabling more insightful analysis and interpretation. This contributes to advancements in fields such as oceanography and underwater exploration, where accurate depiction of underwater environments is paramount.

4. Adaptation of pix2pix GAN [2] for Underwater Image Enhancement: We extend the capabilities of the pix2pix Generative Adversarial Network (GAN) [2] framework for the task of underwater image enhancement by integrating our novel ensemble loss function. By incorporating gradient, brightness, and contrast losses into the training process, we empower the pix2pix GAN [2] to effectively address the complex challenges posed by underwater imaging. This adaptation not only enhances the performance of the GAN but also facilitates the generation of high-quality underwater imagery that meets the diverse needs of scientific research, exploration, and practical applications.

Through these contributions, we aim to advance the state-of-the-art in underwater image enhancement, providing researchers and practitioners with powerful tools for enhancing the clarity, fidelity, and interpretability of underwater imagery. Our methodology holds promise for a wide range of applications, spanning marine biology, oceanography, underwater archaeology, and beyond, and has the potential to drive significant advancements in our understanding of the underwater world.

CHAPTER 2

Literature Survey

Understanding the current research landscape is crucial for guiding our's work and identifying knowledge gaps. In underwater image enhancement (UIE), a thorough literature survey is essential for building on existing methodologies and advancing the state-of-the-art. By examining past research, key findings, trends, and limitations, researchers can contextualize their contributions and propose novel approaches to address unresolved challenges. This chapter provides a comprehensive overview of recent developments in UIE, focusing on methodologies, techniques, and applications, and highlights opportunities for further exploration and innovation.

2.1 Previous works

Wang et al. in the year 2017 proposeed an end-to-end framework for underwater image enhancement, introducing a Convolutional Neural Network (CNN)-based network called UIE-Net. The UIE-Net is trained with two tasks: color correction and haze removal, enabling simultaneous learning of strong feature representations for both objectives. The authors employ a pixels disrupting strategy within their learning framework to better extract inherent features in local patches, thereby improving convergence speed and accuracy. The training of UIE-Net is facilitated by synthesizing 200,000 training images based on a physical underwater imaging model. Experimental results on benchmark underwater images demonstrate the superior performance of UIE-Net compared to existing methods, particularly in cross-scene scenarios. This approach represents a significant advancement in the field, offering a unified and adaptable solution for underwater image enhancement.[3]

In the year 2018, scientists Anwar, Li, and Porikli addressed the challenges posed by light absorption and scattering in underwater scenes, which often lead to

low contrast and distorted color casts in images. They propose a novel convolutional neural network-based image enhancement model, named UWCNN, designed to efficiently tackle these issues. Unlike previous approaches that rely on estimating parameters of underwater imaging models or employing inflexible frameworks suitable only for specific scenes, the UWCNN model adopts an automatic end-to-end and data-driven training mechanism. Leveraging a synthetic underwater image database comprising ten different marine image databases, the authors synthesize data to train multiple UWCNN models tailored to different underwater image formation types. Their experimental results, conducted on both real-world and synthetic underwater images, demonstrate the model's robust generalization across diverse underwater scenes, outperforming existing methods both qualitatively and quantitatively. Additionally, they conduct an ablation study to analyze the impact of each component within their network, providing insights into the efficacy of their proposed approach.[4]

In the year 2019, scientists Uplavikar, Wu, and Wang address the challenges associated with enhancing raw underwater images, which suffer from degradation due to wavelength-dependent light attenuation and scattering. They highlight the additional complexity introduced by the diversity of water types in which these images are captured, such as deep oceanic waters versus shallow coastal waters, making it difficult to train a single model for enhancing underwater images effectively. To overcome this challenge, they propose a novel model that adeptly handles water type diversity by adversarially learning content features of images while disentangling unwanted nuisances corresponding to different water types viewed as distinct domains. Leveraging learned domain-agnostic features, they generate enhanced underwater images and train their model on a dataset comprising images of 10 Jerlov water types. Experimental results showcase the superiority of their proposed model, surpassing previous methods in SSIM [5] and PSNR [5] scores across various Jerlov water types while demonstrating robust generalization to real-world datasets. Furthermore, they demonstrate the utility of enhanced images generated by their model in improving performance on a high-level vision task, specifically object detection. This innovative approach represents a significant advancement in the field of underwater image enhancement, offering promising implications for various applications requiring accurate and reliable image analysis in diverse underwater environments.[6]

In the year 2019, Chongyi Li, Chunle Guo, Wenqi Ren, Runmin Cong, Junhui Hou, Sam Kwong, and Dacheng Tao undertook a significant initiative in the realm of underwater image enhancement. Recognizing the growing importance of this field in marine engineering and aquatic robotics, they embarked on the task of evaluating existing algorithms against large-scale real-world datasets, aiming to

provide a comprehensive understanding of their performance and limitations. Addressing the lack of evaluation on images acquired in natural underwater environments, they introduced the Underwater Image Enhancement Benchmark (UIEB) [7], comprising 950 real-world underwater images, of which 890 were paired with corresponding reference images. Notably, the remaining 60 images, lacking satisfactory reference counterparts, were deemed challenging data. Leveraging this benchmark, they conducted a thorough perceptual study and analysis of state-of-the-art underwater image enhancement algorithms, both qualitatively and quantitatively. Additionally, they proposed Water-Net, an underwater image enhancement network trained on the UIEB [7] dataset, serving as a baseline for evaluating the generalization of CNN-based approaches. Through their benchmark evaluations and the proposed Water-Net model, they shed light on the performance and limitations of existing algorithms, thereby paving the way for future advancements in underwater image enhancement research.[8]

In 2019, Yecai Guo, Hanyu Li, and Peixian Zhuang made significant strides in the field of underwater image enhancement, addressing the challenges of color distortion, underexposure, and fuzziness prevalent in raw underwater images. Their pioneering solution involves the development of a novel multiscale dense generative adversarial network (GAN), specifically tailored for enhancing underwater images. Central to their approach is the incorporation of a residual multiscale dense block in the generator, leveraging multiscale, dense concatenation, and residual learning techniques to enhance performance, capture more details, and utilize previous features efficiently. Moreover, they employ computationally light spectral normalization in the discriminator to stabilize training. Their proposed nonsaturating GAN loss function, combining L1 loss and gradient loss, prioritizes the preservation of image features from ground truth. Through extensive evaluations on synthetic and real underwater images, their method demonstrated superior performance compared to both nondeep and deep learning methods, excelling in both qualitative and quantitative assessments. Furthermore, they conducted an ablation study to elucidate the contributions of each component and performed application tests to showcase the effectiveness of their proposed approach. This work represents a significant advancement in underwater image enhancement research, offering a robust and effective solution to address the challenges inherent in underwater imagery.[9]

In the year 2019, Peng Liu, Guoyu Wang, Hao Qi, Chufeng Zhang, Haiyong Zheng, and Zhibin Yu embarked on a significant endeavor to address the challenges posed by underwater imaging. Recognizing the detrimental effects of light refraction, absorption, and scattering on raw underwater images—manifesting as low contrast, blurred details, and color distortion—they proposed a pioneering so-

lution through a deep residual framework for image enhancement. Their approach begins by leveraging cycle-consistent adversarial networks (CycleGAN) [10] to generate synthetic underwater images, serving as crucial training data for convolutional neural network (CNN) models. Subsequently, they introduced the very-deep super-resolution reconstruction model (VDSR) for underwater resolution applications, culminating in the development of the Underwater Resnet model—a tailored residual learning model specifically designed to tackle underwater image enhancement tasks. Moreover, they refined the model's performance by innovating the loss function, integrating mean squared error loss and a novel edge difference loss, and introducing an asynchronous training mode. Lastly, they examined the impact of batch normalization on the model's efficacy. Through rigorous experiments and comparative analyses, conducted on a diverse array of underwater imagery, their proposed methods exhibited superior color correction and detail enhancement capabilities compared to both previous deep learning models and traditional methods, marking a significant stride forward in the field of underwater image enhancement.[11]

In the year 2020, Md Jahidul Islam, Youya Xia, and Junaed Sattar introduce a groundbreaking approach in their paper—a conditional generative adversarial network-based model—for real-time underwater image enhancement. The key innovation lies in formulating an objective function that supervises adversarial training, evaluating perceptual image quality based on global content, color, local texture, and style information. Additionally, they present the Enhancing Underwater Visual Perception (EUVP) [1], a substantial dataset comprising paired and unpaired underwater images captured under varying visibility conditions using seven different cameras during oceanic explorations and human-robot collaborative experiments. Through rigorous qualitative and quantitative evaluations, they demonstrate the model's efficacy in learning to enhance underwater image quality from both paired and unpaired training data. Moreover, they highlight the enhanced images' improved performance in standard underwater object detection, human pose estimation, and saliency prediction tasks. These findings underscore the model's suitability for real-time preprocessing in the autonomy pipeline of visually-guided underwater robots, marking a significant advancement in underwater image enhancement research.[1]

In the year 2020, Md Jahidul Islam, Peigen Luo, and Junaed Sattar presented a groundbreaking solution to the simultaneous enhancement and super-resolution (SESR) problem in underwater robot vision, tailored for near real-time applications. Their work introduces Deep SESR, a novel residual-in-residual network-based generative model capable of restoring perceptual image qualities at 2x, 3x, or 4x higher spatial resolution. Supervised training of Deep SESR is facilitated by

a multi-modal objective function addressing chrominance-specific underwater color degradation, image sharpness, loss in high-level feature representation, and salient foreground region detection. The authors devised an end-to-end training pipeline enabling joint learning of saliency prediction and SESR on a shared hierarchical feature space for efficient inference. Furthermore, they curated UFO-120, the first dataset dedicated to large-scale SESR learning, comprising over 1500 training samples and a benchmark test set of 120 samples. Through rigorous experimental evaluation on UFO-120 and other standard datasets, they demonstrated Deep SESR's superior performance compared to existing solutions for underwater image enhancement and super-resolution. Their model's generalization capabilities were validated across diverse spectral and spatial degradation levels in underwater and terrestrial images, showcasing its robustness. Finally, the authors assessed Deep SESR's computational feasibility for single-board deployments and highlighted its operational benefits for visually-guided underwater robots, underscoring its potential for real-world applications.[12]

In 2020, Long Chen, Zheheng Jiang, Lei Tong, Zhihua Liu, Aite Zhao, Qianni Zhang, Junyu Dong, and Huiyu Zhou addressed the critical issue of underwater image enhancement as a crucial pre-processing step for subsequent object detection tasks, pivotal in underwater navigation and ocean exploration. They observed that existing strategies often treat enhancement and detection as separate entities, lacking interaction, which may not always optimize the subsequent object detection task effectively. To tackle this challenge, the authors proposed two perceptual enhancement models, each integrating a deep enhancement model with a detection perceptor. The detection perceptor provided feedback in the form of gradients, guiding the enhancement model to generate visually pleasing or detection-favorable images at the patch level. Moreover, recognizing the scarcity of training data, they introduced a hybrid underwater image synthesis model, leveraging both physical priors and data-driven cues to synthesize training data and enhance the generalization of their enhancement model to real-world underwater images. Through comprehensive experimental evaluations on both real-world and synthetic underwater datasets, their proposed method demonstrated superior performance compared to several state-of-the-art methods, showcasing its effectiveness in enhancing underwater images for subsequent object detection tasks in practical underwater environments.[13]

In 2021, Xuelei Chen, Pin Zhang, Lingwei Quan, Chao Yi, and Cunyue Lu addressed the pressing challenge of color distortion in images captured by underwater robots, a critical issue affecting their visual perception in oceanic exploration, resource exploitation, and ecological research. These images typically exhibit hues close to green and blue, alongside low contrast and fuzzy details. To overcome

these limitations, the authors proposed a novel underwater image enhancement algorithm leveraging deep learning and image formation models. Their approach effectively mitigated the influence of underwater environmental factors, resulting in enriched color, enhanced details, and improved image quality as evidenced by higher scores in PSNR [5] and SSIM [5] metrics. Importantly, the proposed method also facilitated better results in feature key-point matching tasks. Notably, the algorithm demonstrated significantly faster computation speeds compared to existing methods, marking a substantial advancement in enhancing the visual perception of underwater robots and their effectiveness in various underwater applications.[14]

In 2021, Chongyi Li, Saeed Anwar, Junhui Hou, Runmin Cong, Chunle Guo, and Wenqi Ren addressed the prevalent challenges of color casts and low contrast in underwater images arising from wavelength- and distance-dependent attenuation and scattering. Their innovative solution, named Ucolor, introduces an underwater image enhancement network guided by medium transmission, leveraging multi-color space embedding. Initially, they proposed a multi-color space encoder network to enrich feature representations by incorporating diverse characteristics from different color spaces into a unified structure. By integrating an attention mechanism, the network dynamically highlights the most discriminative features extracted from multiple color spaces. Drawing inspiration from underwater imaging physical models, they designed a medium transmission-guided decoder network to enhance the network's response to quality-degraded regions. Through this approach, Ucolor effectively enhances the visual quality of underwater images by exploiting multiple color space embeddings and leveraging the strengths of both physical model-based and learning-based methods. Extensive experiments demonstrated Ucolor's superiority over state-of-the-art methods in terms of both visual quality and quantitative metrics, marking a significant advancement in underwater image enhancement research.[15]

In 2021, Nishant Singh and Aruna Bhat addressed the growing interest in underwater image processing, driven by its significance in marine engineering and aquatic robotics. Despite numerous algorithms proposed for underwater image enhancement, their assessment has typically relied on synthetic datasets or a limited selection of real images. In their literature review paper, the authors focused on discussing the latest underwater image enhancement methods based on deep learning techniques. These methods not only improve image quality but also surpass traditional enhancement and restoration methods in terms of performance. By leveraging deep learning approaches, these methods contribute to increasing the variety in underwater imaging, enhancing image quality, and expanding the scope for further improvements. The paper primarily delves into the latest algo-

rithms, their datasets, and the evaluation criteria based on various parameters. Finally, the authors compare the results obtained from these algorithms, shedding light on their relative efficacy and potential for advancement in underwater image processing research.[16]

In 2022, Zhenqi Fu, Xiaopeng Lin, Wu Wang, Yue Huang, and Xinghao Ding introduced a novel underwater image enhancement method named SCNet, aimed at simultaneously improving image quality and addressing the diversity of degradation caused by underwater conditions. SCNet relies on normalization schemes across both spatial and channel dimensions, with a primary focus on learning water type desensitized features. The key strategy involves applying whitening to decorrelate activations across spatial dimensions for each instance in a mini-batch, alongside eliminating channel-wise correlation by standardizing and re-injecting the first two moments of activations across channels. These normalization schemes are implemented at each scale of the U-Net architecture, facilitating multi-scale representations. By encoding water type irrelevant features, the decoder can effectively reconstruct a clean signal, remaining unaffected by various distortion types. Through experimental evaluations on two real-world underwater image datasets, SCNet demonstrated its ability to successfully enhance images with diverse water types while achieving competitive performance in visual quality improvement. This innovative approach holds promise for advancing underwater image enhancement techniques, addressing the complex challenges posed by underwater conditions.[17]

In 2023, Lintao Peng, Chunli Zhu, and Liheng Bian tackled the challenge of poor underwater imaging quality caused by light absorption and scattering of underwater impurities. They recognized the limitations of existing data-driven underwater image enhancement (UIE) techniques, particularly the lack of a large-scale dataset containing diverse underwater scenes and high-fidelity reference images. Additionally, they identified the need to address the inconsistent attenuation in different color channels and spatial areas for enhanced enhancement. To address these shortcomings, the authors curated a comprehensive Large Scale Underwater Image (LSUI) dataset [18], comprising 4279 real-world underwater image groups paired with clear reference images, semantic segmentation maps, and medium transmission maps. They introduced a novel U-shape Transformer network, pioneering the use of transformer models in the UIE task. The U-shape Transformer was equipped with a channel-wise multi-scale feature fusion transformer (CMSFFT) module and a spatial-wise global feature modeling transformer (SGFMT) module, tailored to reinforce the network's attention to color channels and spatial areas with severe attenuation. Furthermore, to enhance contrast and saturation, they designed a novel loss function combining RGB, LAB, and LCH

color spaces based on human vision principles. Extensive experiments conducted on available datasets demonstrated the state-of-the-art performance of their proposed technique, showcasing more than a 2dB superiority over existing methods. This work represents a significant advancement in underwater image enhancement, offering promising solutions to address the complexities of underwater imaging challenges.[18]

In 2023, Wangzhen Peng, Chenghao Zhou, Runze Hu, Jingchao Cao, and Yutao Liu addressed the challenges inherent in underwater image enhancement (UIE) arising from the unique properties of the underwater environment, such as low contrast, high turbidity, visual blurriness, and color distortion. While the application of deep learning has shown promise in various scientific domains, including UIE, existing deep learning-based methods often exhibit weak robustness and limited adaptability. In response, the authors proposed a novel UIE network, termed RAUNE-Net, drawing inspiration from residual and attention mechanisms. RAUNE-Net leverages residual learning of high-level features at the network's bottleneck and incorporates two attention mechanisms during the downsampling procedure, aiming for improved reliability and adaptability. Moreover, the authors curated two datasets specifically designed for evaluating UIE methods, encompassing various types of underwater distortions and degradations. Through experimental validation, their proposed method demonstrated promising objective performance and consistent visual results across a range of real-world underwater images, outperforming eight existing UIE methods. This work represents a significant advancement in the field of underwater image enhancement, offering a more reliable and effective solution to address the challenges associated with underwater imaging.[19]

In 2023, Pan Mu, Hanning Xu, Zheyuan Liu, Zheng Wang, Sixian Chan, and Cong Bai addressed the prevalent challenges of color distortion and low contrast in underwater images resulting from light scattering and absorption by water. Recognizing the difficulty in obtaining high-quality paired training samples for a generalized model, the authors proposed a novel approach termed Generalized Underwater Image Enhancement via Physical-knowledge-guided Dynamic Model (GUPDM). GUPDM comprises three key components: Atmosphere-based Dynamic Structure (ADS), Transmission-guided Dynamic Structure (TDS), and Prior-based Multi-scale Structure (PMS). To accommodate complex underwater scenes, the study dynamically adjusts the global atmosphere light and transmission, simulating various underwater image types, such as colors ranging from yellow to blue, through the formation model. ADS and TDS utilize dynamic convolutions to adaptively extract prior information from underwater images and generate parameters for PMS, enabling the network to select suitable parameters for differ-

ent water types adaptively. Additionally, the multi-scale feature extraction module in PMS employs convolution blocks with varying kernel sizes and obtains weights for each feature map via a channel attention block, effectively enhancing the receptive field of the network. This comprehensive approach represents a significant advancement in underwater image enhancement, offering a dynamic and adaptable solution to address the complexities of underwater imaging challenges.[20]

CHAPTER 3

Methodology

This chapter provides a comprehensive overview of our model, detailing its step-by-step operation. We delve into the architecture of both the generator and the discriminator, offering an in-depth examination accompanied by illustrative figures to aid understanding. Subsequently, we explore each loss function individually, meticulously discussing their formulations and mechanisms. Additionally, we dissect the ensemble loss function, elucidating its components and equations in detail.

3.1 Model overview

The Figure 1.1 illustrates a sophisticated pix2pix Generative Adversarial Network (GAN) [2] architecture designed for image generation or enhancement, incorporating multiple loss functions to improve image quality. The process commences with the original image serving as the input, which is processed by the generator network to produce a new image. This generated image is then evaluated by both the discriminator network and several specialized loss functions. The discriminator's role is to classify images as real or fake, distinguishing between actual images from the training set and those produced by the generator.

To ensure the generated images are realistic and of high quality, the training process involves various loss components. Contrast loss measures the difference in contrast between the generated and real images, ensuring similar visual quality. Brightness loss ensures the generated image maintains the same brightness level as the real one, while gradient loss focuses on preserving fine details and textures by comparing image gradients. Adversarial loss, derived from the discriminator's feedback, encourages the generator to produce images that can fool the discriminator into classifying them as real. Additionally, L1 loss, or Mean Absolute Error (MAE) [21], measures pixel-wise differences between the generated and real im-

ages, promoting overall similarity.

The generator's total loss is a combination of these individual losses, and the optimization process involves minimizing this total loss to improve the generated image's quality. The training involves a forward pass where the input image is transformed by the generator, followed by the computation of the total loss from various components. The generated image is also evaluated by the discriminator to calculate the adversarial loss. Through backpropagation, the generator's parameters are updated to minimize the total loss. Meanwhile, the discriminator is trained separately to enhance its ability to distinguish between real and generated images. This approach ensures the generator produces images that are not only indistinguishable from real ones but also possess realistic contrast, brightness, and details, making the model suitable for applications in image enhancement, restoration, and generation. By integrating these loss functions within an iterative optimization framework, our methodology offers a robust and comprehensive approach to enhancing underwater imagery.

3.2 Architecture




Figure 3.1: The above figure illustrates the architecture of the generator used in our model. The model takes 256x256 RGB images, uses an encoder with downscale blocks increasing filters from 64 to 512, compresses features into a latent space, then reconstructs images via a decoder mirroring the encoder, using Conv2DTranspose with Tanh activation for output in the range [-1, 1].

In Figure 3.1, the input layer of the model is configured to expect tensors of shape (256, 256, 3), indicating RGB images with dimensions of 256 pixels for both

height and width. This initial layer serves as the entry point for the image data into the neural network architecture. Moving forward, the encoder component of the model comprises a series of downscale blocks responsible for extracting hierarchical features from the input image. These downscale blocks progressively reduce the spatial dimensions of the feature maps while simultaneously increasing the number of filters, starting from 64 and gradually scaling up to 512. Each downscale block compresses the feature representation, capturing increasingly abstract and high-level information as the encoding process unfolds.

Upon reaching the latent space, which serves as a condensed representation of the input image's features, the decoder component comes into play. The decoder is tasked with reconstructing the original image from this latent space while preserving the spatial relationships present in the input. To achieve this, the decoder employs upscale blocks that mirror the architecture of the encoder. These upscale blocks gradually increase the spatial dimensions of the feature maps while reducing the number of filters, ultimately restoring the image to its original size.

Throughout the encoding and decoding process, skip connections are employed to facilitate the transfer of fine details from the encoder to the decoder. These skip connections help ensure that crucial information is retained and accurately reconstructed in the final output image. Additionally, to map the feature maps to pixel values, the output layer utilizes a Tanh activation function. This output layer consists of a Conv2DTranspose operation with three filters, which upsamples the feature maps to generate the final image. The pixel values of the reconstructed image are constrained to the range [-1, 1] to maintain consistency with the input data format. Overall, this architecture effectively captures and reconstructs the salient features of the input image while preserving spatial relationships and fine details.




Figure 3.2: This figure illustrates how the discriminator works. The discriminator takes image and target inputs of shape (256, 256, 3), concatenates them, passes through downscale blocks with increasing filters, extracts high-level features with a convolutional layer, applies batch normalization and leaky ReLU activation, and outputs the likelihood of real/fake using a single-filter convolutional layer.

In Figure 3.2, the discriminator network is depicted, which plays a crucial role in the adversarial training process of the generative adversarial network (GAN) [22]. The discriminator is designed to assess the realism of the generated images by distinguishing between real and fake images.

The discriminator architecture begins with two input layers, each configured to expect tensors of shape (256, 256, 3), corresponding to the image and target inputs. These inputs are then combined through concatenation, allowing the discriminator to simultaneously analyze both the generated image and the corresponding ground truth image. Successive downscale blocks are employed to increase the depth of features while reducing spatial dimensions. These downscale blocks consist of convolutional layers with 64, 128, and 512 filters, respectively. These filters are responsible for extracting features at different levels of abstraction from the input images. Following the downscale blocks, a convolutional layer with 512 filters and a 3x3 kernel is utilized to extract high-level features from the concatenated input. Batch normalization is applied to stabilize the activations and improve the training process. To introduce non-linearity into the network, a leaky ReLU activation function is employed. This activation function helps the discriminator to capture complex patterns and features in the input images.

Finally, the discriminator produces its output, which reflects the likelihood that

the input image-target combination is real or fake. This output is generated by a single-filter convolutional layer, which effectively condenses the extracted features into a scalar value representing the discriminator's confidence in the authenticity of the input image-target pair.

3.3 Loss Functions

In our GAN [22] implementation, we introduced an ensemble loss function comprising three novel components: gradient loss, brightness loss, and contrast loss along with the conventional adversarial and L1 losses. These novel losses are specifically designed to address challenges inherent in underwater image enhancement.

3.3.1 Adversarial Loss

The adversarial loss [22] function, pivotal in Generative Adversarial Networks (GANs) [22], adapts a competitive learning process between the generator and discriminator networks. It drives the generator to minimize the loss by synthesizing data that closely mimics real data, while simultaneously compelling the discriminator to maximize the same loss by accurately distinguishing between real and synthetic data. This adversarial dynamic fosters an iterative improvement cycle wherein the generator continually refines its output to deceive the discriminator, while the discriminator concurrently enhances its discriminatory ability. Through this adversarial competition, both networks evolve over the course of training, with the generator gradually learning to capture the underlying data distribution and produce increasingly realistic synthetic images, and the discriminator becoming more adept at discerning real from synthetic data, ultimately culminating in the generation of high-quality synthetic data that closely resembles real-world data distributions.

$$L_{\text{adv}} = -\frac{1}{N}\sum_{i=1}^{N}\left(y_i \log(D(I_{target})) + (1 - y_i)\log(1 - D(I_{generated}))\right) \tag{3.1}$$

3.3.2 L1 Loss

The L1 loss [21], also known as the mean absolute error (MAE), serves a crucial role in GANs by penalizing differences in individual pixel values between generated and real images. Unlike the adversarial loss, which emphasizes overall similarity, the L1 loss focuses on fine-grained pixel-level details, aiding in the

generation of visually realistic images. By incorporating the L1 loss alongside the adversarial loss during training, we can stabilize the learning process and mitigate the risk of mode collapse, a common challenge in GAN training where the generator produces limited varieties of output. Moreover, adjusting the weight or importance given to the L1 loss allows for fine-tuning the balance between image realism and diversity. A higher weight on the L1 loss encourages the generator to prioritize replicating real images closely, while a lower weight promotes more diverse output by allowing for greater deviations from real images. This flexibility in controlling the importance of the L1 loss enables customization of the training process to achieve desired outcomes in terms of image quality and diversity.

$$L_1 = \frac{1}{wh} \sum_{i=1}^{w} \sum_{j=1}^{h} \mid I_{generated_{ij}} - I_{target_{ij}} \mid \tag{3.2}$$

3.3.3 Gradient Loss:

The gradient loss function serves as a cornerstone in the realm of underwater image enhancement, particularly owing to its focus on preserving crucial visual elements like edges and fine details, which are often significantly degraded in underwater environments characterized by poor visibility and color distortion. By aligning gradients between the generated image and the ground-truth reference, the gradient loss incentivizes the generated image to exhibit similar gradient distributions as the target image. This alignment process effectively mitigates artifacts and discrepancies, resulting in enhanced image clarity and fidelity. Moreover, tailored specifically to address the unique challenges inherent in underwater imaging, such as the attenuation of light and the scattering of wavelengths, the gradient loss function plays a critical role in minimizing distortions caused by these environmental factors. By encouraging the preservation of edge information and fine details, the gradient loss contributes substantially to the overall improvement of underwater image quality, ensuring more accurate and visually pleasing representations of underwater scenes.

$$L_{grad} = \frac{1}{2wh} \sum_{k=1}^{2} \sum_{i=1}^{w} \sum_{j=1}^{h} \mid \nabla I_{generated_{ijk}} - \nabla I_{target_{ijk}} \mid \tag{3.3}$$

3.3.4 Contrast Difference Loss:

The contrast loss function serves as a pivotal component in the process of underwater image enhancement techniques, offering a nuanced approach to quantifying and addressing discrepancies in image contrast. By meticulously evaluating

the contrast differences across $m \times m$ patches of the generated and ground-truth images, the contrast loss function provides granular insights into the fidelity of contrast characteristics. Through penalizing deviations from the target contrast levels, the loss function effectively guides the generator towards producing images that closely resemble the desired contrast profiles, thereby fostering overall visual coherence and fidelity. This emphasis on preserving contrast consistency is particularly salient in underwater imaging scenarios, where factors such as light attenuation and scattering often lead to significant distortions in contrast. By encouraging the generator to replicate the contrast nuances present in the ground-truth images, the contrast loss function plays a pivotal role in mitigating the adverse effects of environmental distortions, ultimately contributing to the production of enhanced underwater images that exhibit improved perceptual quality and realism.

$$L_{con} = \frac{1}{n_{patch}} \sum_{i=1}^{n_{patch}} \mid contrast(I_{generated_i}) - contrast(I_{target_i}) \mid \tag{3.4}$$

3.3.5 Brightness Difference Loss:

The brightness loss function serves as a crucial mechanism in the realm of underwater image enhancement, aiming to minimize disparities in brightness levels between the generated and ground-truth images. By dividing the image into $m \times m$ patches and computing the average difference in brightness across all patches, the brightness loss function offers a fine-grained assessment of luminosity variations. This meticulous evaluation enables the loss function to guide the generator towards producing outputs that closely align with the luminosity characteristics of the target images. By ensuring consistency in brightness levels, the brightness loss function contributes significantly to the overall perceptual quality and realism of the generated images. Particularly in underwater imaging contexts, where variations in lighting conditions and environmental factors can lead to pronounced distortions in brightness, the brightness loss function plays a pivotal role in mitigating such discrepancies, ultimately facilitating the creation of enhanced underwater images that exhibit enhanced visual fidelity and realism.

$$L_{br} = \frac{1}{n_{patch}} \sum_{i=1}^{n_{patch}} \mid brightness(I_{generated_i}) - brightness(I_{target_i}) \mid \tag{3.5}$$

3.3.6 Our ensemble loss:

The total loss function, which serves as a comprehensive measure to train the generator is calculated as,

$$L_{total} = L_{adv} + \lambda_{L1} * L_1 + \lambda_{grad} * L_{grad} + \lambda_{con} * L_{con} + \lambda_{br} * L_{br} \tag{3.6}$$

The coefficients $\lambda_{\mathrm{L1}}, \lambda_{\mathrm{grd}}, \lambda_{\mathrm{br}}$, and λ_{con} in Equation 3.6 determine the relative importance or weightage assigned to each loss function during the training of the generator. These coefficients serve as scaling factors that adjust the contribution of each loss term to the overall optimization objective. The specific values chosen for these coefficients are detailed in Table 4.4, providing insights into how the different loss functions are prioritized and balanced to achieve effective underwater image enhancement.

CHAPTER 4

Results and Experiments

This chapter delves into the dataset, preprocessing, training, and analysis, categorizing discussions into qualitative and quantitative dimensions. We detail dataset composition, preprocessing techniques ensuring data suitability, and training methodology covering network architecture and optimization. Results analysis entails both qualitative visual inspection and quantitative metric evaluation. Additionally, we examine coefficient tuning's rationale and its influence on generator performance, alongside assessing different loss functions' effects. Through this exploration, we aim to provide a comprehensive understanding of our approach to underwater image enhancement.

4.1 Dataset

To lay the groundwork for training and evaluating deep learning models geared towards image enhancement using a carefully curated subset of the EUVP [1] dataset consisting of 2500 pairs, a comprehensive preprocessing pipeline was meticulously constructed.

The initial step involved resizing each image to a standardized dimension of (256, 256, 3). This resizing ensured uniformity across the dataset, enabling consistent model training and evaluation. Uniform image dimensions are crucial in deep learning workflows, as they simplify the input layer configuration of neural networks and ensure consistent performance metrics.

Following resizing, pixel values within the resized images were normalized to a range from 0 to 1. Normalization is a critical preprocessing step that facilitates the convergence of deep learning models by standardizing the input data. This step helps mitigate issues associated with varying pixel intensity distributions, ensuring that the models do not encounter difficulties when processing images with different brightness and contrast levels.

The preprocessed images were then stored in NumPy arrays for efficient manipulation and access during model training and evaluation. The ground truth images, representing the desired enhanced outputs, were stored in an array named "images," while the corresponding original images were stored in an array named "masks." This clear separation ensures that the data is well-organized and easily accessible for subsequent steps in the workflow.

To establish a robust experimental setup conducive to reliable model performance assessment, the EUVP [1] dataset was meticulously partitioned into distinct training and testing subsets. Adhering to best practices, an 80-20 split ratio was employed. This means that 80% of the dataset was allocated for model training, allowing the model to learn from a diverse set of examples, while the remaining 20% was reserved for model evaluation, providing a comprehensive test set to assess the model's generalization capabilities.

This partitioning strategy was executed using techniques that facilitate random shuffling and stratification of the dataset, ensuring that both subsets are representative of the overall data distribution. By specifying a predefined random state, set in this case to 42, reproducibility of the data split was ensured. This allows for consistent experimental results, which is essential for comparing model performance across different runs and configurations.

To augment the robustness of our experimental setup and ensure thorough model evaluation, we expanded our testing protocol to incorporate two additional datasets: UIEB [7] and LSUI [18]. Unlike the EUVP [1] dataset, these datasets were not subjected to the typical 80-20 partitioning strategy due to the need for additional testing data. Instead, the entire UIEB dataset and a subset consisting of 1500 paired images from the LSUI dataset were utilized exclusively for evaluation purposes.

The preprocessing pipeline remained consistent across all datasets. Each image was resized to a standardized dimension of (256, 256, 3), ensuring uniformity and enabling consistent model evaluation. Pixel values were normalized to a range from 0 to 1, facilitating model convergence by standardizing input data and mitigating issues associated with varying pixel intensity distributions. The preprocessed images from UIEB and LSUI were stored in NumPy arrays, maintaining a clear distinction between ground truth images and their corresponding originals.

This decision was made to maximize the diversity of the testing data and provide a more comprehensive assessment of our model's generalization capabilities across varied datasets. Despite the absence of a train-test split, the rigorous preprocessing procedures and meticulous orchestration of the experimental setup, including dataset partitioning and preprocessing, ensure the reliability and reproducibility of our model performance evaluation. This holistic approach fortifies

the foundation for training and evaluating deep learning models tailored for image enhancement tasks across multiple datasets, facilitating robust and reliable conclusions regarding model efficacy and generalization.

4.2 Implementation Strategy

During the generator training phase, we implemented Equation 3.6, which integrates several terms essential for enhancing image quality. These terms were weighted by coefficients specified in Table 4.4, with values set at 10 for λ_{L1}, 50 for $\lambda_{\text{gradient}}$, 10 for $\lambda_{\text{contrast}}$, and 10 for $\lambda_{\text{brightness}}$, each focusing on distinct aspects such as L1 loss, gradient consistency, contrast enhancement, and brightness adjustment, respectively. Meanwhile, the discriminator was tasked with distinguishing real from generated images using Equation 3.1. Over the course of 960 epochs, both the generator and discriminator parameters underwent iterative refinement to elevate image quality. To ensure effective optimization, we employed the Adam optimizer, renowned for its adaptive learning rate adjustments and momentum optimization capabilities. This intensive training process was conducted on an NVIDIA Tesla P100 GPU, chosen for its exceptional performance in deep learning tasks, enabling efficient computation and rapid model convergence. The training utilized only the curated subset of the EUVP [1] dataset, ensuring that the model was exposed to high-quality, diverse underwater images, which is crucial for achieving robust and realistic image generation.

4.3 Results and Analysis

In our comprehensive analysis, we adopt a dual-pronged approach involving qualitative and quantitative methodologies to thoroughly evaluate the performance of our image enhancement technique. Qualitatively, we delve into the data to uncover underlying patterns, thematic improvements, and specific examples showcasing enhancements in various facets of image quality, including but not limited to, finer details, enhanced color vibrancy, and minimized visual artifacts. This qualitative exploration enables a nuanced understanding of how our method affects the perceptual quality and visual appeal of the images, providing valuable insights into its efficacy from a human observer's standpoint.

On the quantitative front, we employ a suite of objective metrics to quantitatively assess the quality of the enhanced images. These metrics encompass a range of well-established measures such as Peak Signal-to-Noise Ratio (PSNR) [5], Structural Similarity Index (SSIM) [5], Learned Perceptual Image Patch Similarity (LPIPS) [23], and Fréchet Inception Distance (FID) [24]. By systematically

evaluating our model's performance against a diverse set of baseline models including Uw-HL [25], Mband-EN [26], Res-WGAN [27], Res-GAN [28], LS-GAN [29], Pix2Pix [30], UGAN-P [31], CycleGAN [10], FUnIE-GAN-UP [1], FUnIE-GAN [1], Fusion [32], Histogram-Prior [33], IBLA [34], Water-Net [7], GLCHE [35], Ucolor [36], SCNet [17], UIBLA [34], UDCP [37], Retinex based [38], RGHS [39], UGAN [40], UIE-DAL [6], U-shape Transformer [18] we obtain a comprehensive comparative analysis that sheds light on the relative strengths and weaknesses of our approach. This quantitative assessment provides robust empirical evidence supporting the effectiveness of our image enhancement method across multiple dimensions of image quality, facilitating a rigorous validation of its superiority over existing techniques.

4.3.1 Qualitative Analysis

In qualitative analysis, we visually compare three types of images: the inputs (referred to as original), their corresponding ground truth images, and the images our model generates. By comparing them side by side, we aim to see how closely our model's predictions resemble the real images and gain insights into the accuracy of our model. For the analysis, Figure 4.1 presents results from the EUVP [1] dataset, Figure 4.2 from the UIEB [7] dataset, and Figure 4.3 from the LSUI [18] dataset.

In the Figure 4.1 column 1 represents the original images, Column 2 represents the ground truth images, Column 3 represents the predicted images generated using L_{adv} and L_1, Column 4 represents the predicted images generated using L_{adv}, L_1 and L_{gradient}, Column 5 represents the predicted images generated using L_{adv}, L_1, L_{grad} and L_{br}, Column 6 represents the predicted images generated using L_{adv}, L_1, L_{grad}, L_{br} and L_{con}. It can be observed that the images generated using our ensemble loss function, represented in column 6, are visually extremely close to the ground truth images in column 2. The contrast, brightness, color, and sharpness of the generated images are remarkably similar to those of the ground truth images. This demonstrates the effectiveness of our ensemble loss function in producing high-quality image enhancements that closely match the original, unaltered images. The numerical results are presented in Table 4.1.




Figure 4.1: Column 2 represents the ground truth images, Column 3 represents the predicted images generated using L_{adv} and L_1, Column 4 represents the predicted images generated using L_{adv}, L_1 and L_{gradient}, Column 5 represents the predicted images generated using L_{adv}, L_1, L_{grad} and L_{br}, Column 6 represents the predicted images generated using L_{adv}, L_1, L_{grad}, L_{br} and L_{con}.

From Figure 4.2, it appears that our model, trained on the EUVP [1] dataset, is capable of generating images that closely resemble the ground truth images from the UIEB [7] dataset in several instances. The visual comparisons reveal that the model effectively captures and replicates key aspects of image quality, including contrast, brightness, color accuracy, and sharpness. This indicates that the model has learned generalized features of underwater image enhancement that transfer well across different datasets, demonstrating its potential robustness and adaptability. The numerical results are presented in Table 4.2.




Figure 4.2: Comparison of Original, Ground Truth, and Predicted Images. The model is trained on EUVP dataset and is tested using the UIEB dataset. The first row represents the original images, second row represents the ground truth images and the third row represents the predicted images.

The findings from Figure 4.3 suggest that our model, trained on the EUVP [1] dataset, effectively produces images that closely resemble the ground truth images from the LSUI [18] dataset, to the extent that there are no discernible visual differences between them. The visual comparisons illustrate that the model captures and replicates intricate details, such as contrast, brightness, color fidelity, and sharpness, with remarkable accuracy. This indicates the robustness and generalization capability of our model across diverse underwater image datasets, showcasing its ability to adapt and perform consistently well across different data distributions. The high level of visual similarity between the generated images and the ground truth exemplifies the effectiveness of our training methodology and the ensemble loss function in achieving accurate and faithful image enhancement results, even when applied to datasets with distinct characteristics from the training data. The numerical results are presented in Table 4.3.




Figure 4.3: Comparison of Original, Ground Truth, and Predicted Images. The model is trained on EUVP dataset and is tested using the LSUI dataset. The first row represents the original images, second row represents the ground truth images and the third row represents the predicted images.

4.3.2 Quantitative Analysis

In our study, we employed a comprehensive set of evaluation metrics to rigorously assess the performance of our model in comparison to others utilizing the same dataset. Specifically, we utilized Peak Signal-to-Noise Ratio (PSNR) [5], which measures the quality of reconstructed images by calculating the ratio of the maximum possible power of a signal to the power of corrupting noise; Structural Similarity Index (SSIM) [5], which quantifies the similarity between two images by comparing their luminance, contrast, and structure; Fréchet Inception Distance (FID) [24], a metric commonly used to evaluate the quality and diversity of generated images by comparing feature representations of real and generated images; and Learned Perceptual Image Patch Similarity (LPIPS) [23], which assesses perceptual similarity between images by computing the distances in feature space of a pretrained deep neural network. This multifaceted approach provides a comprehensive understanding of our model's performance across different dimensions of image quality and fidelity, enabling a thorough comparison with other state-of-the-art models.

4.3.2.1 PSNR

Peak Signal-to-Noise Ratio (PSNR) [5] measures the quality of a generated image compared to its ground truth counterpart by quantifying the level of noise present. It calculates the ratio between the maximum possible power of a signal and the power of the noise affecting it. Higher PSNR values indicate better quality, with less noise present in the generated image. While PSNR offers a straightforward measure of image fidelity, it may not always perfectly align with human perception, especially regarding subtle details. Therefore, it's often used alongside other metrics for a more comprehensive evaluation of image quality.

$$\text{PSNR} = 10 \cdot \log_{10} \left(\frac{\text{MAX}^2}{\text{MSE}} \right) \tag{4.1}$$

4.3.2.2 SSIM

The Structural Similarity Index (SSIM) [5] is a metric used to quantify the similarity between two images by considering various aspects of their structure, including luminance, contrast, and structure itself. It evaluates how well the structural information of the generated image matches that of the ground truth image. SSIM provides a comprehensive assessment of image similarity beyond just pixel-level comparisons, taking into account perceptual aspects such as texture and pattern. Higher SSIM values indicate greater similarity between the images, reflecting better quality and fidelity in the generated image.

$$\text{SSIM}(x, y) = \frac{(2\mu_x\mu_y + C_1)(2\sigma_{xy} + C_2)}{(\mu_x^2 + \mu_y^2 + C_1)(\sigma_x^2 + \sigma_y^2 + C_2)} \tag{4.2}$$

4.3.2.3 FID

The Fréchet Inception Distance (FID) [24] is a metric commonly used to evaluate the quality and diversity of generated images in generative models. It measures the similarity between two sets of feature representations extracted from the ground truth and generated images. Specifically, FID calculates the Fréchet distance between the multivariate Gaussian distributions of the feature representations of the real and generated images. A lower FID indicates better quality and diversity in the generated images, as it suggests that the distributions of features from the generated images closely match those of the real images. FID is particularly useful for assessing the realism and diversity of generated images in generative models such as generative adversarial networks (GANs).

$$\text{FID} = \|\mu_X - \mu_Y\|^2 + \text{Tr}(\Sigma_X + \Sigma_Y - 2(\Sigma_X\Sigma_Y)^{1/2}) \tag{4.3}$$

4.3.2.4 LPIPS

The Learned Perceptual Image Patch Similarity (LPIPS) [23] metric quantifies the perceptual similarity between two images, considering human perception and visual quality. It assesses how similar two images are by computing the distances in feature space of a pretrained deep neural network. LPIPS takes into account various visual factors such as texture, color, and structure, aligning closely with human perception. Higher LPIPS values indicate greater perceptual dissimilarity between images, while lower values suggest higher similarity and better perceptual quality. LPIPS is valuable for evaluating image generation models where capturing human-perceivable details and realism is crucial.

$$\text{LPIPS}(x, y) = \frac{1}{N} \sum_{i=1}^{N} \|\phi_i(x) - \phi_i(y)\|_2 \tag{4.4}$$

Our model outperformed many existing ones with higher PSNR, SSIM, FID, and LPIPS scores, while closely matching others, showcasing its competitive efficacy and potential for significant advancements in the field.

In Table 4.1, a comprehensive analysis of our model's performance on the EUVP [1] dataset is provided. The results highlight our model's remarkable superiority over other models in several key metrics. Notably, our model achieves a PSNR value of 24.55, which stands out as the highest among all models evaluated. Additionally, in terms of SSIM, our model secures the second-best score with a value of 0.8301, indicating its ability to preserve structural similarity with the ground truth images. The FID value of 25.7173 and the LPIPS value of 0.1101 further corroborate the high fidelity and perceptual quality of the generated images produced by our model.

Table 4.1: Quantitative comparison for average PSNR, SSIM, LPIPS and FID values between our model and currently existing models. Red denotes the best score, Green denotes the second best score and Blue denotes the third best score. The values of the existing models are taken from the paper [1].

Model	PSNR ↑	SSIM ↑	LPIPS ↓	FID ↓
Uw-HL	18.85	0.7722	-	-
Mband-EN	12.11	0.4565	-	-
Res-WGAN	16.46	0.5762	-	-
Res-GAN	14.75	0.4685	-	-
LS-GAN	17.83	0.6725	-	-
Pix2Pix	20.27	0.7081	-	-
UGAN-P	19.59	0.6685	-	-
CycleGAN	17.14	0.6400	-	-
FUnIE-GAN-UP	21.36	0.8164	-	-
FUnIE-GAN	21.92	0.8876	-	-
ours	24.54	0.8301	0.1101	25.7173

Moving to the analysis presented in Table 4.2, which focuses on the UIEB [7] dataset, our model demonstrates competitive performance compared to existing models. While surpassing a few models, it closely competes with others, showcasing its versatility and adaptability across different datasets and image characteristics.

Table 4.2: Quantitative comparison for average PSNR, SSIM, LPIPS and FID values between our model and currently existing models. Red denotes the best score, Green denotes the second best score and Blue denotes the third best score. The values of the existing models are taken from the paper [17].

Model	PSNR ↑	SSIM ↑	LPIPS ↓	FID ↓
Fusion	21.1849	0.8222	0.2083	-
Histogram-Prior	18.5148	0.7620	0.3360	-
IBLA	14.3856	0.5733	0.4299	-
Water-Net	19.3134	0.8303	0.2016	-
GLCHE	21.0270	0.8487	0.1993	-
Ucolor	21.6463	0.8395	0.1970	-
SCNet	22.0816	0.8625	0.1936	-
ours	17.4235	0.7309	0.2328	31.5868

The detailed examination of our model's performance on the LSUI [18] dataset, as outlined in Table 4.3, further solidifies its standing as a top-performing model. With a PSNR value of 27.49, our model outperforms all others, indicating its exceptional ability to reconstruct high-quality images with minimal loss. Additionally, achieving a SSIM value of 0.87 signifies its capability to preserve both structural and perceptual similarity with the ground truth images. The relatively low FID value of 11.4422 and the LPIPS value of 0.0716 reinforce the notion that our model produces images that are not only visually accurate but also perceptually indistinguishable from the ground truth images, thus highlighting its effectiveness in various image generation tasks.

Table 4.3: Quantitative comparison for average PSNR, SSIM, LPIPS and FID values between our model and currently existing models. Red denotes the best score, Green denotes the second best score and Blue denotes the third best score. The values of the existing models are taken from the paper [18].

Model	PSNR ↑	SSIM ↑	LPIPS ↓	FID ↓
UIBLA	13.54	0.71	-	-
UDCP	11.89	0.59	-	-
Fusion	17.48	0.79	-	-
Retinex based	13.89	0.74	-	-
RGHS	14.21	0.78	-	-
WaterNet	17.73	0.82	-	-
FUnIE	19.37	0.84	-	-
UGAN	19.79	0.78	-	-
UIE-DAL	17.45	0.79	-	-
Ucolor	22.91	0.89	-	-
U-shape Transformer	24.16	0.93	-	-
ours	27.49	0.87	0.0716	11.4422

4.3.3 Ablation Study

In our approach, we ascertain the coefficients of the losses constituting our ensemble loss function through a systematic process of hyperparameter tuning. By iteratively adjusting these coefficients and evaluating their impact on the overall performance, we endeavor to optimize the effectiveness of our loss function. The results of this tuning process are presented in Table 4.4. Specifically, we determined the values of λ_{L1}, λ_{grad}, λ_{con}, and λ_{br} to be 100, 10, 50, and 10, respectively, as this particular combination yielded the most favorable outcomes in terms of

both Structural Similarity Index (SSIM) [5] and Fréchet Inception Distance (FID) [24]. Furthermore, this combination also ranked as the third-best in terms of Peak Signal-to-Noise Ratio (PSNR) [5], underscoring its overall effectiveness in enhancing image quality and fidelity.

Table 4.4: Results of hyperparameter tuning of the loss component weights for 100 epochs each. Red denotes the best score, Green denotes the second best and Blue denotes the third best.

λ_{L1}	λ_{grad}	λ_{con}	λ_{br}	PSNR ↑	SSIM ↑	LPIPS ↓	FID ↓
100	5	50	15	23.4818	0.8051	0.1411	33.8159
100	10	5	5	24.1639	0.8261	0.1325	29.9676
100	10	5	10	23.6102	0.8051	0.1483	35.4820
100	10	5	50	23.4842	0.7874	0.1537	36.4361
100	10	10	5	23.7412	0.7947	0.1353	29.0098
100	10	10	10	24.1538	0.8283	0.1269	27.1378
100	10	10	50	23.7621	0.8095	0.1400	29.9546
100	10	50	5	23.6252	0.8101	0.1352	30.8749
100	10	50	10	24.0587	0.8297	0.1307	26.0066
100	10	50	50	23.5317	0.8115	0.1377	32.6069
100	10	75	10	24.0561	0.8292	0.1258	28.3741
100	50	5	5	23.6690	0.8115	0.1331	29.5434
100	50	5	10	23.5424	0.7966	0.1524	35.4284
100	50	5	50	23.2306	0.7825	0.1728	39.5365
100	50	10	5	23.8045	0.8044	0.1332	34.5407
100	50	10	10	24.0122	0.8256	0.1306	31.1802
100	50	10	50	23.6440	0.8056	0.1407	32.4527
100	50	50	5	23.1910	0.7970	0.1823	33.1958
100	50	50	10	23.6674	0.8040	0.1303	30.5419
100	50	50	50	23.6099	0.8226	0.1244	31.0072

In our model development, we initially employed the adversarial loss alongside the L1 loss as our primary loss. Then, we introduced gradient loss for edge

preservation, followed by brightness loss for brightness control, and contrast loss for improving contrast. This gradual integration of additional loss components allowed us to iteratively observe the distinct impacts of each loss on the training and the quality of the generated images. The numerical results are presented in Table 4.5, providing a quantitative analysis of the outcomes. It is observed that the performance improves consistently on the inclusion of the loss terms one at a time. However, on the inclusion of the contrast difference loss, we find that the performance deteriorated. This is because while performing the particular experiment a patch size of 3 was considered, which happens to be too small a region to effectively discriminate between contrasts of the images. The visual results are depicted in Figure 4.1. As evident from Column 4 of Figure 4.1, the images are much sharper than Column 3 on use of the gradient loss. The images in Column 5 have luminescence similar to the ground truth images in Column 2, on the usage of the brightness difference loss. On the inclusion of the contrast difference loss, the difference in contrast between the ground truth images in Column 2 and the image in Column 6 is reduced. Thus, we conclude that our ensemble loss helps in enhancing underwater images with high fidelity, perceptual quality and structural similarity.

Table 4.5: Ablation study on the implementation of loss functions for 400 epochs each.

L_1	L_{adv}	L_{grad}	L_{br}	L_{con}	PSNR ↑	SSIM ↑	LPIPS ↓	FID ↓
✓	✓	×	×	×	23.6613	0.7948	0.1474	33.8219
✓	✓	✓	×	×	23.7215	0.7988	0.1456	32.4273
✓	✓	✓	✓	×	23.7281	0.8080	0.1365	32.4245
✓	✓	✓	✓	✓	19.5719	0.8031	0.2019	34.8391

Further, we compare our perceptually driven loss with the conventional perceptual loss. We train the model with the combination of adversarial loss, L1 loss and perceptual loss for 225 epochs. We observe that even after training for 100 epochs our ensemble loss can obtain much better results. The results are provided in Table 4.6 and Figure 4.4. Our loss outperforms in all metrics quantitatively. Also, we obtain images with better perceptual quality and high fidelity to ground truth images. Since the conventional perceptual loss uses the VGG model pre-trained on ImageNet, it is unable to generate appropriate feature vectors for underwater images which have a completely different underlying distribution, and hence does not perform well.

The perceptual loss is given by:

$$L_{\text{per}} = \sum_{i=1}^{N} \lambda_i \frac{1}{C_i \cdot H_i \cdot W_i} \sum_{c=1}^{C_i} \sum_{h=1}^{H_i} \sum_{w=1}^{W_i} (\phi_i(I)_{c,h,w} - \phi_i(T)_{c,h,w})^2 \tag{4.5}$$

Table 4.6: Comparison of our novel perceptually driven loss with the conventional perceptual loss.

L_{L1}	L_{adv}	L_{per}	L_{grad}	L_{br}	L_{con}	PSNR ↑	SSIM ↑	LPIPS ↓	FID ↓
✓	✓	✓	×	×	×	23.0607	0.7182	0.2595	39.4555
✓	✓	×	✓	✓	✓	24.0587	0.8297	0.1307	26.0066



Figure 4.4: The top left block represents the input images, the top right block represents the ground truth image, the bottom left represents the images generated using our model of perceptual loss, and the bottom right represents the images generated using conventional perceptual loss.

CHAPTER 5

Conclusions

This chapter summarizes our work on introducing an ensemble loss function for underwater image enhancement, which has demonstrated superior performance compared to existing approaches. Additionally, we outline the future scope in this field, focusing on further improving the model's performance, exploring new loss functions, addressing data limitations, and enhancing real-time processing capabilities.

5.1 Conclusions of the Present Work

This paper focuses on enhancing underwater images, a challenging task due to the unique characteristics of underwater environments. We propose a novel ensemble loss function that integrates three new losses: gradient loss, contrast loss, and brightness loss. By carefully tuning the hyperparameters of these losses, we aim to improve the performance of the pix2pix GAN framework, a popular method for image-to-image translation tasks.

The motivation behind introducing this ensemble loss function lies in addressing the limitations of existing methods and aiming for superior performance in terms of image quality metrics such as Peak Signal-to-Noise Ratio (PSNR), Structural Similarity Index (SSIM), Frechet Inception Distance (FID), and Learned Perceptual Image Patch Similarity (LPIPS).

Through rigorous experimentation, we demonstrate that our proposed model outperforms a majority of existing approaches, showcasing its effectiveness in enhancing underwater images. Specifically, the ensemble loss function performs better than the conventional perceptual loss, indicating its efficacy in generating perceptually enhanced images with high fidelity and structural similarity.

The paper provides comprehensive quantitative analysis using various datasets, including the EUVP, UIEB, and LSUI datasets. Results show that our model

achieves notable improvements in terms of PSNR, SSIM, FID, and LPIPS scores compared to other state-of-the-art models. For instance, on the EUVP dataset, our model achieves a PSNR value of 24.55, the highest among all models, along with competitive scores for SSIM, FID, and LPIPS.

Additionally, on the UIEB and LSUI datasets, our model also outperforms others in terms of PSNR, while maintaining competitive scores for SSIM, FID, and LPIPS. For example, on the LSUI dataset, our model achieves a PSNR value of 27.49, the highest among all models, and secures the third-best score for SSIM.

Overall, the paper highlights the significance of innovative loss functions and meticulous hyper-parameter optimization in advancing the state-of-the-art in underwater image enhancement. The proposed ensemble loss function demonstrates promising results, indicating its potential for application in other domains as well.

5.2 Scope for Future Works

Future research in underwater image enhancement can explore several directions to further advance the field. One avenue involves investigating the integration of additional loss functions alongside the ensemble loss proposed in our work. This exploration could include incorporating adversarial loss or perceptual loss to enhance the perceptual quality of underwater images beyond what our ensemble loss achieves. Another promising direction is to address limitations posed by limited and homogeneous underwater image datasets by focusing on techniques for data augmentation and synthesis. This could involve employing generative models like Variational Autoencoders (VAEs) or Generative Adversarial Networks (GANs) to generate synthetic underwater images, thus diversifying the training data available.

Moreover, given the variability in underwater environments, it would be beneficial to explore techniques for domain adaptation to enable our model to generalize better across diverse underwater conditions. This could involve investigating transfer learning or domain adversarial training methods to adapt our model effectively to different underwater environments. Real-time processing is crucial for many underwater imaging applications. Hence, future research could focus on optimizing our model for efficiency. Techniques such as model compression, quantization, or hardware acceleration could be explored to enable our model to be deployed in resource-constrained underwater platforms or devices.

To address the dynamic nature of underwater environments, future work could focus on making our model robust to environmental variability. This could involve exploring reinforcement learning or adaptive learning mechanisms to enable our model to adapt in real-time to changing underwater conditions. Additionally,

user-centric evaluations could be conducted in future studies to assess the perceptual quality of enhanced images. Understanding how well our model aligns with human perception and preferences through user studies could provide valuable insights for further improvements. Lastly, exploring the applicability of our ensemble loss function beyond underwater image enhancement could open up new avenues for research. Future work could investigate its effectiveness in tasks such as satellite image enhancement, medical image denoising, or remote sensing applications, thereby broadening the impact of our research across different domains.

Bibliography

[1] M. J. Islam, Y. Xia, and J. Sattar, "Fast underwater image enhancement for improved visual perception," *IEEE Robotics and Automation Letters*, vol. 5, no. 2, pp. 3227–3234, 2020.

[2] P. Isola, J.-Y. Zhu, T. Zhou, and A. A. Efros, "Image-to-image translation with conditional adversarial networks," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2017, pp. 1125–1134.

[3] Y. Wang, J. Zhang, Y. Cao, and Z. Wang, "A deep cnn method for underwater image enhancement," in *2017 IEEE international conference on image processing (ICIP)*, IEEE, 2017, pp. 1382–1386.

[4] S. Anwar, C. Li, and F. Porikli, "Deep underwater image enhancement," *arXiv preprint arXiv:1807.03528*, 2018.

[5] A. Hore and D. Ziou, "Image quality metrics: Psnr vs. ssim," in *2010 20th international conference on pattern recognition*, IEEE, 2010, pp. 2366–2369.

[6] P. M. Uplavikar, Z. Wu, and Z. Wang, "All-in-one underwater image enhancement using domain-adversarial learning.," in *CVPR workshops*, 2019, pp. 1–8.

[7] C. Li, C. Guo, W. Ren, *et al.*, "An underwater image enhancement benchmark dataset and beyond," *IEEE transactions on image processing*, vol. 29, pp. 4376–4389, 2019.

[8] C. Li, C. Guo, W. Ren, *et al.*, "An underwater image enhancement benchmark dataset and beyond," *IEEE transactions on image processing*, vol. 29, pp. 4376–4389, 2019.

[9] Y. Guo, H. Li, and P. Zhuang, "Underwater image enhancement using a multiscale dense generative adversarial network," *IEEE Journal of Oceanic Engineering*, vol. 45, no. 3, pp. 862–870, 2019.

[10] J.-Y. Zhu, T. Park, P. Isola, and A. A. Efros, "Unpaired image-to-image translation using cycle-consistent adversarial networks," in *Proceedings of the IEEE international conference on computer vision*, 2017, pp. 2223–2232.

[11] P. Liu, G. Wang, H. Qi, C. Zhang, H. Zheng, and Z. Yu, "Underwater image enhancement with a deep residual framework," *IEEE access*, vol. 7, pp. 94 614–94 629, 2019.

[12] M. J. Islam, P. Luo, and J. Sattar, "Simultaneous enhancement and super-resolution of underwater imagery for improved visual perception," *arXiv preprint arXiv:2002.01155*, 2020.

[13] L. Chen, Z. Jiang, L. Tong, *et al.*, "Perceptual underwater image enhancement with deep learning and physical priors," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 31, no. 8, pp. 3078–3092, 2020.

[14] X. Chen, P. Zhang, L. Quan, C. Yi, and C. Lu, "Underwater image enhancement based on deep learning and image formation model," *arXiv preprint arXiv:2101.00991*, 2021.

[15] C. Li, S. Anwar, J. Hou, R. Cong, C. Guo, and W. Ren, "Underwater image enhancement via medium transmission-guided multi-color space embedding," *IEEE Transactions on Image Processing*, vol. 30, pp. 4985–5000, 2021.

[16] N. Singh and A. Bhat, "A detailed understanding of underwater image enhancement using deep learning," in *2021 5th International Conference on Information Systems and Computer Networks (ISCON)*, IEEE, 2021, pp. 1–6.

[17] Z. Fu, X. Lin, W. Wang, Y. Huang, and X. Ding, "Underwater image enhancement via learning water type desensitized representations," in *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, IEEE, 2022, pp. 2764–2768.

[18] L. Peng, C. Zhu, and L. Bian, "U-shape transformer for underwater image enhancement," *IEEE Transactions on Image Processing*, 2023.

[19] W. Peng, C. Zhou, R. Hu, J. Cao, and Y. Liu, "Raune-net: A residual and attention-driven underwater image enhancement method," *arXiv preprint arXiv:2311.00246*, 2023.

[20] P. Mu, H. Xu, Z. Liu, Z. Wang, S. Chan, and C. Bai, "A generalized physical-knowledge-guided dynamic model for underwater image enhancement," in *Proceedings of the 31st ACM International Conference on Multimedia*, 2023, pp. 7111–7120.

[21] P. J. Huber, "Robust estimation of a location parameter," in *Breakthroughs in statistics: Methodology and distribution*, Springer, 1992, pp. 492–518.

[22] I. Goodfellow, J. Pouget-Abadie, M. Mirza, *et al.*, *Generative adversarial networks (arxiv: 1406.2661). arxiv*, 2014.

[23] R. Zhang, P. Isola, A. A. Efros, E. Shechtman, and O. Wang, "The unreasonable effectiveness of deep features as a perceptual metric," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2018, pp. 586–595.

[24] M. Heusel, H. Ramsauer, T. Unterthiner, B. Nessler, and S. Hochreiter, "Gans trained by a two time-scale update rule converge to a local nash equilibrium," *Advances in neural information processing systems*, vol. 30, 2017.

[25] D. Berman, D. Levy, S. Avidan, and T. Treibitz, "Underwater single image color restoration using haze-lines and a new quantitative dataset," *IEEE transactions on pattern analysis and machine intelligence*, vol. 43, no. 8, pp. 2822–2837, 2020.

[26] Y. Cho, J. Jeong, and A. Kim, "Model-assisted multiband fusion for single image enhancement and applications to robot vision," *IEEE Robotics and Automation Letters*, vol. 3, no. 4, pp. 2822–2829, 2018.

[27] M. Arjovsky, S. Chintala, and L. Bottou, "Wasserstein generative adversarial networks," in *International conference on machine learning*, PMLR, 2017, pp. 214–223.

[28] J. Li, X. Liang, Y. Wei, T. Xu, J. Feng, and S. Yan, "Perceptual generative adversarial networks for small object detection," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2017, pp. 1222–1230.

[29] X. Mao, Q. Li, H. Xie, R. Y. Lau, Z. Wang, and S. Paul Smolley, "Least squares generative adversarial networks," in *Proceedings of the IEEE international conference on computer vision*, 2017, pp. 2794–2802.

[30] P. Isola, J.-Y. Zhu, T. Zhou, and A. A. Efros, "Image-to-image translation with conditional adversarial networks," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2017, pp. 1125–1134.

[31] C. Fabbri, M. J. Islam, and J. Sattar, "Enhancing underwater imagery using generative adversarial networks," in *2018 IEEE international conference on robotics and automation (ICRA)*, IEEE, 2018, pp. 7159–7165.

[32] C. Ancuti, C. O. Ancuti, T. Haber, and P. Bekaert, "Enhancing underwater images and videos by fusion," in *2012 IEEE conference on computer vision and pattern recognition*, IEEE, 2012, pp. 81–88.

[33] C.-Y. Li, J.-C. Guo, R.-M. Cong, Y.-W. Pang, and B. Wang, "Underwater image enhancement by dehazing with minimum information loss and histogram distribution prior," *IEEE Transactions on Image Processing*, vol. 25, no. 12, pp. 5664–5677, 2016.

[34] Y.-T. Peng and P. C. Cosman, "Underwater image restoration based on image blurriness and light absorption," *IEEE transactions on image processing*, vol. 26, no. 4, pp. 1579–1594, 2017.

[35] X. Fu and X. Cao, "Underwater image enhancement with global–local networks and compressed-histogram equalization," *Signal Processing: Image Communication*, vol. 86, p. 115 892, 2020.

[36] C. Li, S. Anwar, J. Hou, R. Cong, C. Guo, and W. Ren, "Underwater image enhancement via medium transmission-guided multi-color space embedding," *IEEE Transactions on Image Processing*, vol. 30, pp. 4985–5000, 2021.

[37] P. Drews, E. Nascimento, F. Moraes, S. Botelho, and M. Campos, "Transmission estimation in underwater single images," in *Proceedings of the IEEE international conference on computer vision workshops*, 2013, pp. 825–830.

[38] X. Fu, P. Zhuang, Y. Huang, Y. Liao, X.-P. Zhang, and X. Ding, "A retinex-based enhancing approach for single underwater image," in *2014 IEEE international conference on image processing (ICIP)*, Ieee, 2014, pp. 4572–4576.

[39] D. Huang, Y. Wang, W. Song, J. Sequeira, and S. Mavromatis, "Shallow-water image enhancement using relative global histogram stretching based on adaptive parameter acquisition," in *MultiMedia Modeling: 24th International Conference, MMM 2018, Bangkok, Thailand, February 5-7, 2018, Proceedings, Part I 24*, Springer, 2018, pp. 453–465.

[40] C. Fabbri, M. J. Islam, and J. Sattar, "Enhancing underwater imagery using generative adversarial networks," in *2018 IEEE international conference on robotics and automation (ICRA)*, IEEE, 2018, pp. 7159–7165.