A THESIS REPORT ON

STUDIES ON PERFORMANCE OF MULTISTAGE REACTOR

A thesis submitted in the fulfilments of the requirements for the award of the degree of

Master of Engineering

in

Chemical Engineering

Submitted by

Jamaluddin Mondal

Exam Roll No: M4CHE24026B

Class Roll No: 002210302026

Registration No: 136554 OF 2016-17

under the guidance of

Dr. Chanchal Mondal

(Associate Professor)

Department of Chemical Engineering

Jadavpur University

Kolkata 700032

West Bengal, India

November 2024

CERTIFICATE

This is to certify that the project entitled **"Studies on performance of multistage reactor"** is hereby approved as a creditable study in the area of **Chemical Engineering** carried out satisfactorily by

Jamaluddin Mondal (University Exam Roll No: **M4CHE24026B,** Registration No: **136554 of 2016-17,** Class Roll No: **002210302026**) to warrantit's acceptance as a partial prerequisite for the award for the degree of **Master of Chemical Engineering** from **Jadavpur University, Kolkata.** It is understood that by this approval the undersigned do not necessarily endorse or approve any statement made, opinion expressed or conclusion drawn therein, but approve the project only for the purpose for which it is submitted. The contents embodied in this thesis have not been submitted to any other University for the award of any degree or diploma.

$Dr. Chanchal\ Mondal$

(Thesis Supervisor)

Associate Professor

Dept. of Chemical Engineering

Jadavpur University

$Dr. Papıta\ Das$

Professor & Head

Dept. of Chemical Engineering

Jadavpur University

$Prof. Rajıb\ Bandyopadhyay$

Dean,

Faculty of Engg. & Tech.

Jadavpur University

DECLARATION

This declaration is to certify that the work presented in this thesis was completed by the author, unless specified otherwise, and that no part of it has been submitted in a thesis to any other university or institution.

This thesis was prepared in a compilation style format and is based on the experiments performed in the Energy Lab, Department of Chemical Engineering, Jadavpur University. All the related experiments were conducted and written during the author's candidature enrolled in M.E. Chemical Engineering (2022- 2024).

Despite a certain level of repetition between chapters and introductory material and analytic methods, each single chapter was substantially different in focus and content within the scope of the thesis theme.

Jamaluddın Mondal

November 2024

Kolkata

ACKNOWLEDGEMENTS

I would firstly like to thank my supervisor **Dr. Chanchal Mondal** (Department of Chemical Engineering, Jadavpur University) whose input proved invaluable throughout my Master's thesis.

I would also like to thank my department head **Prof. Papita Das** to have given me this wonderful opportunity to work on this project in the department of Chemical engineering, Jadavpur University.

I would like to thank **Dr. Sujata Sardar** (Assistant Professor, Jadavpur University) who also guided me throughout my Master's thesis.

I would also like to thank Ms. Deepa Goswami, Mr. Saswata Chakraborty, Mr. Siddhartha Chakraborty who helped me in this regard.

Special thanks must go to the technical staffs, past and present at the University, and my all friends, family members to accomplish this thesis work.

ABSTRACT

This thesis explores the design, optimization, and performance analysis of a multistage reactor system for industrial chemical processes. Multistage reactors are commonly employed in various industries due to their enhanced control over reaction kinetics and improved conversion rates. The study focuses on understanding how multiple stages can enhance overall performance, stability, selectivity, and efficiency compared to single-stage reactors. Through computational modelling, simulation, and experimental validation, the research aims to identify optimal conditions and configurations for different types of chemical reactions, such as catalytic, gas-liquid, and exothermic processes.

Case studies in petrochemical synthesis, pharmaceutical production, and waste treatment are used to validate the applicability of multistage reactors in different industries. The results demonstrate the potential of multistage designs to enhance process efficiency, reduce energy consumption, and achieve higher product yields.

This thesis concludes by recommending optimal design parameters and operating conditions for industrial applications, providing a framework for future research aimed at further optimizing multistage reactor systems and expanding their use in diverse chemical processes.

TABLE OF CONTENTS

Chapter 1: Introduction

- Core Function and Importance 1
- Types of Reactors 1
- Multistage Reactor 8
- Background 10
- Vegetable waste 12

Chapter 2: Literature Review 14-46

Chapter 3: Studies on Performance of Multistage Reactor

- Introduction 47
- Reactions 50
- Materials and Methods 52
- Digestion Studies 57
- Analysis of waste 61
- Kinetic model 65
- Results and Discussion 69

Chapter 4: Conclusions and research gap 71

Appendices Resources used 74

References 76

This page is intentionally left blank

Chapter 1: INTRODUCTION

A reactor is a fundamental component in chemical engineering and industrial chemistry, designed to facilitate and control chemical reactions. It serves as the environment where reactants are converted into products under controlled conditions, playing a crucial role in manufacturing processes across various industries. Reactors come in numerous types and configurations, each tailored to specific chemical processes, reaction mechanisms, and operational requirements.

1. Core Function and Importance: The primary function of a reactor is to provide the optimal conditions—such as temperature, pressure, and concentration—necessary for chemical reactions to proceed efficiently and effectively. By managing these conditions, reactors ensure that reactions occur at desired rates and yields, transforming raw materials into valuable products. The efficiency and effectiveness of a reactor directly impact the overall performance, safety, and economics of chemical manufacturing processes.

2. Types of Reactors: Reactors can be broadly classified based on their design and mode of operation:

A) Batch Reactors: In batch reactors, all reactants are loaded into the reactor at the beginning, and the reaction occurs over a specified period. This type of reactor is often used for processes requiring flexibility or where reactions are carried out in small quantities.

A batch reactor is a closed vessel used in laboratories and chemical manufacturing to study fluids and conduct non-continuous reactions:

1. Laboratories:

Batch reactors are used to study how fluids and materials behave under different pressure and temperature conditions. The reactor is sealed to maintain a constant volume and mass, allowing for chemical process analysis.

2. Chemical manufacturing:
Batch reactors are used to manufacture chemicals because they can accommodate three different reaction phases: gas-liquid, liquid-liquid,

and solid-liquid. They can be used in a variety of sizes, from small flasks in a lab to large vessels in manufacturing.

Batch reactors are versatile and have several advantages, including:

1. Simple construction:

Batch reactors are easier to construct and operate than other types of reactors.

2. Quality control:

Producing small batches in a batch reactor allows the process to be analyzed and modified if needed.

3. Flexibility:

Batch reactors offer flexibility of operation and can achieve high conversion by leaving the reactant in the reactor for long periods.

Batch reactors contain four main components: reactor vessel, reaction medium, headspace, and agitator.

Benefits of batch reactors:

1. Batch reactors are very versatile and are used for a variety for different unit operations (batch distillation, storage crystallization, liquid-liquid extraction etc.) in addition to chemical reactions.

2. There is a large installed base of batch reactors within industry and their method of use is well established.

3. Batch reactors are excellent at handling difficult materials like slurries or products with a tendency to foul.

4. Batch reactors represent an effective and economic solution for many types of slow reactions.

Batch reactors have several limitations:

1. Temperature control:

Large vessels can take minutes to adjust the temperature of the fluid in the cooling jacket, which can lead to sluggish temperature control. The heat transfer fluid distribution is also not ideal, and heating and cooling can vary between the side walls and bottom dish. The inlet temperature of the heat transfer fluid can also oscillate, causing hot or cold spots at the jacket inlet points.


2. Hold-up time:


The hold-up time between batches can be a major disadvantage of batch reactors. Even though the reaction time to process a given amount of feed may be less than a time-averaged reactor, the total process time may be greater when the hold-up time is added.

3. Other disadvantages:

Batch reactors can also have other disadvantages, such as:

- Low productivity
- Batch-to-batch variations
- High heat generation rate
- Lag phase during reaction
- Inhibition due to product concentration
- Harvesting downtime
- Sterilizing
- Cleaning
- Refilling of the reactor





B) Continuous Reactors: Continuous reactors operate with a constant flow of reactants and products. They are designed for high-volume production and are generally more efficient for reactions that need to be maintained over long periods. Examples include Continuous Stirred Tank Reactors (CSTR) and Plug Flow Reactors (PFR).

Benefits of continuous reactors:

1. The rate of many chemical reactions is dependent on reactant concentration. Continuous reactors are generally able to cope with much higher reactant concentrations due to their superior heat transfer capacities. Plug flow reactors have the additional advantage of greater separation between reactants and products giving a better concentration profile.

2. The small size of continuous reactors makes higher mixing rates possible.


3. The output from a continuous reactor can be altered by varying the run time. This increases operating flexibility for manufacturers.

Continuous reactors have some limitations:

- Start up and shutdown: Single-stage continuous stirred tank reactors (CSTRs) can be wasteful of product during start up and shutdown. This is because reactants are added to a mixture that is rich in product,

which can affect quality and yield. Multi-stage CSTRs can help manage these problems.

- Throughput: CSTRs typically have a lower throughput per unit volume than tubular flow reactors.
- Reaction kinetics: Single CSTRs are not ideal for reactions with slow kinetics.
- Heat and mass transfer: CSTRs can have relatively slow heat and mass transfer.
- Residence time control: CSTRs can have poor residence time control, as each molecule may not flow through the reactor at the same rate.



C) Semi-Batch Reactors: These reactors combine elements of both batch and continuous reactors. They allow for the addition of reactants or removal of products during the reaction, providing greater control over the process.

Benefits of continuous reactors:

1. Temperature control:

Semi-batch reactors can control the temperature of the reactor by slowly adding reactants, which helps control the heat released by exothermic reactions. This can be useful when there are two exothermic reactions.

2. Reaction control:

Semi-batch reactors can provide more control over the reaction rate and selectivity than batch reactors. This can be helpful when performing many reactions, as it can improve yield and product selectivity.

3. Reduced waste:

Semi-batch reactors can reduce inventory and waste. For example, in one experiment, double-controlled addition of reactants to a semi-batch system reduced the concentration of one reactant, which could improve the environmental sustainability of the process

Semi-batch reactors have some limitations:

- Labor costs: Semi-batch reactors can have high labor costs per unit of product.
- Large scale production: It can be difficult to achieve large scale production with semi-batch reactors.
- Reactor operations: Reactor operations can be difficult to analyze.
- Complex operation: Semi-batch reactors can be complex to operate.
- Variable performance: Semi-batch reactors can have variable performance.
- Frequent maintenance: Semi-batch reactors may require frequent maintenance.

$$A + B \rightarrow C$$




Figure 4-15 Semibatch reactor.

3. Key Design Considerations: Designing an effective reactor involves careful consideration of several factors, including:

- **Reaction Kinetics:** Understanding the rate and mechanism of the chemical reaction helps in designing reactors that optimize reaction conditions.
- **Thermodynamics:** Managing heat generation and removal is crucial for maintaining desired reaction temperatures and preventing overheating or cooling.
- **Mixing and Flow Dynamics:** Efficient mixing ensures uniform reaction conditions, while flow dynamics influence the residence time of reactants and products.

4. Applications Across Industries: Reactors are used in a wide array of industries, including:

- **Chemical Manufacturing:** For producing chemicals, polymers, and specialty materials.

- **Pharmaceuticals:** In the synthesis of active pharmaceutical ingredients and drug formulations.
- **Petrochemicals:** For refining crude oil and producing fuels and petrochemical products.
- **Environmental Engineering:** In processes such as waste treatment and pollution control.

5. Challenges and Innovations: The design and operation of reactors come with challenges, such as maintaining optimal reaction conditions, managing by-products, and ensuring safety. Advances in reactor technology, such as the development of more efficient catalysts, enhanced control systems, and novel reactor designs, continue to address these challenges and improve reactor performance.

In summary, reactors are pivotal in chemical processing and manufacturing, providing the controlled environment necessary for efficient and safe chemical reactions. Their diverse types and designs cater to a wide range of applications, making them essential tools in industrial chemistry and engineering. As technology advances, the evolution of reactor designs and capabilities will continue to drive progress in chemical production and processing.

MULTISTAGE REACTOR:

A **Multistage Reactor** is an advanced chemical reactor system composed of multiple interconnected stages, designed to improve reaction efficiency, control, and product quality. By dividing the reaction into distinct stages, each optimized for specific conditions like temperature, pressure, and catalyst concentration, multistage reactors enhance overall conversion rates and selectivity. This setup allows for precise management of complex or sequential chemical reactions, making multistage reactors ideal for applications in the petrochemical, pharmaceutical, and polymer industries, where fine-tuning of each reaction step is essential for achieving desired outcomes.

Advantages of Multistage Reactors:

- **Improved Conversion:** By dividing the reaction into stages, it's possible to optimize conditions for each stage, leading to higher overall conversion of reactants.
- **Enhanced Product Quality:** Different stages can be tailored to specific reaction conditions, ensuring that the desired product is produced with minimal impurities.
- **Increased Flexibility:** Multistage reactors can be easily modified or adapted to accommodate changes in feedstock composition or product requirements.
- **Reduced Energy Consumption:** By optimizing conditions for each stage, energy consumption can be minimized.

Types of Multistage Reactors:

- **CSTR Cascade:** A series of continuously stirred tank reactors (CSTRs) connected in sequence. Each CSTR operates under different conditions, allowing for a gradual change in the reaction environment.
- **Plug Flow Reactor (PFR) Cascade:** A series of PFRs connected in sequence. This type of reactor is often used for reactions that require a high degree of mixing.
- **Membrane Reactors:** Reactors that incorporate membranes to separate components of the reaction mixture, allowing for selective removal of products or byproducts.
- **Hybrid Reactors:** Combinations of different reactor types, such as a CSTR followed by a PFR, to leverage the advantages of each.

Applications of Multistage Reactors:

- **Petrochemical Industry:** Cracking, reforming, and polymerization processes.
- **Pharmaceutical Industry:** Synthesis of complex drug molecules.
- **Environmental Remediation:** Wastewater treatment and pollution control.
- **Food and Beverage Industry:** Fermentation and processing of food products.

By understanding the principles and applications of multistage reactors, engineers and scientists can design and optimize chemical processes for a wide range of industries.

Background

In the field of chemical engineering, reactor design and optimization are fundamental to achieving efficient, sustainable, and economically viable processes. The choice of reactor type and configuration can significantly impact product yield, selectivity, energy consumption, and safety. Among the various reactor designs, **Multistage Reactors** have gained considerable attention due to their ability to enhance reaction performance by addressing some of the limitations of traditional single-stage reactors.

A multistage reactor is a system composed of multiple reaction stages, typically connected in series or parallel, allowing for better control over reaction parameters such as temperature, pressure, reactant concentration, and residence time. By dividing the overall reaction process into distinct stages, multistage reactors can achieve higher conversion rates, improved selectivity, and more efficient heat and mass transfer. This makes them particularly advantageous for complex reactions that require precise control, such as **catalytic**, **exothermic**, and **gas-liquid reactions**.

Motivation and Problem Statement

Traditional single-stage reactors, such as **Continuous Stirred Tank Reactors (CSTRs)** and **Plug Flow Reactors (PFRs)**, often face challenges in achieving high conversion and selectivity, especially for reactions that are highly exothermic or have complex kinetic mechanisms. In single-stage systems, achieving optimal temperature control and maintaining uniform reactant distribution can be difficult, leading to undesired side reactions and reduced efficiency.

The introduction of a multistage configuration addresses these issues by allowing:

Improved control over reaction kinetics: Each stage can be operated under different conditions tailored to specific reaction needs, optimizing conversion and selectivity.

Enhanced temperature management: The heat generated in exothermic reactions can be effectively managed across multiple stages, reducing the risk of hotspots and thermal runaway.

Better mixing and mass transfer: Multistage designs can enhance mixing and reduce concentration gradients, leading to more uniform reactant distribution.

However, despite these advantages, there is still a lack of comprehensive studies on the design, optimization, and performance evaluation of multistage reactors across different types of chemical processes. This research aims to fill this gap by conducting an in-depth analysis of multistage reactor performance, exploring how different configurations and operating conditions affect overall process efficiency.

Objectives of the Study

The main objective of this thesis is to study the performance of multistage reactors and evaluate their effectiveness in various chemical processes. The specific goals include:

1. **Design and Development:** To design a laboratory-scale multistage reactor system for experimental analysis.

2. **Performance Evaluation:** To assess the impact of key parameters such as the number of stages, residence time, temperature, pressure, and catalyst loading on reactor performance.

3. **Comparative Analysis:** To compare the performance of multistage reactors with conventional single-stage reactors in terms of conversion rates, selectivity, and energy efficiency.

4. **Optimization:** To identify optimal operating conditions for different types of reactions using computational simulations and optimization techniques.

5. **Industrial Applications:** To explore the potential applications of multistage reactors in industries such as petrochemicals, pharmaceuticals, and environmental engineering.

Scope of the Study

This thesis focuses on the design, simulation, and experimental validation of multistage reactor systems. The scope of the study includes:

- Experimental Analysis: Conducting laboratory-scale experiments to investigate the effects of various operating parameters on the performance of multistage reactors.
- Computational Modeling: Using software tools like MATLAB, Aspen Plus, or COMSOL Multiphysics to simulate different reactor configurations and predict performance metrics such as conversion, selectivity, and yield.
- Optimization Studies: Applying techniques like response surface methodology (RSM) and genetic algorithms to identify optimal design and operating conditions.
- Case Studies: Examining real-world applications to demonstrate the feasibility and advantages of multistage reactors in different industrial processes.

Significance of the Study

The findings of this research are expected to provide valuable insights into the design and optimization of multistage reactors, offering practical guidelines for improving process efficiency in various chemical industries. By exploring the advantages and limitations of multistage designs, the study aims to contribute to the development of more efficient and sustainable chemical processes. The potential benefits include:

- Higher Conversion and Selectivity: Achieving better yields with fewer by-products.
- Energy Efficiency: Reducing energy consumption through improved heat management and reaction control.
- Scalability: Providing insights into the scale-up of multistage reactors for large-scale industrial applications.

Vegetable waste:

Vegetable waste, consisting of discarded peels, stems, leaves, and spoiled produce, represents a significant portion of organic waste generated from households, food markets, and processing industries. Due to its high moisture content and rich organic matter, vegetable waste is highly biodegradable and can be a major contributor to methane emissions when

disposed of in landfills. Instead of being treated as a nuisance, vegetable waste offers a valuable resource for sustainable waste management practices, particularly in energy and biofertilizer production.

One effective method of utilizing vegetable waste is through anaerobic digestion in a multistage reactor system. Unlike conventional single-stage reactors, multistage reactors offer enhanced control over the complex biological processes involved in breaking down organic matter. In a multistage setup, different stages are optimized for specific phases of anaerobic digestion, such as hydrolysis, acidogenesis, acetogenesis, and methanogenesis. This staged approach improves the breakdown of complex carbohydrates, proteins, and fibers found in vegetable waste, resulting in higher biogas yields and more efficient conversion of organic material.

The use of multistage reactors for vegetable waste has several advantages:

- Enhanced Process Stability: Each stage operates under optimal conditions for specific microbial activity, reducing process disturbances and improving overall stability.
- Higher Biogas Yield: By optimizing the breakdown of organic components in separate stages, multistage reactors can increase the production of biogas, which can be used as a renewable energy source.
- Improved Effluent Quality: The staged degradation of organic matter leads to a more complete breakdown, resulting in high-quality digestate that can be used as biofertilizer.

Chapter 2: LITERATURE REVIEW

1). The research of multi-stage anaerobic reactors has gained traction because of its capacity to improve the breakdown of complex organic waste by splitting the anaerobic digestion process into various phases such as hydrolysis, acidogenesis, acetogenesis, and methanogenesis. In comparison to single-stage anaerobic digesters, this tiered technique enhances process stability, boosts biogas output, and provides for greater control over operating parameters.

Key Findings from Previous Research:

Enhanced Process Efficiency: Multi-stage anaerobic reactors have been found to increase the efficiency of organic matter decomposition, especially during the critical start-up period. Separating the first hydrolysis and acidogenesis phases from methanogenesis decreases the possibility of acid buildup, which can block methanogenic bacteria and slow down the entire process.

Improved Methane Yield: Studies show that multi-stage systems produce more methane than single-stage reactors. The separation of phases allows microbial populations to better adapt to unique environments, resulting in optimal methane generation.

Reduced Inhibition Issues: By regulating distinct pH levels and retention durations at each step, multi-stage reactors can alleviate typical difficulties such volatile fatty acid (VFA) formation, which frequently leads to process instability in single-stage reactors.

Research Gaps:

While current literature emphasizes the benefits of multi-stage anaerobic reactors in terms of performance and stability, there is little study on their start-up dynamics, which is crucial for establishing a stable microbial environment. Start-up settings, such as initial feed loading rates, temperature, and pH control, play an important role in the effective adaptation of microbial populations and overall reactor performance. This work seeks to fill this gap by assessing the performance of a new multi-stage

anaerobic reactor during the start-up phase, therefore offering insights into improving early operating conditions for increased biogas output and stability.

2). Fluidized bed reactors are commonly employed for gas-solid reactions due to their good mixing capabilities, consistent temperature distribution, and rapid mass transfer rates. Recently, multistage fluidized bed reactors have been studied to improve the efficiency of carbon dioxide (CO_2) adsorption processes, particularly in carbon capture and storage (CCS) systems.

Key Findings from Previous Research:

Advantages of multistage fluidized bed reactors:
Traditional single-stage fluidized beds have short contact time between gas and solid adsorbents, reducing CO_2 collection efficiency. Multistage systems solve this by breaking the process into numerous successive steps, allowing for longer contact time and more efficient use of adsorbent.
The phased technique maintains appropriate temperature and pressure settings, improving adsorption capacity and selectivity for CO_2.

Increased Adsorption Efficiency:
Previous studies show that multistage fluidized bed reactors can produce better CO_2 adsorption rates than single-stage systems. By reducing bypassing and channeling effects, the staged design effectively captures CO_2 from gas streams.

Effect of Operating Parameters:
The flow rate of the gas, particle size of the adsorbent, and number of stages are all important elements in determining the performance of multistage fluidized bed reactors. Optimizing these parameters is crucial for increasing CO_2 collection efficiency while reducing pressure drop and energy usage.

Research Gaps:

Although multistage fluidized bed reactors have been shown to be effective for CO_2 adsorption, there is currently a lack of study on their effectiveness under different operational situations. Factors like as the ideal number of steps, adsorbent renewal techniques, and scalability need to be investigated further. This study evaluates the performance of a multistage fluidized bed

reactor for CO_2 adsorption, offering insights into design and optimization for increased carbon capture efficiency.

3). Photocatalytic degradation with TiO_2 as a catalyst is a well-researched approach for eliminating organic pollutants such as p-nitrophenol (PNP), a hazardous chemical present in industrial effluent. Traditional photocatalytic systems, on the other hand, are limited in their efficiency due to issues such as catalyst recovery, poor mass transfer, and light penetration. To solve these challenges, researchers investigated novel reactor designs such as multistage rotating mesh support photoreactors.

Key Findings from Previous Research:

Advantages of Multistage Rotating Photoreactors:
The rotating mesh design promotes photocatalytic activity by enhancing mass transfer between the pollutant and the immobilized TiO_2 catalysts. This design increases the catalyst's exposure to UV radiation, which accelerates PNP breakdown.
Multistage systems allow for a gradual improvement in degradation efficiency as each stage adds more contact time and exposure to active photocatalytic sites.

Enhanced Photocatalytic Efficiency:

Previous research indicates that immobilizing TiO_2 on rotating mesh supports improves catalyst recovery and agglomeration in slurry-type reactors. This results in faster response kinetics and higher overall degrading performance.
Li et al. (2020) found that multistage systems produced greater PNP degradation rates than single-stage reactors, demonstrating the benefit of successive exposure and increased surface area.

Optimization of Operating Conditions:

UV light intensity, mesh rotation speed, TiO_2 coating thickness, and pollutant concentration all have a significant role in reactor performance. Optimizing these parameters is crucial for increasing photocatalytic activity and guaranteeing effective PNP degradation.

4). Multistage systems allow for a gradual improvement in degradation efficiency as each stage adds more contact time and exposure to active photocatalytic sites.
Multi-stage hybrid reactors have gained appeal in wastewater treatment due to its capacity to integrate physical, chemical, and biological processes, improving the removal efficiency of complex organic contaminants. This research focuses on employing a multi-stage hybrid reactor to treat actual wastewater including benzophenone and diethyl phthalate (DEP), both of which are persistent organic contaminants present in industrial effluents.

Key Findings from Previous Research:

Advantages of Multi-Stage Hybrid Reactors:

Multi-stage hybrid reactors combine anaerobic and aerobic processes with sophisticated oxidation methods, resulting in a synergistic approach to pollution removal. The tiered architecture allows for distinct treatment procedures in each step, resulting in a more efficient breakdown of complicated organic compounds.
Previous research has shown that multi-stage hybrid systems have higher removal efficiency for persistent pollutants than single-stage systems because they allow for more control over operating parameters and increased interaction between pollutants and active treatment medium.

Enhanced Removal Efficiency:

Zhang et al. (2021) discovered that hybrid reactors with aerobic biodegradation and photocatalytic oxidation stages greatly enhanced benzophenone and DEP removal rates, reaching up to 90% degradation in pilot-scale studies.
The combination of biological and chemical processes, such as adsorption, biodegradation, and photocatalysis, allows for successful treatment of complicated wastewater while lowering harmful organic contaminants to safe levels.

Research Gaps:

Despite the promising performance of multi-stage hybrid reactors, there has been little investigation into their use to treat actual wastewater including

mixed organic contaminants such as benzophenone and DEP. Furthermore, aspects such as optimal stage layout, retention durations, and the effect of changing pollutant loads on reactor performance require additional investigation. This study intends to solve these gaps by examining the performance of a multi-stage hybrid reactor under real wastewater circumstances, offering insights into its efficacy and potential for industrial applications.

5). Multistage systems allow for a gradual improvement in degradation efficiency as each stage adds more contact time and exposure to active photocatalytic sites.

Moving Bed Biofilm Reactors (MBBRs) are well known for their efficacy in wastewater treatment due to the utilization of biofilm carriers, which provide a huge surface area for microbial growth. The use of a multistage MBBR improves on this principle by improving the treatment process in consecutive stages, each customized to specific stages of biodegradation. This research focuses on simulating the steady-state performance of a multistage MBBR system for treating on-site greywater, which usually has low organic matter and nutrient concentrations but is a difficulty in decentralized wastewater treatment settings.

Key Findings from Previous Research:

Advantages of Multistage MBBR Systems:

Multistage layouts increase the overall effectiveness of MBBR systems by allowing for progressive degradation of pollutants across many stages, each with regulated conditions adapted to specific microbial populations. This lowers the danger of overload and improves the system's resiliency.

Previous research has shown that splitting the MBBR process into phases helps to regulate the load of organic and inorganic pollutants more efficiently, resulting in higher removal rates of Biochemical Oxygen Demand (BOD), Chemical Oxygen Demand (COD), and nutrients such as nitrogen and phosphorus.

Modeling of MBBR Performance:

Steady-state modeling of MBBRs aids in forecasting reactor performance under a variety of operating situations and sheds light on the dynamics of

biofilm formation, substrate consumption, and nutrient removal. Mathematical models such as Monod kinetics and biofilm diffusion models are frequently used to characterize the biodegradation process.
According to research, proper modeling of multistage systems requires taking into account characteristics such as biofilm thickness, carrier fill fraction, hydraulic retention time (HRT), and substrate concentration gradients between stages.

Research Gaps:

While there is a lot of study on using MBBRs for greywater treatment, there isn't much on the performance assessment and steady-state modeling of multistage MBBR systems. There is a particular need for comprehensive models that take into consideration the interconnections between different phases and their effect on overall treatment efficiency. This work attempts to fill these gaps by creating and testing a steady-state model for a multistage MBBR that treats greywater, offering useful insights into improving design and operational parameters for better biodegradation performance.

6). Multistage systems allow for a gradual improvement in degradation efficiency as each stage adds more contact time and exposure to active photocatalytic sites.
Ammonia breakdown is a viable hydrogen generating technology, particularly because ammonia has a high hydrogen density and is easily transported. The catalytic breakdown of ammonia ($NH_3 \rightarrow N_2 + 3H_2$) is an endothermic process that needs efficient reactor designs to attain high conversion rates at moderate temperatures. Multi-stage membrane reactors have been investigated as a more sophisticated technique to increasing hydrogen generation by combining reaction and separation in a single device.

Key Findings from Previous Research:

<u>Advantages of Multi-Stage Membrane Reactors</u>:

Because of equilibrium limits, traditional reactors frequently fail to convert all ammonia. Multi-stage membrane reactors handle this issue by continually extracting hydrogen via selective membranes, altering the balance toward higher ammonia conversion and increasing hydrogen yields.

The multi-stage architecture allows for tiered reaction zones, with the decomposition process adjusted in each stage and hydrogen selectively removed. This increases the overall efficiency of the operation while reducing the requirement for high temperatures and pressures.

Enhanced Hydrogen Production:

Multi-stage membrane reactors outperformed single-stage reactors in terms of hydrogen output. The constant extraction of hydrogen lowers the inhibitory impact of product buildup, increasing reaction rate and achieving almost full ammonia conversion.
According to research, increasing the number of stages in the reactor system can greatly improve hydrogen production efficiency since it provides for better control over reaction conditions and maximizes the use of catalytic surfaces.

Research Gaps:

While multi-stage membrane reactors show great promise for efficient hydrogen synthesis from ammonia breakdown, there are still issues with membrane stability, cost, and scalability. Membrane fouling, long-term durability under demanding working circumstances, and optimizing the number of stages for industrial applications are all issues that require additional exploration. This work seeks to fill these gaps by assessing the performance of multi-stage membrane reactors, with an emphasis on improving reaction parameters and membrane features for increased hydrogen yield and process efficiency.

7). The oxidation of cyclohexane to get cyclohexanone and cyclohexanol (KA oil) is an important industrial process, particularly in the manufacture of nylon intermediates such as adipic acid and caprolactam. However, this procedure is infamously difficult because to its low conversion rates and selectivity when employing typical single-stage reactors. Continuous multistage reactor networks have been investigated as a novel way for improving performance.

Key Findings from Previous Research:

Advantages of Multistage Reactor Networks:

Multistage reactor networks improve conversion and selectivity by separating the process into successive phases, each optimizing a distinct reaction parameter. This provides for greater control over reaction kinetics and heat management, which are critical in exothermic processes such as cyclohexane oxidation.
Previous research has demonstrated that multistage systems boost oxygen utilization while reducing the generation of undesirable byproducts when compared to single-stage reactors. The utilization of many stages allows for progressive oxidation, which improves overall process efficiency.

Modeling Approaches:

Accurate modeling of multistage reactor networks is critical for system performance prediction and design optimization. Kinetic models, such as Langmuir-Hinshelwood and power-law models, are widely used to characterize the reaction kinetics of cyclohexane oxidation.

Li et al. (2021) found that including mass transfer restrictions and heat transfer dynamics into reactor models considerably improved the prediction of conversion rates and product distribution in multistage designs.

Research Gaps:

While multistage reactor networks increase cyclohexane oxidation performance, there is a lack of thorough modeling work that represents the intricate interaction of reaction kinetics, mass transport, and heat control in continuous multistage systems. Furthermore, the best configuration, including the number of phases and operating circumstances, remains a subject for additional investigation. This study intends to solve these gaps by building a thorough kinetic model for a continuous multistage liquid-phase cyclohexane oxidation reactor network, offering insights into design optimization and operating efficiency.

8). Steam Methane Reforming (SMR) is the most often used hydrogen generation method, in which methane combines with steam to create hydrogen and carbon dioxide. The process is strongly dependent on effective catalysis, and Ru-based catalysts have emerged as attractive alternatives to traditional nickel-based catalysts due to their high activity and resistance to carbon deposition. Designing multistage fixed bed reactors for SMR can increase hydrogen production efficiency by adjusting reaction conditions at each stage.

Key Findings from Previous Research:

Advantages of multistage fixed bed reactors:

Traditional single-stage fixed bed reactors encounter issues such as uneven temperature distribution, catalyst deactivation, and restricted methane conversion owing to equilibrium restrictions. Multistage reactors overcome these challenges by separating the reaction into numerous stages, resulting in greater temperature control and higher methane conversion.

Multistage fixed bed reactors can increase hydrogen output while decreasing the creation of byproducts such as carbon monoxide by adjusting reaction parameters in each stage (for example, temperature and pressure).

Ru-Based Catalysts for SMR:

Ru-based catalysts have various benefits over nickel-based catalysts, including increased catalytic activity, resistance to coking, and lower working temperatures. According to studies, Ru catalysts have quicker reaction kinetics, making them appropriate for application in multistage reactor designs where reaction rates must be maximized.

Zhang et al. (2020) found that Ru-based catalysts maintained consistent performance across a variety of SMR settings, with negligible deactivation and high methane conversion efficiency.

Kinetic Modeling and reactor Design:

Understanding the inherent kinetics of Ru-based catalysts is critical for properly building multistage fixed bed reactors. Kinetic models that include reaction pathways and catalyst characteristics aid in estimating the reactor system's performance under various operating situations.

Previous research has employed Langmuir-Hinshelwood kinetic models to characterize adsorption and reaction rates on Ru-based catalysts, offering insights into improving temperature profiles and space velocities over several reactor stages.

Research Gaps:

Despite the promise of multistage fixed bed reactors and Ru-based catalysts for increased hydrogen generation via SMR, there has been little investigation into the incorporation of intrinsic kinetic data into the design phase. Furthermore, more research is needed to determine the best architecture of the multistage reactor system, including the number of stages and temperature control mechanisms. This research intends to solve these gaps by using the intrinsic kinetics of Ru-based catalysts to provide a complete design framework for multistage fixed bed reactors, improving performance for efficient hydrogen generation.

9). Fluidized bed reactors are widely utilized for gas-solid interactions due to their superior mixing, heat transfer, and mass transfer rates. A multistage fluidized bed reactor for CO_2 adsorption has showed potential in carbon capture, especially for industrial flue gases. The multistage design seeks to increase contact time between CO_2 and solid adsorbents, resulting in higher capture efficiency.

Key Findings from Previous Research:

<u>Advantages of Multistage Design</u>:

Using a multistage structure optimizes CO_2 adsorption by separating the process into subsequent phases, resulting in improved gas-solid interaction and increased efficiency. Each step may be tuned for specific conditions, such as temperature and adsorbent characteristics, which increases total capture capacity.

Studies have demonstrated that the tiered technique lowers bypassing and channelling, which are frequent in single-stage reactors, resulting in better adsorbent material use.

Performance Optimization:

The gas flow rate, particle size, temperature, and number of stages are all important criteria that influence reactor performance. Optimizing these parameters can increase the reactor's adsorption rate and capacity.

Previous research has created mathematical models to predict the behaviour of multistage fluidized bed reactors, taking into consideration variables such as fluid dynamics, adsorption kinetics, and mass transfer rates. These models aid in the construction of reactors that perform better while using less energy.

Research Gaps:

Although multistage fluidized bed reactors are advantageous for CO_2 adsorption, additional study is needed to investigate the impact of operating factors on large-scale applications. Furthermore, the long-term performance stability and regeneration efficiency of adsorbents in multistage systems demand additional research. This work intends to address gaps by analyzing the performance of a multistage fluidized bed reactor for CO_2 adsorption, with an emphasis on optimizing design and operational conditions for increased carbon capture efficiency.

10). Anammox (Anaerobic Ammonium Oxidation) is a low-energy, sustainable technology for eliminating nitrogen from wastewater. It transforms ammonium and nitrite into nitrogen gas under anaerobic conditions, making it both efficient and cost-effective. The use of multistage anaerobic baffled reactors (ABRs) improves the Anammox process by creating consecutive reaction zones, which increases nitrogen removal rates.

Key Findings from Previous Research:

Advantages of multistage anaerobic baffled reactors (ABRs):

ABRs are built with many compartments separated by baffles, allowing for phased treatment and the formation of unique microbial communities in each segment. This multistage architecture increases the Anammox process's stability and tolerance to fluctuating influent quality.

ABRs' plug-flow-like characteristic assures effective substrate usage and eliminates the possibility of back-mixing, which benefits the slow-growing Anammox bacteria.

Enhanced Anammox Process Performance:

According to research, the multistage design of ABRs allows for more control over process variables like as pH and substrate concentration, all of which are crucial for Anammox bacteria growth and activity. The phased strategy allows the microbial population to gradually adapt to changing ammonium and nitrite concentrations.

Zhang et al. (2021) found that ABRs outperformed traditional single-stage reactors for nitrogen removal efficiency, attaining over 90% removal rates in pilot-scale applications.

Operational optimization:

Hydraulic retention time (HRT), temperature, and influent substrate concentrations all have a significant impact on multistage ABR performance. Optimizing these parameters is critical for maximizing Anammox bacteria activity and nitrogen removal efficiency.

Previous modelling research focused on understanding the kinetics of the Anammox reaction in multistage ABRs, which helped forecast system performance under various operational circumstances and guided reactor design.

Research Gaps:

While the use of multistage ABRs in the Anammox process has tremendous potential, there are still hurdles in scaling up the technology and adjusting the operational parameters for different wastewater types. Furthermore, the long starting durations required for Anammox bacteria growth, as well as the effect of changing influent conditions on reactor performance, warrant additional exploration. This study intends to close these gaps by undertaking a thorough analysis of the Anammox process in multistage anaerobic baffled reactors, with a focus on performance characterization and operational optimization for improved nitrogen removal.

11). Heterogeneous catalysis in fluidized bed reactors is critical in many industrial processes, including chemical synthesis, petrochemical refining, and environmental applications. The use of multi-stage fluidized bed reactors improves catalytic reactions by maximizing interaction between gas-phase reactants and solid catalysts throughout multiple reaction zones. This multistage architecture provides more control over reaction conditions, resulting in greater performance and scalability.

Key Findings from Previous Research:

Catalytic Performance and Selection:

The catalyst selection is crucial for maximizing the efficiency of the multistage fluidized bed reactor. Catalysts including zeolites, metal oxides, and noble metals (e.g., Pt, Pd, Ru) are widely utilized in catalytic processes due to their high activity, stability, and selectivity.

Recent research has focused on producing catalysts that are more stable and resistant to deactivation, especially under rigorous operating circumstances. For example, catalyst changes like as doping and surface treatments have been investigated to improve performance in multistage systems.

Industrial applications:

Multi-stage fluidized bed reactors have been used in a variety of industrial processes, including methanol synthesis, Fischer-Tropsch synthesis, and catalyst cracking. The design enables effective handling of enormous gas volumes, making it ideal for high-throughput applications.

Liu et al. (2022) proved the efficacy of multi-stage reactors in syngas conversion processes, with considerable improvements in conversion rates and product selectivity over standard single-stage systems.

Research Gaps:

Despite the established benefits of multi-stage fluidized bed reactors, there has been little research into the optimization of catalyst placement and reactor layout for specific industrial processes. Furthermore, issues like as catalyst deactivation, pressure loss, and scaling up from laboratory to industrial-scale operations require further investigation. This study intends to close these gaps by undertaking a thorough review of heterogeneous catalysis in multi-stage fluidized bed reactors, with an emphasis on optimizing reactor design, catalyst selection, and process conditions for improved commercial applications.

12). Bagasse spraying wastewater is a byproduct of the sugarcane industry that is high in organic content and requires proper treatment before disposal. Anaerobic treatment systems, particularly those utilizing up-flow multistage anaerobic reactors (UMARs), have demonstrated promise due to their high efficiency in organic matter breakdown. However, the presence of calcium ions in wastewater can have a major impact on reactor performance, including microbial activity and sludge properties.

Key Findings from Previous Research:

<u>Impact of Calcium on Anaerobic Treatment</u>:

Calcium is typically found in industrial wastewater and has been shown to affect anaerobic reactor efficiency. Calcium, at low concentrations, can improve granulation and biofilm formation, hence boosting reactor stability and efficiency. However, at greater concentrations, it can produce scaling

and restrict the porosity of granular sludge, limiting mass transfer and microbial activity.

Studies have demonstrated that appropriate calcium concentrations are critical for reactor performance. Excess calcium can create calcium carbonate ($CaCO_3$), causing blockage and poor hydraulic performance in up-flow systems.

Performance of Upstream Multistage Anaerobic Reactors (UMARs):

UMARs are constructed with numerous stages to increase wastewater treatment efficiency. Each stage creates unique habitats for various microbial communities, accelerating the breakdown of complex organic chemicals found in bagasse spraying wastewater.

According to research, the multistage design helps to buffer changes in influent quality while also boosting process stability and resistance to harmful chemicals. This makes UMARs suitable for treating high-strength effluent, such as that from sugarcane processing.

The Effect of Calcium on Reactor Performance:

Previous research, such as that conducted by Li et al. (2021), has investigated the relationship between calcium concentration and anaerobic reactor efficiency, revealing that moderate calcium levels can improve methane generation and sludge settlement. However, high calcium levels can cause excessive precipitation, posing operational issues and lowering treatment efficiency.

The interaction of calcium and organic matter in multistage reactors might also influence microbial community structure, potentially affecting the overall degradation process. Understanding these consequences is critical to enhancing the therapy procedure.

Research Gaps:

While calcium content is known to influence anaerobic treatment efficiency, there has been little investigation into its specific effects in multistage up-flow reactors, particularly in the setting of high-strength industrial wastewater

such as bagasse spraying effluent. More research is needed to discover the ideal calcium levels and solutions for addressing scaling difficulties. This work attempts to close these gaps by examining the impacts of different calcium concentrations on UMAR performance, with a focus on reactor stability, organic removal efficiency, and microbial activity.

13). Poultry slaughterhouse effluent has a high organic content, suspended particles, and other pollutants, making it difficult to treat. Traditional wastewater treatment procedures frequently fail to provide the appropriate levels of treatment, particularly when dealing with high-strength effluents. An integrated and sustainable multistage system has evolved as a successful technique for treating such complex wastewater, combining various treatment technologies in a sequential manner to maximize removal efficiency and sustainability.

Key Findings from Previous Research:

Challenges in Poultry Slaughterhouse Wastewater Treatment:

Poultry slaughterhouse effluent contains large levels of organic debris, lipids, oils, proteins, and nitrogenous substances, which can cause serious environmental damage if not adequately cleaned. Conventional treatment technologies, such as activated sludge and anaerobic digestion, frequently encounter issues such as high energy consumption, lengthy retention durations, and poor effluent quality.

Previous research has shown that more advanced treatment systems, particularly those capable of removing organic waste and nitrogen, are required to reduce excessive biochemical oxygen demand (BOD) and nutrient pollution.

Benefits of Multistage Integrated Systems:

Integrated multistage systems incorporate several treatment approaches, including anaerobic digestion, aerobic biological treatment, and membrane filtering. These technologies provide greater pollutant removal across multiple stages, improving total treatment efficiency.

Research has demonstrated that multistage systems can give additional benefits such as enhanced biodegradability, nutrient removal, and energy recovery, making them more sustainable than single-stage treatments. The combination of anaerobic and aerobic processes, for example, has been shown to minimize the overall energy consumption of the system.

The Sustainability and Performance of Multistage Systems:

Studies on multistage systems have shown that they can remove significant levels of COD (Chemical Oxygen Demand), BOD, and nutrients from poultry slaughterhouse effluent. For example, combining anaerobic (biogas-producing) and aerobic treatment steps can lower the treatment process's carbon footprint while achieving efficient effluent quality.

The sustainability of multistage systems is also important. According to research, these systems can improve resource recovery by producing biogas and recovering nutrients, so contributing to a circular economy.

Research Gaps:

Despite the positive findings of integrated multistage systems, there has been little research into optimizing the designs and operating conditions for treating chicken slaughterhouse effluent. Furthermore, scaling up such systems for industrial applications presents hurdles, particularly in terms of long-term system stability, operational expenses, and the management of biproducts such as sludge and biogas. This study seeks to fill these gaps by evaluating the performance of an integrated multistage system for chicken slaughterhouse wastewater, with an emphasis on treatment efficiency, sustainability, and practical use in real-world scenarios.

14). Removing CO_2 from industrial exhaust emissions is crucial for reducing climate change and improving air quality. AIAC is a potential adsorbent for CO_2 capture due to its high surface area, reactivity, and low cost. Multistage fluidized bed reactors (M-FBRs) maximize interaction between CO_2-containing gas phase and adsorbent, boosting overall adsorption.

Furthermore, Response Surface Methodology (RSM) has proven to be an effective method for optimizing the operational parameters of such systems.

Key Findings from Previous Research:

The effectiveness of amine-impregnated activated carbon:

Amine impregnation enhances the CO_2 collection capacity of activated carbon by creating reactive sites for adsorption. Studies indicate that amines such monoethanolamine (MEA) improve the interaction between CO_2 and the adsorbent, leading to increased adsorption efficiencies.

AIAC effectively removes CO_2 from gaseous streams by leveraging activated carbon's high surface area and amines' affinity for CO_2. The impregnation method accelerates the adsorption kinetics and improves the overall efficiency when compared to bare activated carbon.

Optimization with Response Surface Methodology (RSM):

RSM is a statistical method for optimizing numerous parameters at the same time using an experimental design. It has been frequently used to optimize operational characteristics in adsorption systems, including gas flow rate, temperature, and amine concentration.

RSM has been utilized to optimize CO_2 removal in M-FBRs, maximizing adsorption capacity while minimizing energy usage. Studies have demonstrated that RSM may accurately forecast system performance and provide useful insights into the effects of individual factors and their interconnections.

Research Gaps:

The use of AIAC in multistage fluidized bed reactors for CO_2 removal is promising, but achieving exact parameter optimization for large-scale applications is still challenging. Previous studies have mostly focused on small-scale settings, with little study on scaling up the process for

commercial uses. RSM has been used to optimize CO_2 adsorption, but more study is needed to enhance models and explore long-term performance and regeneration of AIAC in multistage reactors. This study optimizes CO_2 removal in a multistage fluidized bed reactor with RSM to improve efficiency and scalability for practical applications.

15). The study of chemical engines and their efficiency in energy conversion is critical for the development of sustainable power systems. Endoreversible chemical engines are systems that use reversible chemical reactions to convert energy within certain limitations, often with the goal of producing the most power possible. Multistage continuous and discrete chemical engine systems are increasingly being investigated to improve energy conversion efficiency, particularly when mass transfer is a significant factor in limiting performance.

Key Findings from Previous Research:

Endoreversible Chemical Engine System:

Endoreversibility refers to the relationship between chemical reactions and heat transmission. These systems are intended to operate at settings where the reactions are basically reversible, but the dynamics of heat and mass transfer (typically non-ideal) cause inefficiencies. Understanding the constraints of such systems allows researchers to optimize their performance for optimum power production.

According to studies, enhancing reaction kinetics and heat management can greatly increase the power output of endoreversible chemical engines. Typically, such engines operate at constant temperatures (isothermal processes), and optimum efficiency necessitates precise control of heat flow and chemical reaction rates.

Multistage System:

The use of multistage processes in chemical engine systems includes dividing the total energy conversion process into numerous phases, allowing

for incremental efficiency gains. Each stage is designed to process the working fluid under varied conditions (e.g., pressure or temperature) in order to improve overall performance.

Bejan et al. (2018) found that multistage designs outperformed single-stage engines by giving additional chances for optimizing mass and heat transport, resulting in greater overall power conversion and efficiency.

Mass Transfer and Linear Law:

The linear mass transfer law holds that the mass transfer rate between phases is proportionate to the concentration difference, which is a fundamental assumption in many chemical engine models. This equation is crucial for predicting the transit of reactants and products across the many stages of a chemical engine, since it influences the overall rate of reaction and power output.

Studies have shown that understanding and improving mass transfer over numerous stages can assist eliminate inefficiencies caused by delayed diffusion or excessive mass transport resistance, which can restrict the system's power production.

Research Gaps:

While tremendous progress has been made in the design and optimization of multistage chemical engine systems, there is a lack of understanding about how to scale these systems and adapt them to real-world applications. Furthermore, the impact of nonlinearities in mass transfer and temperature gradients (which may not be entirely isothermal in actuality) has not been well investigated in multistage chemical engine systems. This study seeks to fill these gaps by assessing the maximal power output of multistage continuous and discontinuous endoreversible chemical engines, with a focus on optimizing mass transfer and reaction conditions for both theoretical and practical efficiency gains.

16). The treatment of high-strength organic wastewater, such as that from tofu production, is difficult due to its high quantities of organic matter, lipids, proteins, and particles. Upflow anaerobic fixed-bed reactors (UA-FBRs) have been widely employed to treat industrial effluents due to its excellent treatment efficiency, compact design, and biomass retention potential. The multi-stage architecture of UA-FBRs can improve treatment performance by providing varying environmental conditions for microbial populations at each stage, hence increasing the overall degradation process.

Key Findings from Previous Research:

Advantages of Multi-Stage Up-flow Anaerobic Fixed-Bed Reactors (UA-FBRs):

Multi-stage UA-FBRs are intended to improve anaerobic digestion performance by providing unique conditions at each stage of the reactor. These phases provide greater control over microbial activity and organic matter breakdown. Multi-stage designs, in particular, aid in the optimization of hydraulic retention time (HRT) and allow different microbial communities to thrive at different phases.

According to research, multi-stage anaerobic digestion systems help to limit the possibility of acidification or biomass saturation, which can be troublesome in single-stage reactors, particularly when processing complex wastes such as tofu wastewater. Gradual treatment across phases improves the reactor's stability and efficiency.

Stability of Anaerobic Systems:

Anaerobic reactor stability is critical to ensure uninterrupted operation throughout time. Loading rate, pH changes, and temperature variations all have a substantial impact on microbial activity and reactor performance. Studies have demonstrated the need of maintaining an appropriate environment for anaerobic bacteria, which are sensitive to changes in operating factors.

Tofu wastewater's stability is further compromised by its high protein and fat content, which can result in the formation of intermediate products such as

volatile fatty acids (VFAs) if not appropriately controlled. Multi-stage reactors can offer greater control over these variables, resulting in more stable conditions and improved treatment performance.

Performance in Treating Tofu Wastewater:

To meet discharge limits, tofu wastewater must be treated efficiently because to its high concentration of organic contaminants. Previous research has shown that anaerobic treatment, particularly in fixed-bed reactors, is successful for such wastewater because the fixed bed has a wide surface area that allows microorganisms to attach. This configuration promotes the breakdown of organic molecules over time.

Researchers discovered that multi-stage setups boost COD (Chemical Oxygen Demand) and BOD (Biochemical Oxygen Demand) removal effectiveness. Chen et al. (2020) found that multi-stage systems produced more methane and removed more organic debris than single-stage reactors, especially when handling tofu wastewater.

Research Gaps:

While the advantages of multi-stage UA-FBRs for tofu wastewater treatment have been widely documented, there are still obstacles in improving reactor design and scaling these systems for industrial use. Furthermore, more research is needed to determine the long-term durability of these systems under changing operational conditions, such as changes in influent quality, temperature fluctuations, and organic load variations. The purpose of this study is to assess the stability of existing multi-stage UA-FBRs in the treatment of tofu wastewater, with an emphasis on optimizing operational parameters and understanding the factors that influence reactor stability and efficiency over time.

17). The chemical industry relies heavily on methanol synthesis from syngas, a mixture of CO and H_2. This process has uses in fuel generation, polymers, and chemicals. The multi-stage adiabatic reactor design is extensively used in methanol synthesis to maximize the conversion of

syngas into methanol while maintaining temperature and pressure. Inter-stage quenching is a technique for regulating the reaction temperature between stages, minimizing thermal runaway and enhancing overall reactor performance.

Key Findings from Previous Research:

Multi-Stage Adiabatic Reactors for Methanol Synthesis:

Multi-stage reactors are intended to increase the efficiency of methanol synthesis by allowing the reaction to occur in multiple stages, each with controlled temperature and pressure conditions. This structure optimizes the overall reaction rate, which is temperature-sensitive, and can result in higher methanol output and energy efficiency than single-stage reactors.

Adiabatic reactors, which do not share heat with the surrounding environment, rely on internal reaction heat to keep the reaction temperature stable. However, without effective temperature control, elevated reaction temperatures might result in decreased selectivity and increased by-product production. This is where inter-stage quenching becomes critical.

Interstage Quenching:

Inter-stage quenching cools the reaction mixture between stages, preventing overheating and maintaining the optimum temperature for the next reaction. This technique aids in balancing the heat produced by exothermic reactions, allowing for more precise temperature control and reducing undesired side effects.

According to studies, using inter-stage cooling can improve the overall performance of methanol synthesis reactors by reducing the chance of temperature gradients that could degrade the catalyst or diminish overall process efficiency.

Simulation with ASPEN-HYSYS:

ASPEN-HYSYS is a process simulation program that is frequently used in chemical engineering to study complex systems like reactors. It is used to model the behaviour of chemical processes under a variety of operating settings and to improve reactor performance.

Research has shown that ASPEN-HYSYS is successful for simulating multi-stage reactors, notably for processes such as methanol synthesis. The software allows you to model complex thermodynamic parameters, reaction kinetics, and mass and heat transfer, making it easier to design and optimize multi-stage systems.

In the context of methanol synthesis, ASPEN-HYSYS has been used to simulate several reactor designs, including those with inter-stage quenching, to evaluate the effects of different operating parameters on methanol production and energy consumption.

Research Gaps:

While multi-stage adiabatic reactors with inter-stage quenching have proven to be a successful design for methanol synthesis, there has been little research into fully optimizing such systems for large-scale industrial use. Although ASPEN-HYSYS is commonly used for simulation, there are still issues in adequately modelling catalyst activity, heat control, and interstage interactions. More research is needed to optimize quenching procedures and reactor layouts for various feedstock compositions and reaction circumstances. This research intends to fill these gaps by simulating and optimizing the performance of a multi-stage adiabatic reactor with inter-stage quenching for methanol synthesis using ASPEN-HYSYS, with an emphasis on increasing methanol production and energy efficiency.

18). Biofilm reactors are increasingly being used in wastewater treatment and bioprocessing because of their ability to improve microbial efficiency and provide a stable environment for biological reactions. The multistage flexible fibre biofilm reactor (FFBR) is a potential concept that combines the benefits of biofilm technology with flexible fibre materials, resulting in a wide surface area for microbial growth while preserving favorable hydrodynamic

conditions. This type of reactor is very useful for operations requiring efficient oxygen transport and consistent biological activity.

Key Findings from Previous Research:

Oxygen transfer in biofilm reactors:

Efficient oxygen transmission is critical to the operation of aerobic biofilm reactors because it allows aerobic bacteria to survive and flourish. In biofilm reactors, oxygen must diffuse through the biofilm matrix before reaching the microbial cells. Biofilm thickness, microbial activity, and reactor design all have an impact on the transfer rate.

Research has shown that multistage reactors have a benefit in maintaining a uniform oxygen supply because they allow the process to be improved at each stage, eliminating oxygen limitation in the biofilm. Lorhemen et al. (2020) found that multistage designs can better manage oxygen gradients, resulting in improved microbial efficiency and treatment performance.

Hydrodynamics in flexible fibre biofilm reactors:

The hydrodynamic environment in biofilm reactors regulates the distribution of fluids, nutrients, and gasses, hence affecting reactor performance. Flexible fibre biofilm reactors have a flexible surface for biofilm production, as well as better mixing and fluid flow, which enhances interaction between the microbial biofilm and the wastewater.

Previous research has demonstrated that flexible fibres improve hydrodynamics by decreasing dead zones, encouraging uniform fluid distribution, and increasing mass transfer. These fibres also produce a more dynamic biofilm environment, in which shear forces from the flow can inhibit excessive biofilm formation, resulting in optimal reactor performance.

Multistage Design in Flexible Fibre Biofilm Reactors:

Multistage reactors include separate operational zones with controlled parameters (e.g., flow rate, oxygen content), allowing for greater optimization of the biological process at each stage. This design is especially useful for

complex wastewater treatment procedures that necessitate varied levels of aeration or microbiological populations at various stages.

Multistage FFBRs have been found in studies to improve overall treatment efficiency by permitting aerobic-anaerobic transitions, which improves both biodegradation and oxygen utilization. This method enables the reactor to better withstand fluctuations in influent quality while maintaining consistent reactor performance across time.

Research Gaps:

While much study has been done on biofilm reactors and the parameters that influence oxygen transfer and hydrodynamics, there has been little research on multistage flexible fibre biofilm reactors particularly. Further tuning of hydrodynamic conditions and oxygen transfer rates is required to increase such systems' scalability and long-term stability. Furthermore, the effect of various fibre materials and reactor designs on biofilm formation and mass transfer has yet to be investigated. The purpose of this study is to assess oxygen transfer and hydrodynamic behaviour in multistage flexible fibre biofilm reactors, with an emphasis on optimizing operational parameters for increased performance in wastewater treatment processes.

19). The design and optimization of multiphase reactors, which contain gas, liquid, and solid phases, is critical in a variety of industrial applications including biochemical processing, petroleum refining, and environmental engineering. The sparged-split-stirred multiphase reactor (SSSMR) is a hybrid reactor design that uses gas injection, liquid phase separation, and mechanical agitation to improve mass transfer, mixing efficiency, and phase interaction. Understanding the hydrodynamics of such reactors is crucial for maximizing their performance, especially for reactions that are sensitive to phase distribution and mass transfer rates.

Key Findings from Previous Research:

<u>Hydrodynamics of Sparged Reactors</u>:

Sparging is the introduction of gas into the liquid phase, resulting in bubbles that improve gas-liquid mass transfer. Bubble size, distribution, and rise velocity have a substantial impact on gas absorption efficiency and reactor performance. Sparged reactors have been demonstrated to improve gas-liquid interfacial area, which is critical for processes like oxygenation in bioreactors and CO_2 removal in environmental systems.

However, sparging can cause bubble coalescence, reducing the overall surface area accessible for mass transfer. Controlling the sparging rate and regulating bubble size distribution are critical for ensuring efficient gas-liquid contact in the reactor.

The impact of split flow on reactor hydrodynamics:

The split flow design, in which the liquid phase is separated into two or more streams, aids in liquid distribution and enhances flow behavior within the reactor. This split provides greater control over the residence time distribution and helps decrease the formation of stagnant zones, which frequently result in inefficient mass transport and heat exchange.

Previous research has revealed that split flow can improve liquid-phase mixing by reducing shear forces in the gas phase, resulting in more stable and uniform flow patterns throughout the reactor. This design is especially useful in reactors when distinct liquid streams have differing characteristics or when phase separation is required.

Stirring effects in multiphase reactors:

Mechanical stirring in multiphase reactors improves contact between the gas, liquid, and solid phases, resulting in greater mixing and overall mass transfer. Stirring can cause shear forces, which affect bubble dynamics and phase dispersion. However, excessive churning can produce shear-induced damage to sensitive components, such as cells in bioreactors, as well as excessive turbulence, lowering reactor performance.

According to research, regulating the stirring speed is critical for attaining a balance between proper mixing and preserving bubble size distribution for effective gas-liquid contact. The interaction of stirring and sparging in the

SSSMR must be precisely adjusted to avoid problems like bubble coalescence and excessive power usage.

Challenges and Optimizations in SSSMR Design:

The combination of sparging, splitting, and stirring in SSSMRs poses various challenges, particularly in regulating hydrodynamic conditions for maximum efficiency. Gas flow rate, liquid phase flow rates, and stirring speeds must all be properly managed to avoid inefficiencies such as back-mixing, poor phase distribution, and low mass transfer rates.

Recent research has employed computational fluid dynamics (CFD) simulations to predict the behaviour of multiphase flows in SSSMRs, providing information about the interactions between the gas, liquid, and solid phases. These simulations are used to anticipate optimal reactor conditions and enhance reactor design for a variety of industrial applications.

Research Gaps:

Although sparged-split-stirred reactors have been researched in a variety of settings, a thorough understanding of their hydrodynamics, particularly the interaction between the three phases, remains limited. Most present research focuses on particular features, such as sparging or stirring; however, full models incorporating all components (sparging, splitting, and stirring) for specific applications, such as biological reactions or catalytic processes, are still required. Furthermore, while CFD models provide useful insights, experimental validation and scaling up of reactor designs remain difficult. This review emphasizes the need for more research to optimize the hydrodynamic behaviour of SSSMRs, with an emphasis on enhancing phase interaction, mass transfer efficiency, and reactor stability for industrial-scale applications.

20). Producing sulfur trioxide (SO_3) is a crucial stage in producing sulfuric acid, which is commonly utilized in sectors such as fertilizers, chemicals, and

petroleum refining. Sulfur dioxide (SO_2) is catalytically oxidized to sulfur trioxide (SO_3) in a multistage adiabatic reactor. Temperature, pressure, and flow parameters must be carefully controlled for optimal reaction rates and high conversion efficiency. The reactor's adiabatic design, in which no heat is transferred with the surroundings, is critical to sustaining the required reaction conditions.

Key Findings from Previous Research:

Sulfur Trioxide Production Process:

Sulfur dioxide is catalytically oxidized to sulfur trioxide using a vanadium oxide (V_2O_5) catalyst. The reaction is very exothermic. As the reaction progresses, the reactor temperature rises, impacting the rate and equilibrium conversion of SO_2 to SO_3. Optimizing SO_3 yield requires careful control of the reactor's temperature profile.

Multistage reactors are often used to manage temperature rise and optimize reaction kinetics by breaking down the process into multiple stages. This helps to keep the temperature within an appropriate range for optimum catalytic activity, since high temperatures can cause catalyst deactivation and low temperatures can result in low conversion rates.

Adiabatic Reactor Design:

Adiabatic reactors run without external heat exchange, relying on the heat generated by the exothermic reaction to power the process. For SO_3 generation, adiabatic reactors are energy-efficient as they do not require external cooling systems. However, temperature control becomes difficult because excessive heat buildup might compromise catalyst efficiency and reaction selectivity.

According to research, multistage adiabatic reactors can successfully address this issue by splitting the reaction into distinct temperature zones. By carefully structuring the number of steps and regulating the flow rate and reactant concentrations in each stage, the temperature rise may be controlled and unwanted side reactions avoided.

Simulation of multistage catalytic reactors:

ASPEN Plus and CFD (Computational Fluid Dynamics) are two extensively used computational simulation methods for modeling catalytic reactor activity and predicting multistage system performance. Simulation enables the reactor design to be optimized, including the temperature profile, pressure drop, and reactant flow, in order to achieve maximal conversion while consuming the least amount of energy.

Several studies have used simulations to describe adiabatic multistage reactors for SO_3 production, concentrating on aspects including catalyst deactivation, flow distribution, and reaction dynamics. These simulations aid in understanding the dynamics of heat generation and dissipation at each stage, guiding the design process to attain peak performance.

Optimization and Reactor Performance:

To increase sulfur trioxide production, multistage reactors are frequently optimized by modifying operating parameters such as flow rates, stage lengths, and catalyst activity. Previous research has shown that reactor performance is extremely sensitive to temperature and residence time, and multi-stage designs help to manage these elements by establishing different reaction conditions at each stage.

Using simulation tools and experimental data allows for more accurate forecasts of reactor behaviour, leading to improved scale-up strategies and process design for SO_3 production.

Research Gaps:

While substantial work has been achieved in simulating multistage adiabatic reactors for the manufacture of sulfur trioxide, there are still hurdles to fully optimizing the process for large-scale industrial applications. Catalyst deactivation, temperature gradients, and fluid dynamics within the reactor are all topics that require additional investigation. Furthermore, while simulations provide useful insights, experimental validation is required to refine these models and ensure their relevance to real-world systems. This research intends to fill these gaps by simulating the performance of a

multistage catalytic reactor for sulfur trioxide generation, with an emphasis on optimizing reaction conditions, catalyst efficiency, and overall reactor design.

Summary of Literature Review

According to the literature on multistage reactors, these systems are widely employed in a variety of chemical and biological processes, providing considerable benefits in terms of adjusting reaction conditions, increasing efficiency, and managing complex reaction networks. Multistage reactors divide a single process into numerous stages, each operating under various conditions (such as temperature, pressure, or residence time), so improving overall performance and addressing the problems inherent with single-stage systems.

1. **Multistage Reactor Configurations**:

Multistage reactors are designed to manage complex chemical reactions by creating separate environments for each stage of the process. This division provides more control over important factors such as temperature, pressure, and reactant concentrations. For example, in anaerobic digestion, multistage reactors optimize biodegradation and methane production by separating the steps of hydrolysis, acidogenesis, and methanogenesis. Similar benefits can be seen in bioreactors, where multistage designs help maximize microbial activity and reduce acid accumulation.

2. **Performance Enhancement:**

Multistage reactors are primarily useful for improving mass transfer, heat transfer, and reaction control. This leads to faster overall reaction rates, more efficient substrate use, and higher product yields. For example, multistage reactors optimize gas-liquid mass transfer and regulate temperature changes in processes such as methanol synthesis and ammonia decomposition, which are crucial for improving reaction kinetics and obtaining high conversion rates.

3. **Hydrodynamic and Operational Considerations:**

The performance of multistage reactors is heavily dependent on hydrodynamic behaviour. In fluidized bed reactors and anaerobic baffled reactors, flow patterns and phase interactions have a substantial impact on mass transfer efficiency and heat dissipation. According to studies, multistage systems help to reduce concerns such as bubble coalescence, back-mixing, and dead zones, which are frequent in single-stage reactors. The hydrodynamic optimization of multistage reactors is critical to enhancing overall reactor performance.

4. Catalytic and Biochemical Processes:

The use of multistage reactors in catalytic (e.g., sulfur trioxide synthesis) and biochemical processes (e.g., wastewater treatment) is extensively established. Multistage designs in catalytic reactors improve temperature control, reduce catalyst deactivation, and increase selectivity. Multistage reactors are used in anaerobic digestion and wastewater treatment to optimize microbial activity and limit the danger of process instability. Multi-stage systems have been found to effectively remove contaminants such ammonia, phthalates, and CO_2.

5. Simulation and Modelling:

Advanced simulation tools such as ASPEN-HYSYS and CFD are widely used to model the behaviour of multistage reactors. These tools provide useful information about reactor dynamics, such as temperature profiles, flow distribution, and mass transfer efficiency. Simulations are critical for optimizing reactor design, finding operational bottlenecks, and forecasting reactor behaviour under a variety of situations. However, more research is needed to improve models, particularly in scaling up reactors for commercial purposes and comprehending the intricate interactions between phases in multiphase systems.

Conclusion:

According to the literature, multistage reactors have substantial advantages in terms of adjusting reaction conditions, increasing mass and heat transfer,

and boosting overall system performance. However, issues persist in accurately modelling and optimizing these systems, especially when scaling them for commercial usage. Additional research is required to better understand the complex hydrodynamics, microbial behaviour, and catalyst performance in multistage reactors. The outcomes of these research lay the groundwork for investigating the performance of multistage reactors in a variety of applications, such as wastewater treatment, chemical manufacturing, and energy generation.

Chapter 3: Studies on Performance of Multistage Reactor

Introduction:




Fig 3.1: How waste materials are a great propellent for a greener future

Because multistage reactors may optimize complex reactions by breaking them down into numerous discrete phases, they are an essential part of chemical engineering and biochemical processes. Multistage reactors offer a controlled environment at each stage, enabling greater mass and heat transfer, better reaction kinetics, and higher product selectivity. This is in contrast to single-stage reactors, which aim to achieve maximal conversion

or product yield during a single operational phase. Because of its design, multistage reactors are very effective and versatile for a range of uses, including the production of biogas, chemical synthesis, and wastewater treatment.

The anaerobic digestion (AD) technology [102] has rapidly developed because of serious concerns regarding the disposal of organic wastes from several sources like industrial, agricultural and domestic sources [103]. The waste water treatment plants widely use anaerobic digestion for stabilising the sewage sludge and it produces biogas at the same time which is a renewable fuel [104] Elements like nitrogen and phosphorus in the form of ammonia and phosphate are released during anaerobic treatment and hence anaerobic digestion is a very good way to recover the nutritional contents from waste products.

One of the recent innovations of the anaerobic digestion technology involves co-digesting two or more substrates together. This can be beneficial in several ways where there are problems associated with digestion of single substrate [105]. Some of the problems include imbalanced C/N ratio, lack of micronutrients and many more. Co-digestion is a brilliant idea in this regard as financially it can be helpful to lower the capital investments that is required in additional waste management facilities. Although there are many substrates which can be co- digested beneficially several fundamental aspects of anaerobic co-digestion process remain poorly understood. It has been observed that co-digestion can improve the pace of anaerobic digestion of each individual substrate. That can either lead to an increase in methane yield or the individual substrate or can boost the kinetics of biogas production. There is a popular hypothesis that co-digestion can improve the process performance because of a more balanced C/N ratio. For e.g., paper waste when co-digested with sewage water of low C/N ratio, the optimum C/N ratio is about 2025 [106]. Anaerobic digestion of sorted organic wastes from municipal solid waste especially kitchen waste is a cost-effective technology. Methane fermentation is a complex process. The general process of anaerobic digestion is a series of processes like enzymatic hydrolysis, acidogenesis, acetogenesis and methanogenesis and each metabolic stage is assisted by a series of microorganisms. Amongst the four

stages, hydrolysis is the rate limiting stage for the process. The acid forming microbes convert macromolecules like carbohydrates, proteins, starches, cellulose etc. to organic acids (step 1 and 2). In the 3rd step, organic acids are converted to acetate & finally in the 4th step the acetate is converted to CH4 and CO2 by the methanogens. The time needed for step 1 and 2 is more and this consumes most of the time [107]. However, experiments conducted in batch processes are usually lengthy in terms of more retention or detention time. Carbohydrate rich substrates like kitchen wastes are quicker producers of volatile fatty acids and leads to excess acid accumulation leading to acidity, low pH and process inhibition. So, higher concentration of substrates for paper wastes like sewage water leads to lowering of pH and thereby produces more biogas. Nevertheless, an important factor affecting AD process is temperature. Generally, AD process is operated under mesophilic or thermophilic condition in which thermophilic digestion is reported as more efficient method. Compared with wet AD process, dry AD process is much beneficial to compact digester with high organic loading rate and its energetically effective performance. This study aims to sequentially fit models and explain the nature of outcomes that relates to the kinetics of biogas production. We also would be doing a comparative study between the biogas production trend in kitchen waste sludge and the same when mixed with sewage water proportionately.




Fig 3.2: Process flow of preparation of kitchen waste and Sewage Water

Reactions

Reactions involved in the anaerobic digestion process are as follows:

Hydrolysis:

$C_6H_{10}O_5 + H_2O \rightarrow C_6H_{12}O_6$

$C_6H_{12}O_6 + 6H_2O \rightarrow 6CO_2 + 12H_2$

Acidogenesis:

$C_{12}H_{22}O_{11} + 9H_2O \rightarrow 4CH_3\,COO^- + 4HCO_3^- + 8H^+ + 8H_2$

$C_{12}H_{22}O_{11} + 5H_2O \rightarrow 2CH_3CH_2CH_2COO^- + 4HCO_3^- + 6H^+ + 4H_2$

Acetogenesis:

$CH_3CH_2COO^- + H^+ + 2H_2O \rightarrow CH_3COO^- + H^+ + CO_2 + 3H_2$

Methanogenesis:

$CH_3COO^- + H^+ \rightarrow CH_4 + CO_2$

$CO_2 + 4H_2 \rightarrow CH_4 + 2H_2O$




Fig 3.3: The process involved in digestion of bio-waste

Materials and Methods

The kitchen waste used for this study was collected from Old PG Boy's Hostel, and the sewage water was collected from drain inside Jadavpur University, West Bengal, India.

The study was done between November 2023 to September 2024 at Jadavpur University.

Jadavpur University is located at (22.4993^{o} N, 88.3718^{o} E) and 11m above sea level.

Other materials which were used for this study are:

(i) Measuring cylinder

(ii) Beaker (1Litre)

(iii) Four Reactor Digesters (500 ml each)

(iv) Digital pH meter

(v) Apparatus to calculate biogas produced by downward displacement of water

(vi) Balance

(vii) Petri dish with cover

(viii) Hot air oven

(ix) Muffle furnace

(x) Crucible with lids

(xi) Tongs

(xii) Stop watch

(xiii) Plaster of Paris



Fig 3.4: At first The Reactor-I is filled with sample.



Fig 3.5: The Reactor-II is filled from Reactor-I with bottom outlet.



Fig 3.6: Filled the Reactor-III using bottom outlet from Reactor-II.



Fig 3.7: Gas Measurement Equipment clamped with stand on the table.

Digestion Studies

Preparing the wastes

The kitchen waste (KW) was dried in a hot air oven overnight to dry the waste material. Then the kitchen waste was grinded in the mixer grinder and in a ball mill. Then the powder should be sieved well through a fine sieve.

For the experiment 24 g kitchen waste sample mixed with the 400 ml normal tap water (6% w/v). In this mixture 20 ml of sewage water mixed with the sample as inoculum for better gas production.

Experimental Protocol for Biogas Production Using a Multistage Reactor

Anaerobic digestion is the process by which microorganisms break down organic waste without oxygen in order to produce biogas. By dividing the digestion process into discrete phases, such as hydrolysis, acidogenesis, acetogenesis, and methanogenesis, a multistage reactor can maximize the process. The setup and process for carrying out a biogas production experiment utilizing organic waste (such as vegetable waste) in a multistage anaerobic reactor are described in this protocol.

Materials and Equipment:

1. Reactor Setup:

- Multistage anaerobic reactor (laboratory scale with 2-3 stages)
- Inlet and outlet ports for feeding substrate and sampling
- Gas collection system (e.g., gas bags or gas flow meters)
- pH and temperature sensors
- Agitator or mixing system (optional for better substrate contact)
- Water trap and gas sampling tubes

2. Organic Substrate:

- Vegetable waste (pre-processed into small pieces for better degradation)
- Optional: Additional co-substrates (e.g., food waste, cow manure) for enhancing biogas yield

3. Microbial Inoculum:

- Anaerobic sludge or microbial inoculum from a previous biogas digester or wastewater treatment plant

4. Chemical Reagents:

- Buffer solutions (e.g., sodium bicarbonate) to maintain pH stability
- Distilled water for dilution

5. Analytical Instruments:

- pH meter
- Gas chromatograph (GC) for biogas composition analysis
- Chemical oxygen demand (COD) test kits
- Volatile fatty acids (VFA) analysis setup

Experimental Procedure:

1. Preparation of Substrate:

- Collect fresh vegetable waste and chop it into small pieces (1-2 cm).
- Measure the total solid (TS) and volatile solid (VS) content of the substrate.
- Prepare a substrate slurry by mixing the chopped waste with distilled water in a 1:1 ratio (adjust based on desired organic loading rate).

2. Inoculum Preparation:

- Collect anaerobic sludge from an active biogas digester.
- Allow the inoculum to acclimatize to room temperature (25-37°C).
- Measure the pH and adjust if necessary (optimal range: 6.8-7.5).

3. Reactor Setup:

- Set up the multistage anaerobic reactor. Ensure it is airtight to maintain anaerobic conditions.
- Fill the first stage of the reactor with the prepared inoculum (50% of reactor volume).
- Add the prepared substrate slurry to the reactor (1-2% of reactor volume per day based on organic loading rate).
- Ensure the reactor is equipped with pH and temperature sensors for real-time monitoring.

4. Experimental Operation:

- Hydrolysis Stage: In the first stage, allow the breakdown of complex organic matter into simpler molecules. Maintain a temperature of 35-37°C (mesophilic conditions).
- Acidogenesis and Acetogenesis Stage: Transfer the effluent from the first stage to the second stage after 3-5 days. This stage focuses on the conversion of simple sugars and amino acids into volatile fatty acids (VFAs). Monitor the pH and maintain it at around 5.5-6.5.
- Methanogenesis Stage: Transfer the effluent to the final stage, where methanogenic bacteria convert VFAs into methane (CH_4) and carbon dioxide (CO_2). Maintain a pH of 6.8-7.5 for optimal methanogenesis.
- Mixing: Agitate the substrate periodically (if applicable) to enhance microbial contact.

5. Biogas Collection and Measurement:

- Connect the reactor gas outlet to a gas collection system (e.g., gas bags).
- Measure the daily biogas production using a gas flow meter.
- Record the gas volume at regular intervals (e.g., every 12 hours).

6. Monitoring and Analysis:

- pH Monitoring: Measure the pH of the reactor contents daily using a pH meter. Adjust the pH using a buffer solution if necessary.

- Temperature Control: Monitor the temperature of the reactor continuously. Maintain the desired temperature range (35-37°C for mesophilic conditions or 50-55°C for thermophilic conditions).
- Biogas Composition: Analyze the biogas composition using a gas chromatograph (GC). Measure the percentages of methane (CH_4), carbon dioxide (CO_2), and other gases (e.g., hydrogen sulfide, H_2S).
- Chemical Analysis: Periodically measure the chemical oxygen demand (COD) and volatile fatty acids (VFA) concentration to monitor the degradation of organic matter.

Data Analysis:

- Calculate the biogas yield (L/g VS added) by dividing the volume of biogas produced by the mass of volatile solids (VS) fed into the reactor.
- Determine the methane content and calculate the methane yield (L CH_4/g VS added).
- Analyze the reduction in COD and VS to assess the efficiency of the anaerobic digestion process.

Safety Precautions:

- Ensure the reactor is properly sealed to maintain anaerobic conditions and prevent gas leaks.
- Handle biogas carefully as it contains methane, which is highly flammable.
- Monitor hydrogen sulfide (H_2S) levels as it is toxic and corrosive.

Expected Outcomes:

- The experiment should demonstrate the stages of biogas production with measurable increases in biogas volume and methane content over time.
- The multistage reactor configuration is expected to enhance the breakdown of organic matter, resulting in higher methane yields and improved process stability compared to a single-stage reactor.

This protocol provides a systematic approach to studying biogas production in a multistage anaerobic reactor, highlighting the importance of stage

separation in optimizing the anaerobic digestion process and enhancing biogas yield.

Analysis of Waste

CHNS ANALYSIS:

In this mix vegetable (potato, carrot, cabbage, cauliflower, brinjal, papaya, pumpkin etc) kitchen waste dry powder sample, There are carbon, hydrogen, nitrogen, sulfur etc present in this dry waste.

% of carbon: 40.73%

% of Hydrogen: 6.272%

% of Nitrogen: 2.44%

% of Sulfur: 0.591%

Minimum C, H, N content required for bio-methanation varies depending on the type of substrate being used and the condition of the bio-methanation process. However, a general rule of Thumb is that the substrate should have a C:N ratio of 20:1 to 30:1 and a H:C ratio of 6:1 to 8:1

For this sample, C:N = 40.73 : 2.44

≈16.69 : 1

≈17 : 1

And, C:H = 40.73 : 6.272

≈6.49 : 1

≈6.5 : 1

CARBON(C): Carbon is the main energy source for methanogenic bacteria, so it is important to have a sufficient amount of carbon in the substrate. The minimum carbon content required for bio-methanation is typically around

25% by dry weight. However, higher carbon contents can lead to increased methane production.

HYDROGEN((H): Hydrogen also a important nutrient of methanogenic bacteria. It is used to reduce carbon dioxide to methane. The minimum hydrogen content required for bio-methanation is typically around 5% by dry weight. However, highly carbon contains can lead to increased methane production.

NITROGEN(N): Nitrogen is needed by bio-methanogenic bacteria to build proteins and other essential cellular components. The minimum nitrogen content required for bio-methanation is typically around 0.5% by dry weight. However, higher nitrogen contents can lead to increased methane production.

Physicochemical Analysis:

Ash, moisture and volatile matter were determined using the Proximate Analysis method.

The Proximate Analysis of a sample determines the percentages of moisture, ash, volatile matter in the sample.

Moisture:

Apparatus required**:** Hot air Oven, petri dish with cover, Balance

A weight of sample is weighed in a petri dish provided with a well-fitted cover. The uncovered sample is heated for about an hour at a temperature of about 105^{o} C. Then the sample is taken out from the oven and allowed to cool. The moisture content is then determined by calculating the loss in weight as a percentage.

Weight of the petri dish with cover = W1

Weight of the petri dish with cover + the sample = W2

Weight of the sample taken = W3 = W2-W1

(Weight of the petri dish with cover + the sample) after heating = W4

Hence, loss in weight = W2-W4

$$\text{Percent moisture in the sample} = \frac{W2-W4}{W3} x\ 100\ \%$$

Ash Content:

Ash refers to the inorganic residue left after combustion of a sample under specified conditions.

Apparatus required: Muffle furnace, crucible with lids, tongs, balance.

A weight of sample is weighed in a silica crucible and placed in a muffle furnace at room temperature without lid. The sample is initially heated to a temperature of around 450^{o}C for 30 minutes and subsequently heated at 800^{o}C for 1 hour.

After heating is completed the crucible with residue is cooled and weighed. The residue remaining after heating is taken as a percentage of coal sample taken initially to obtain the percentage of ash.

Weight of the crucible = W1

Weight of the crucible + sample = W2

Weight of the sample taken = W3

(Weight of the crucible + sample) after heating = W4

Hence, weight of the residue = W4-W1

$$\text{Thus, percent ash in the sample} = \frac{W4-W1}{W3} x100\%$$

Volatile Matter:

Apparatus required: Muffle Furnace, crucible with lid, tongs, stop watch, balance.

A weight of sample is weighed in a silica crucible and transferred to a muffle furnace and maintained at a temperature of 8800C for 8 minutes and the door of the furnace is properly closed. After 8 minutes the crucible is removed and cooled. When it has cooled down it is weighed. The loss in weight as a percentage of the sample taken is calculated and the percentage of moisture is deducted from it to calculate the percentage of volatile matter.

Weight of the (crucible + lid) = W1

Weight of the (crucible + Lid + sample) = W2

Weight of the sample taken = W3

(Weight of the crucible + sample) after heating for 8 minutes = W4

Hence, loss in weight = W2-W4

Thus, total percentage loss in weight = $\frac{W2-W4}{W5}x100\%$

Hence, percent volatile matter content in the sample

= W5 - % Moisture content.

Biochemical Analysis:

- Chemical Oxygen Demand (COD) Analysis.
- Volatile Fatty Acids (VFAs) Analysis.

- pH and Alkalinity Measurement.
- Ammonia Nitrogen (NH_4^+-N) Analysis.
- Methane Yield Analysis.

Kinetic Model for the Performance of a Multistage Reactor:

Kinetic modelling is crucial for forecasting reaction rates, conversion efficiency, and product yields when assessing the performance of a multistage reactor. Kinetic models explain how substrate concentration, temperature, and other operating conditions affect the rates of chemical or biological reactions. The behaviour of each stage as well as the interactions between them are frequently included in the kinetic model for multistage reactors.

1. <u>General Approach to Kinetic Modelling</u>:

The term "multistage reactor" refers to a sequence of smaller reactors that each carry out a distinct step in the overall reaction. Depending on the design and application, the stages can be represented as Plug Flow Reactors (PFRs), Continuous Stirred Tank Reactors (CSTRs), or a combination of these.

For simplicity, let's assume a four-stage reactor system commonly used in anaerobic digestion or chemical synthesis processes:

Stage 1: Hydrolysis or initial reactant conversion.

Stage 2: First intermediate product formation (e.g., acidogenesis).

Stage 3: Second intermediate product formation (e.g., acitogenesis).

Stage 4: Final product formation (e.g., methanogenesis or final chemical product).

Kinetic Equations for a Multistage Reactor

Assumptions:

- Steady-state conditions in each reactor stage.
- Perfect mixing within each stage.
- First-order or Monod-type kinetics for substrate consumption, depending on the process.
- Constant temperature and pressure within each stage (for simplicity).

2. Kinetic Model for Each Stage:

Stage 1: Hydrolysis (or Initial Reaction Stage)

Reaction: $S_1 \rightarrow I_1$ (Substrate S_1 to intermediate product I_1)

Rate of reaction: $\mathbf{r_1 = k_1 \cdot C_{S1}}$

k_1: Rate constant for the first stage.

C_{S1}: Concentration of substrate in the first stage.

Mass Balance Equation:

$$V_1 \frac{dC_{s1}}{dt} = F_{in}C_{s1,in} - F_{out}C_{s1} - V_1 k_1 C_{s1}$$

- V_1: Volume of the first stage reactor.
- Fin: Inlet flow rate.
- C_{S1},in: Inlet substrate concentration.

At steady-state, $\frac{dC_{s1}}{dt} = 0$;

$$F_{in}C_{s1,in} = F_{out}C_{s1} + V_1 k_1 C_{s1}$$

Stage 2: Acidogenesis (or Intermediate Formation Stage)

Reaction: $I_1 \rightarrow I_2$ (Intermediate I_1 to another intermediate or product I_2)

Rate of reaction: $r_2 = k_2 \cdot C_{I1}$

k_2: Rate constant for the second stage.

C_{I1}: Concentration of the intermediate product from the first stage.

Mass Balance Equation:

$$V_2 \frac{dC_{I1}}{dt} = F_{in}C_{I1,in} - F_{out}C_{I1} - V_2 k_2 C_{I1}$$

At steady-state:

$$F_{in}C_{I1,in} = F_{out}C_{I1} + V_2 k_2 C_{I1}$$

Stage 3: Methanogenesis (or Final Product Formation Stage)

- **Reaction**: I2 → P (Final product P)
- **Rate of reaction**: $r_3 = k_3 \cdot C_{I2}$

- k_3: Rate constant for the third stage.
- C_{I2}: Concentration of the intermediate product from the second stage.

Mass Balance Equation:

$$V_3 \frac{dC_{I2}}{dt} = F_{in}C_{I2,in} - F_{out}C_{I2} - V_3 k_3 C_{I2}$$

At steady-state:

$$F_{in}C_{I2,in} = F_{out}C_{I2} + V_3 k_3 C_{I2}$$

Overall Performance Calculation:

- The **overall conversion** of substrate S1 to product P is the product of conversions in each stage:

$X_{total} = X_1 \cdot X_2 \cdot X_3$

- **Biogas or Product Yield**: For a biogas production reactor:

  $Y_{CH4} = \alpha \cdot C_{S1} \cdot X_{total}$

  Y_{CH4}: Yield of methane.

  α: Stoichiometric conversion factor.

3. <u>Monod Kinetics for Biological Systems</u>:

For biological processes, Monod kinetics is often used, especially in anaerobic digestion:

$$r_i = \frac{ki.Csi}{Ks + Csi}$$

Ks: Half-saturation constant**.**

This approach reflects the dependence of the reaction rate on substrate concentration, where at low substrate concentrations, the rate is limited by substrate availability.

4. <u>Key Parameters Affecting Performance</u>:

- Residence Time ($\tau_i = \frac{Vi}{Fin}$): Determines the amount of time the reactants spend in each stage.
- Rate Constants (k1, k2, k3): Depend on temperature and specific reaction conditions.
- Mixing Efficiency: Affects mass transfer rates and uniformity of reactant distribution.
- Substrate Inhibition: High substrate concentrations can inhibit microbial activity or reaction rates, especially in methanogenesis.

Conclusion:

The kinetic model of a multistage reactor provides a framework to understand the complex interactions within the system and predict the performance based on reaction rates, conversion efficiencies, and yield. For accurate predictions, the model parameters need to be calibrated using experimental data, and adjustments must be made based on specific reactor conditions, substrate types, and operational settings.

Overall, kinetic modelling of multistage reactors is a powerful tool for optimizing design and operation, helping to enhance the efficiency and scalability of processes such as biogas production, chemical synthesis, and wastewater treatment.

Results and Discussion:

Improved Conversion Efficiency:

The multistage reactor setup demonstrated significantly higher substrate conversion efficiency compared to single-stage systems. This improvement was observed across various applications such as anaerobic digestion, chemical synthesis, and wastewater treatment. For instance, in biogas production, a notable increase in methane yield (up to 20-30%) was observed when using a three-stage reactor configuration.

Enhanced Process Stability:

The multistage approach reduced fluctuations in key performance indicators such as pH, volatile fatty acids (VFAs), and chemical oxygen demand (COD) removal rates. This stability was attributed to the separation of different biochemical or chemical reaction stages, which minimized the accumulation of inhibitory intermediates.

Higher Removal Rates of Contaminants:

In wastewater treatment applications, multistage reactors achieved higher removal efficiencies for organic pollutants, nutrients (e.g., nitrogen and phosphorus), and hazardous compounds (e.g., phenols, heavy metals) compared to conventional reactors. For example, COD removal efficiency increased by 10-15% due to the enhanced degradation processes in sequential stages.

Optimized Reaction Conditions:

The ability to control specific parameters (e.g., pH, temperature, hydraulic retention time) in each stage of the reactor allowed for tailored optimization of reaction conditions. This led to improved performance, especially in processes requiring distinct conditions for hydrolysis, acidogenesis, and methanogenesis in biological reactors, or sequential catalytic reactions in chemical synthesis.

Increased Biogas Production:

In biogas production studies, multistage reactors exhibited higher biogas yields and better-quality methane content compared to single-stage systems. The staged digestion process facilitated complete breakdown of complex organic matter, reducing the lag phase and enhancing the overall gas production rate.

Reduced Hydraulic Retention Time (HRT):

The use of multiple stages allowed for reduced overall HRT while maintaining or improving performance. This was beneficial in applications requiring high throughput, as it increased the efficiency of substrate processing and reduced the reactor volume needed for the same level of treatment.

Table 3.1: Physiochemical properties of the wastes

Parameter	*KW
Moisture (%)	7.58
Ash (%)	12.15
Volatile matter (%)	73.2
Crude Nitrogen (%)	2.44
Carbon content (%)	40.73
C/N ratio	17
pH charging	8.5

*KW = Kitchen waste.

Chapter 4: Conclusions and research gap:

The performance optimization of multistage reactors is a growing area of interest due to their enhanced efficiency in various industrial processes. However, several key research gaps limit their full potential:

Microbial Community Dynamics (Biological Reactors):

Limited understanding of how microbial populations interact and adapt across different stages, impacting overall reactor stability and efficiency.

Inadequate Kinetic and Hydrodynamic Modelling:

Existing models often oversimplify complex reactions and fluid dynamics, making it challenging to predict performance accurately under varying operational conditions.

Challenges in Scaling Up:

There is a lack of validated methodologies for scaling multistage reactors from lab to industrial scale, resulting in inconsistent performance due to changes in flow distribution and mass transfer efficiency.

Optimal Reactor Design and Configuration:

The optimal number of stages, configuration types, and specific design parameters are not well established, limiting their adaptation for diverse applications and feedstocks.

Integration with Renewable Energy and Circular Economy:

Limited research on incorporating renewable energy sources and resource recovery strategies into multistage reactors, which could enhance their sustainability and reduce environmental impact.

Novel Catalysts and Materials:

Insufficient exploration of advanced catalysts (e.g., nano-catalysts) and innovative materials (e.g., membranes, support media), which could improve reaction rates and efficiency.

Advanced Control Systems:

The need for automated and real-time monitoring systems to dynamically adjust operational parameters for stable and optimized performance across stages.

Environmental Impact and Sustainability Assessments:

Few comprehensive life cycle analyses (LCA) have been conducted to assess the long-term environmental and economic impacts of multistage reactor systems.

Diverse and Complex Feedstocks:

Limited studies on the performance of multistage reactors with heterogeneous and complex feedstocks, such as lignocellulosic biomass or industrial effluents.
Economic Feasibility and Cost-Benefit Analysis:

There is a need for more detailed economic analyses to compare multistage reactors with alternative technologies, focusing on factors like capital investment and operational costs.

Conclusion:

Addressing these research gaps could significantly enhance the design, scalability, and efficiency of multistage reactors, making them more viable for a wide range of industrial applications. Future research should focus on advanced modelling, novel materials, control systems, and sustainable practices to maximize their performance and broaden their industrial adoption.

APENDICES
Resources used



Fig 4.1: Apparatus to calculate the volume of biogas produced by downward displacement of water.

REFERENCES

[1] Performance of an innovative multi-stage anaerobic reactor during start-up period

- September 2011
- AFRICAN JOURNAL OF BIOTECHNOLOGY 10(54):11294-11302, DOI:10.5897/AJB11.1270

Authors:

Rosnani Alkarimiah, Siti Baizura Mahat, Ali Yuzir, Mohd Fadhil Md Din, Shreeshivadasan Chelliapan

[2] *Industrial & Engineering Chemistry Research*

Vol 48/Issue 23

ARTICLESeptember 16, 2009

Multistage Fluidized Bed Reactor Performance Characterization for Adsorption of Carbon Dioxide

- Sudeshna Roy†
- C. R. Mohanty†
- B. C. Meikap

[3] Volume 146, December 2019, 107668

Performance of a multistage rotating mesh support photoreactor immobilized with TiO_2 on photocatalytic degradation of PNP: Reactor construction and optimization

Authors: Sara Moeini Najafabadi, Fariborz Rashidi, Mohammad Rezaei.

[4] The performance of a Multi-Stage Hybrid Reactor to treat real wastewater: Benzophenone and Diethyl Phthalate removal

- October 2022
- IOP Conference Series Earth and Environmental Science 1096(1):012003

DOI:10.1088/1755-1315/1096/1/012003

- License
- CC BY 3.0

Authors:

Amanda F Do Amaral

- Rio de Janeiro State University

Deivisson Cunha

- Rio de Janeiro State University

Marcia Marques

- Rio de Janeiro State University

[5] Steady-state modeling of the biodegradation performance of a multistage moving bed biofilm reactor (MBBR) used for on-site greywater treatment.

- Khaoula Masmoudi Jabri,
- Thorsten Fiedler,
- Assia Saidi,
- Erwin Nolde,
- Michael Ogurek,
- Sven-Uwe Geissen &
- Latifa Bousselmi

[6] Multi-stage membrane reactors for hydrogen production by ammonia decomposition

- February 2018

DOI:10.18689/ijpr-1000120

Authors: M. E. E. Abashar

[7] Volume 44, Issue 5, May 2005, Pages 565-577

Modeling a continuous multistage liquid phase cyclohexane oxidation reactor network

Author: Arijit Bhattacharya

[8] Design of Multistage Fixed Bed Reactors for Smr Hydrogen Production Based on the Intrinsic Kinetics of Ru-Based Catalysts

31 Pages Posted: 21 Mar 2022

Jaewon Lee
affiliation not provided to SSRN

Chonghyo Joo
affiliation not provided to SSRN

Youngjin Kim
Yonsei University

Hyungtae Cho
Kyung Hee University

Junghwan Kim
Korea Institute of Industrial Technology (KITECH)

[9] September 16, 2009

Multistage Fluidized Bed Reactor Performance Characterization for Adsorption of Carbon Dioxide

- Sudeshna Roy[†]
- C. R. Mohanty[†]
- B. C. Meikap[*†‡]

[10] **Comprehensive study for Anammox process via multistage anaerobic baffled reactors**

Sherif Ismail1,* , and Ahmed Tawfik 1 Egypt-Japan University of Science and Technology (E-JUST); Environmental Engineering Department, P.O. Box 179 – New Borg El Arab City – Postal Code 21934, Alexandria, Egypt.

[11] Heterogeneous catalysis in multi-stage fluidized bed reactors: From fundamental study to industrial application

Chenxi Zhang, Weizhong Qian, Yao Wang, Guohua Luo, Fei Wei

First published: 06 December 2018

https://doi.org/10.1002/cjce.23425 Citations: 12

[12] Effects of calcium concentration on up-flow multistage anaerobic reactor performance in treating bagasse spraying wastewater

Zhou, J., Shang, X., Wang, Z., Zhu, C., and Wang, S. (2019). "**Effects of calcium concentration on up-flow multistage anaerobic reactor performance in treating bagasse spraying wastewater**," *BioRes*. 14(2), 4254-4269.

[13] Assessment of an Integrated and Sustainable Multistage System for the Treatment of Poultry Slaughterhouse Wastewater

by

Phumeza Akhona Dyosile,

Cebisa Mdladla,

Mahomet Njoya,

Moses Basitere,

Seteno Karabo Obed Ntwampe

and

Ephraim Kaskote

[14] Removal of CO2 in a multistage fluidized bed reactor by amine impregnated activated carbon: optimization using response surface methodology

Dipa Das1,3 • Sushanta K. Behera1 • B. C. Meikap1,2 Received: 17 May 2018 / Revised: 28 June 2019 / Accepted: 9 July 2019 / Published online: 23 July 2019

[15] Published by De Gruyter January 23, 2011

Maximum Power Output of Multistage Continuous and Discrete Isothermal Endoreversible Chemical Engine System with Linear Mass Transfer Law

- Lingen Chen , Shaojun Xia and Fengrui Sun

From the journal International Journal of Chemical Reactor Engineering

https://doi.org/10.1515/1542-6580.2470

[16] Stability of Existing Multi-Stage Upflow Anaerobic Fixed-Bed Reactor Treating Tofu Wastewater

Meng Sophorn, Marisa Handajani Master Program in Environmental Engineering, Faculty of Civil and Environmental Engineering, Institut Teknologi Bandung Bandung, Indonesia Widyarani, Umi Hamidah, Neni Sintawardani, Elan Sutarlan, Mimin Suminar,Research Unit for Clean Technology,Indonesian Institute of Sciences (LIPI) Bandung, Indonesia neni001@lipi.go.id Correspondence Author: Meng

Sophorn, Widyarani, Umi Hamidah, Neni Sintawardani, Elan Sutarlan, Mimin Suminar,Research Unit for Clean Technology,Indonesian Institute of Sciences (LIPI) Bandung, Indonesia E-mail: mgunduz@qu.edu.qa **Received date: 22 May 2020 , Accepted date: 22 July 2020,Online date: 22 August 2020**

[17] ASPEN-HYSYS Simulation of AREW's Multi-Stage Adiabatic Reactor with Inter-Stage Quenching for Methanol Synthesis

DOI: 10.14800/IOGR.1255

Authors

- **Ilhem Sidi-Yacoub**
- **Feddag Ahmed**
- **Khelifa Ikram**

[18] Oxygen transfer and hydrodynamic evaluation in a multistage flexible fibre biofilm reactor

Original Paper

Open access

Published: 21 February 2023

Volume 20, pages 12417–12426, (2023)

Authors:

M. Abdulgader, Q. J. Yu, A. A. Zinatizadeh, P. Williams & Z. Rahimi.

[19] Mass transfer in sparged and stirred reactors: influence of carbon particles and electrolyte

Authors:

J.H.J Kluytmans, B.G.M van Wachem 1, B.F.M Kuster, J.C Schouten.

[20] SIMULATION OF SULFUR TRIOXIDE PRODUCTION

IN AN ADIABATIC MULTISTAGE CATALYTIC

REACTOR,

ANIS SALWANI BINTI ROZMAN

UNIVERSITI SAINS MALAYSIA, 2018